

# **INSTARMAC**

## **SAFETY DATA SHEET SCJ**

### **SECTION 1: Identification of the substance/mixture and of the company/undertaking**

#### **1.1. Product identifier**

**Product name** SCJ  
**Internal identification** Cold Joint Sealer

#### **1.2. Relevant identified uses of the substance or mixture and uses advised against**

#### **1.3. Details of the supplier of the safety data sheet**

**Supplier** Instarmac Group plc  
Danny Morson Way  
Birch Coppice Business Park  
Dordon, Tamworth  
Staffordshire. B78 1SE  
United Kingdom  
Tel: +44 (0) 1827 872244  
Fax: +44 (0) 1827 874466  
email@instarmac.co.uk www.instarmac.co.uk

#### **1.4. Emergency telephone number**

**Emergency telephone** +44 (0)7971 217 347 (24 hours)

### **SECTION 2: Hazards identification**

#### **2.1. Classification of the substance or mixture**

##### **Classification (EC 1272/2008)**

**Physical hazards** Aerosol 1 - H222, H229  
**Health hazards** Not Classified  
**Environmental hazards** Aquatic Chronic 3 - H412

#### **2.2. Label elements**

##### **Pictogram**



**Signal word** Danger

**Hazard statements** H222 Extremely flammable aerosol.  
H229 Pressurised container: may burst if heated  
H412 Harmful to aquatic life with long lasting effects.  
EUH208 Contains ADHESION PROMOTER. May produce an allergic reaction.

## SCJ

<b>Precautionary statements</b>	<p>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</p> <p>P211 Do not spray on an open flame or other ignition source.</p> <p>P251 Do not pierce or burn, even after use.</p> <p>P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.</p> <p>P501 Dispose of contents/ container in accordance with national regulations.</p> <p>P271 Use only outdoors or in a well-ventilated area.</p> <p>P102 Keep out of reach of children.</p> <p>P260 Do not breathe vapour/ spray.</p>
---------------------------------	--

### 2.3. Other hazards

#### SECTION 3: Composition/information on ingredients

### 3.1. Substances

Classification according to EC  
1272/2008 (CLP)

### 3.2. Mixtures

<b>PROPANE</b>		<b>10-30%</b>
CAS number: 74-98-6	EC number: 200-827-9	REACH registration number: 01-2119486944-21-0000
<b>Classification</b>		
Flam. Gas 1 - H220 Press. Gas		
<b>DIMETHYL ETHER</b>		<b>10-30%</b>
CAS number: 115-10-6	EC number: 204-065-8	REACH registration number: 01-2119472128-37-0000
<b>Classification</b>		
Flam. Gas 1 - H220 Press. Gas		
<b>WHITE SPIRIT</b>		<b>5-10%</b>
CAS number: 64742-88-7	EC number: 265-191-7	REACH registration number: 01-2119458049-33-0000
<b>Classification</b>		
Flam. Liq. 3 - H226 STOT RE 1 - H372 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411		

## SCJ

<b>BUTANE</b> <span style="float: right;"><b>5-10%</b></span>		
CAS number: 106-97-8	EC number: 203-448-7	REACH registration number: 01-2119474691-32-0000
<b>Classification</b> Flam. Gas 1 - H220 Press. Gas		
<b>ISOBUTANE</b> <span style="float: right;"><b>5-10%</b></span>		
CAS number: 75-28-5	EC number: 200-857-2	REACH registration number: 01-2119485395-27-0000
<b>Classification</b> Flam. Gas 1 - H220 Press. Gas		
<b>NAPHTHA (PETROLEUM), HYDROTREATED HEAVY; LOW BOILING POINT HYDROGEN</b> <span style="float: right;"><b>5-10%</b></span>		
CAS number: 64742-48-9	EC number: 265-150-3	REACH registration number: 01-2119480153-44-0000
<b>Classification</b> Muta. 1B - H340 Carc. 1B - H350 Asp. Tox. 1 - H304		
<b>XYLENE</b> <span style="float: right;"><b>5-10%</b></span>		
CAS number: 1330-20-7	EC number: 215-535-7	REACH registration number: 01-2119488216-32-0000
<b>Classification</b> Flam. Liq. 3 - H226 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Irrit. 2 - H315		
<b>1,2,4-TRIMETHYLBENZENE</b> <span style="float: right;"><b>1-5%</b></span>		
CAS number: 95-63-6	EC number: 202-436-9	REACH registration number: 01-2119472135-42-0000
<b>Classification</b> Flam. Liq. 3 - H226 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 STOT SE 3 - H335 Aquatic Chronic 2 - H411		

## SCJ

<b>Tall oil, reaction products with N-(2-aminoethyl)piperazine</b> <1%		
CAS number: 92062-17-4	EC number: 295-532-5	REACH registration number: 01-2119491298-25-0000
M factor (Acute) = 1	M factor (Chronic) = 1	
<b>Classification</b> Acute Tox. 4 - H302 Skin Corr. 1A - H314 Eye Dam. 1 - H318 Skin Sens. 1 - H317 Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410		
<b>CUMENE</b> <1%		
CAS number: 98-82-8	EC number: 202-704-5	REACH registration number: 01-2119473983-24-0000
<b>Classification</b> Flam. Liq. 3 - H226 STOT SE 3 - H335 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411		
<b>ETHANOL</b> <1%		
CAS number: 64-17-5	EC number: 200-578-6	REACH registration number: 01-2119457610-43-0000
<b>Classification</b> Flam. Liq. 2 - H225		
<b>METHANOL</b> <1%		
CAS number: 67-56-1	EC number: 200-659-6	REACH registration number: 01-2119433307-44-0000
<b>Classification</b> Flam. Liq. 2 - H225 Acute Tox. 3 - H301 Acute Tox. 3 - H311 Acute Tox. 3 - H331 STOT SE 1 - H370		

The full text for all hazard statements is displayed in Section 16.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

<b>General information</b>	Move affected person to fresh air at once. Get medical attention if any discomfort continues.
<b>Inhalation</b>	Move affected person to fresh air at once. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Keep affected person warm and at rest. Get medical attention immediately.

## SCJ

<b>Ingestion</b>	Do not induce vomiting. Rinse mouth thoroughly with water. Give plenty of water to drink. Give milk instead of water if readily available. Never give anything by mouth to an unconscious person. Get medical attention if any discomfort continues.
<b>Skin contact</b>	Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.
<b>Eye contact</b>	Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

#### 4.2. Most important symptoms and effects, both acute and delayed

#### 4.3. Indication of any immediate medical attention and special treatment needed

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

**Suitable extinguishing media** Extinguish with the following media: Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.

#### 5.2. Special hazards arising from the substance or mixture

**Specific hazards** Containers can burst violently or explode when heated, due to excessive pressure build-up.

#### 5.3. Advice for firefighters

**Protective actions during firefighting** Containers close to fire should be removed or cooled with water. Use water to keep fire exposed containers cool and disperse vapours.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.2. Environmental precautions

#### 6.3. Methods and material for containment and cleaning up

**Methods for cleaning up** Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Leave small quantities to evaporate, if safe to do so. Do not allow material to enter confined spaces, due to the risk of explosion. If leakage cannot be stopped, evacuate area.

#### 6.4. Reference to other sections

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

**Usage precautions** Keep away from heat, sparks and open flame. Avoid spilling. Avoid contact with skin and eyes. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level.

#### 7.2. Conditions for safe storage, including any incompatibilities

**Storage precautions** Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.

#### 7.3. Specific end use(s)

### SECTION 8: Exposure Controls/personal protection

#### 8.1. Control parameters

##### Occupational exposure limits

##### PROPANE

Long-term exposure limit (8-hour TWA): WEL 1800 Asphyxiating.

Short-term exposure limit (15-minute): WEL

## SCJ

### DIMETHYL ETHER

Long-term exposure limit (8-hour TWA): WEL 400 ppm 766 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 500 ppm 958 mg/m<sup>3</sup>

### BUTANE

Long-term exposure limit (8-hour TWA): WEL 600 ppm 1450 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 750 ppm 1810 mg/m<sup>3</sup>

### ISOBUTANE

Long-term exposure limit (8-hour TWA): OES 800 ppm

Short-term exposure limit (15-minute): OES 800 ppm

### XYLENE

Long-term exposure limit (8-hour TWA): WEL 100 ppm(Sk)

Short-term exposure limit (15-minute): WEL 150 ppm(Sk)

### 1,2,4-TRIMETHYLBENZENE

Long-term exposure limit (8-hour TWA): 25 ppm 125 mg/m<sup>3</sup>

### CUMENE

Long-term exposure limit (8-hour TWA): WEL 25 ppm(Sk) 125 mg/m<sup>3</sup>(Sk)

Short-term exposure limit (15-minute): WEL 50 ppm(Sk) 250 mg/m<sup>3</sup>(Sk)

### ETHANOL

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1920 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL

### METHANOL

Long-term exposure limit (8-hour TWA): WEL 200 ppm(Sk) 266 mg/m<sup>3</sup>(Sk)

Short-term exposure limit (15-minute): WEL 250 ppm(Sk) 333 mg/m<sup>3</sup>(Sk)

WEL = Workplace Exposure Limit

**Ingredient comments** WEL = Workplace Exposure Limits

### WHITE SPIRIT (CAS: 64742-88-7)

**Ingredient comments** WEL = Workplace Exposure Limits

#### 8.2. Exposure controls

##### Protective equipment



##### Appropriate engineering controls

Provide adequate general and local exhaust ventilation.

##### Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible.

##### Hand protection

Use protective gloves.

##### Other skin and body protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

##### Hygiene measures

Do not smoke in work area. Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

## SCJ

**Respiratory protection** No specific recommendations. Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit.

### SECTION 9: Physical and Chemical Properties

#### 9.1. Information on basic physical and chemical properties

<b>Appearance</b>	Aerosol.
<b>Colour</b>	Black.
<b>Odour</b>	Characteristic.
<b>Solubility(ies)</b>	Insoluble in water.

#### 9.2. Other information

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

#### 10.2. Chemical stability

**Stability** Stable at normal ambient temperatures.

#### 10.3. Possibility of hazardous reactions

#### 10.4. Conditions to avoid

**Conditions to avoid** Avoid heat, flames and other sources of ignition. Avoid contact with the following materials: Strong oxidising agents. Strong alkalis. Strong mineral acids.

#### 10.5. Incompatible materials

#### 10.6. Hazardous decomposition products

**Hazardous decomposition products** Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>).

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

##### Acute toxicity - dermal

**ATE dermal (mg/kg)** 22,000.0

##### Acute toxicity - inhalation

**ATE inhalation (gases ppm)** 50,000.0

**ATE inhalation (vapours mg/l)** 122.22

**ATE inhalation (dusts/mists mg/l)** 16.67

**Inhalation** May cause respiratory system irritation. Vapours may cause headache, fatigue, dizziness and nausea. Prolonged inhalation of high concentrations may damage respiratory system. Harmful by inhalation.

**Ingestion** May cause discomfort if swallowed. May cause stomach pain or vomiting. Gastrointestinal symptoms, including upset stomach.

**Skin contact** Harmful in contact with skin. Irritating to skin. Prolonged or repeated exposure may cause severe irritation. Product has a defatting effect on skin. May cause allergic contact eczema. May cause allergic contact eczema.

**Eye contact** Irritating to eyes. May cause chemical eye burns.

## SCJ

Route of entry Inhalation Skin and/or eye contact

### SECTION 12: Ecological Information

Ecotoxicity Dangerous for the environment if discharged into watercourses.

#### 12.1. Toxicity

#### 12.2. Persistence and degradability

#### 12.3. Bioaccumulative potential

#### 12.4. Mobility in soil

#### 12.5. Results of PBT and vPvB assessment

#### 12.6. Other adverse effects

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Disposal methods Empty containers must not be punctured or incinerated because of the risk of an explosion. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

### SECTION 14: Transport information

Road transport notes As supplied, this product is consigned under the Limited Quantities provisions.

#### 14.1. UN number

UN No. (ADR/RID) 1950

UN No. (IMDG) 1950

UN No. (ICAO) 1950

#### 14.2. UN proper shipping name

Proper shipping name (ADR/RID) AEROSOLS

Proper shipping name (IMDG) AEROSOLS

Proper shipping name (ICAO) AEROSOLS

Proper shipping name (ADN) AEROSOLS

#### 14.3. Transport hazard class(es)

ADR/RID class 2.1

ADR/RID label 2.1

IMDG class 2.1

ICAO class/division 2.1

#### Transport labels



#### 14.4. Packing group

ADR/RID packing group N/A

IMDG packing group N/A



## SCJ

ICAO packing group N/A

**14.5. Environmental hazards**

Environmentally hazardous substance/marine pollutant

No.

**14.6. Special precautions for user**

EmS F-D, S-U

**14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code****SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**National regulations** Health and Safety at Work etc. Act 1974 (as amended).  
The Control of Substances Hazardous to Health (Amendment) Regulations 2004  
The Aerosol Dispensers Regulations 2009 (SI 2009 No. 2824).

**Guidance** Safety Data Sheets for Substances and Preparations.  
Approved Classification and Labelling Guide (Sixth edition) L131.

**15.2. Chemical safety assessment****SECTION 16: Other information**

**General information** If further information on training is required contact Instarmac Group plc

**Revision date** 10/01/2018

**Hazard statements in full**

H220 Extremely flammable gas.  
H222 Extremely flammable aerosol.  
H225 Highly flammable liquid and vapour.  
H226 Flammable liquid and vapour.  
H229 Pressurised container: may burst if heated  
H301 Toxic if swallowed.  
H302 Harmful if swallowed.  
H304 May be fatal if swallowed and enters airways.  
H311 Toxic in contact with skin.  
H312 Harmful in contact with skin.  
H314 Causes severe skin burns and eye damage.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.  
H319 Causes serious eye irritation.  
H331 Toxic if inhaled.  
H332 Harmful if inhaled.  
H335 May cause respiratory irritation.  
H340 May cause genetic defects.  
H350 May cause cancer.  
H370 Causes damage to organs .  
H400 Very toxic to aquatic life.  
H410 Very toxic to aquatic life with long lasting effects.  
H411 Toxic to aquatic life with long lasting effects.  
H412 Harmful to aquatic life with long lasting effects.  
EUH208 Contains ADHESION PROMOTER. May produce an allergic reaction.

## SCJ

The purpose of the above information is to describe the products only in terms of health and safety requirements. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. It is the users obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date specified.

All goods are supplied in accordance with Instarmac Group plc's general conditions of sale, copies of which may be obtained by telephoning sales on 01827 872244