

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 08.06.2016

Version number 1

Revision: 13.04.2016

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name weber.tec grout resin

Safety data sheet no.: 44P2869R

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture Construction chemicals

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Saint-Gobain Weber

Dickens House

Enterprise Way

Flitwick

Bedford.

MK45 5BY

Tel: +44(0)1525 718877

Web: www.netweber.co.uk

email:sara.kelly@netweber.co.uk

1.4 Emergency telephone number: +44(0) 8703 330070 Office hours only (08.30-17.00 UK time)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08 health hazard

Repr. 2 H361d Suspected of damaging the unborn child.

STOT RE 1 H372 Causes damage to the hearing organs through prolonged or repeated exposure.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H335 May cause respiratory irritation.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.06.2016

Version number 1

Revision: 13.04.2016

Trade name weber.tec grout resin

(Contd. of page 1)

Hazard pictograms


GHS02 GHS07 GHS08

Signal word Danger

Hazard-determining components of labelling:

styrene

Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H361d Suspected of damaging the unborn child.

H335 May cause respiratory irritation.

H372 Causes damage to the hearing organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

Contains phthalic anhydride. May produce an allergic reaction.

2.3 Other hazards
Results of PBT and vPvB assessment
PBT: Does not contain PBT substances.

vPvB: Does not contain vPvB substances.

SECTION 3: Composition/information on ingredients

3.2 Chemical characterisation: Mixtures
Description: Mixture of substances listed below with non hazardous additions.

Dangerous components:

CAS: 100-42-5 EINECS: 202-851-5 Index number: 601-026-00-0	styrene ⚠ Flam. Liq. 3, H226; ⚠ Repr. 2, H361d; STOT RE 1, H372; ⚠ Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319	25 - 50%
CAS: 85-44-9 EINECS: 201-607-5 Index number: 607-009-00-4	phthalic anhydride ⚠ Resp. Sens. 1, H334; ⚠ Eye Dam. 1, H318; ⚠ Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	0.1 - 1%

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.06.2016

Version number 1

Revision: 13.04.2016

Trade name weber.tec grout resin

(Contd. of page 2)

Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

Immediately remove any clothing soiled by the product.

Remove the victim immediately from the danger area. If the patient is unwell consult a doctor and present this data sheet.

After inhalation

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

After skin contact

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

After eye contact

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

Rinse liquid should be tempered (20-30 °C).

After swallowing

Rinse out mouth with water. Do not induce vomiting. Seek medical attention and present this data sheet.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

For safety reasons unsuitable extinguishing agents Water with full jet

5.2 Special hazards arising from the substance or mixture

Can form explosive gas-air mixtures.

During heating or in case of fire poisonous gases are produced.

5.3 Advice for firefighters

Protective equipment: Wear self-contained respiratory protective device.

Additional information Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation.

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 08.06.2016

Version number 1

Revision: 13.04.2016

Trade name weber.tec grout resin

(Contd. of page 3)

6.2 Environmental precautions:

The product must not get into watercourses or into the soil.

Prevent seepage into sewage system, workpits and cellars.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Keep receptacles tightly sealed.

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

7.2 Conditions for safe storage, including any incompatibilities

Storage

Requirements to be met by storerooms and receptacles:

Store only in unopened original receptacles.

Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from oxidising agents.

Further information about storage conditions: None.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

Additional information about design of technical facilities: No further data; see item 7.

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

CAS No.	Designation of material	%	Type	Value	Unit
100-42-5	styrene				
WEL	Short-term value: 1080 mg/m ³ , 250 ppm Long-term value: 430 mg/m ³ , 100 ppm				

Additional information:

The applicable TRGS 900 (MAK list) was used as the basis for the preparation and/or revision of this safety data sheet.

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 08.06.2016

Version number 1

Revision: 13.04.2016

Trade name weber.tec grout resin

(Contd. of page 4)

8.2 Exposure controls

Personal protective equipment:

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

Do not eat, drink, smoke or sniff while working.

Use a moisturising skin cream after processing the product.

Respiratory protection:

Provide a good standard of general ventilation (not less than 3 to 5 changes of air per hour): If exposure limits are likely to be exceeded/in case of insufficient ventilation wear suitable respiratory equipment: Breathing apparatus with filter type A (organic gases and vapours filter conforming to EN14387, APF 40<1 hour, APF 200> 1 hour).

Protection of hands: Protective gloves.

Material of gloves

PVA gloves

Neoprene gloves

Nitrile rubber, NBR

Eye protection: Safety glasses with side shields. Do not wear contact lenses.

Body protection:

Protective work clothing.

Wear fire/flame resistant/retardant clothing

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Appearance:

Form:	Liquid
Colour:	Amber coloured
Odour:	Characteristic
Odour threshold:	Not determined.

pH-value: Not applicable.

Change in condition

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: 145 °C (DIN)

Flash point: 31 °C (DIN ISO 2592)

Flammability (solid, gaseous): Not applicable.

Ignition temperature: 480 °C (DIN 51794)

Decomposition temperature: Not determined.

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.06.2016

Version number 1

Revision: 13.04.2016

Trade name weber.tec grout resin

(Contd. of page 5)

Self-igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Explosion limits:	
Lower:	1.2 Vol % (DIN 51649)
Upper:	8.9 Vol % (DIN 51649)
Oxidising properties	Not determined.
Vapour pressure at 20 °C:	6 hPa (DIN 51640)
Density:	Not determined
Bulk density:	Not applicable.
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with Water:	Not miscible or difficult to mix
Segregation coefficient (n-octanol/water) log Pow:	Not determined.
Viscosity:	
dynamic:	Not determined.
kinematic:	Not determined.
Solvent separation test:	Not determined
Solvent content:	
Organic solvents:	40.1 %
EU-VOC	40.10 %
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability Stable at recommended storage conditions

Thermal decomposition / Conditions to be avoided:

No decomposition if used according to specifications.

10.3 Possibility of hazardous reactions

Reacts with strong oxidizing agents

Reacts with reducing agents

Reacts with peroxides

10.4 Conditions to avoid No further relevant information available.

10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous decomposition products:

Carbon monoxide

Carbon dioxide

GB

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 08.06.2016

Version number 1

Revision: 13.04.2016

Trade name weber.tec grout resin

(Contd. of page 6)

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

Components	Type	Value	Species
100-42-5 styrene			
Oral	LD50	5000 mg/kg	(rat)
Inhalative	LC50/4 h	24 mg/l	(rat)

Primary irritant effect:

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity

Suspected of damaging the unborn child.

STOT-single exposure

May cause respiratory irritation.

STOT-repeated exposure

Causes damage to the hearing organs through prolonged or repeated exposure.

Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: No further relevant information available.

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential No further relevant information available.

Behaviour in environmental systems:

12.4 Mobility in soil No further relevant information available.

Additional ecological information:

General notes:

Danger to drinking water if even small quantities leak into the ground.

12.5 Results of PBT and vPvB assessment

PBT: Does not contain PBT substances.

vPvB: Does not contain vPvB substances.

12.6 Other adverse effects No further relevant information available.

GB

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 08.06.2016

Version number 1

Revision: 13.04.2016

Trade name weber.tec grout resin

(Contd. of page 7)

SECTION 13: Disposal considerations

13.1 Waste treatment methods

European waste catalogue

Possible waste code. The concrete waste code depends on the source of the waste.

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

14.1 UN-Number
ADR, IMDG, IATA

UN1866

14.2 UN proper shipping name
ADR
IMDG, IATA

1866 RESIN SOLUTION, special provision 640E
RESIN SOLUTION

14.3 Transport hazard class(es)

ADR



Class

3 (F1) Flammable liquids.

IMDG, IATA



Class

3 Flammable liquids.

14.4 Packing group
ADR, IMDG, IATA

III

14.5 Environmental hazards:

Not applicable.

14.6 Special precautions for user
Danger code (Kemler):
EMS Number:

Warning: Flammable liquids.
30
F-E,S-E

**14.7 Transport in bulk according to Annex II of
Marpol and the IBC Code**

Not applicable.

Transport/Additional information:

ADR

Limited quantities (LQ)
Excepted quantities (EQ)

5L
Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml

Transport category

3

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 08.06.2016

Version number 1

Revision: 13.04.2016

Trade name weber.tec grout resin

(Contd. of page 8)

Tunnel restriction code	D/E
UN "Model Regulation":	UN 1866 RESIN SOLUTION, SPECIAL PROVISION 640E, 3, III

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

Seveso category P5c FLAMMABLE LIQUIDS

Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 May cause respiratory irritation.
- H361d Suspected of damaging the unborn child.
- H372 Causes damage to the hearing organs through prolonged or repeated exposure.

Department issuing SDS: Quality Department

Contact: Dr S. Kelly; tel. + 44 (0) 1525 718877

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

(Contd. on page 10)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.06.2016

Version number 1

Revision: 13.04.2016

Trade name weber.tec grout resin

(Contd. of page 9)

vPvB: very Persistent and very Bioaccumulative
DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)
SVHC: Substances of Very High Concern
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Resp. Sens. 1: Respiratory sensitisation – Category 1
Skin Sens. 1: Skin sensitisation – Category 1
Repr. 2: Reproductive toxicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

GB