

ROAD PAINT RAPID

Ready for car traffic in only 6 hours!



AREAS OF USE

- Car parks
- Walkways
- School playgrounds
- Private car parks

FEATURES

- Fast curing – showerproof in only 1 hour
- Can be applied at low temperatures
- Ideal for busy areas
- Medium to heavy traffic
- Apply with a roller or brush
- Suitable for external areas only

Watco Road Paint Rapid is a hard wearing chlorinated rubber based exterior coating with a matt finish, that is ideal for coating exterior concrete and asphalt. It is showerproof in only one hour and can be applied at temperatures as low as 5°C. Easy to apply by brush or roller, it offers exceptional wear resistance making it ideal for highlighting traffic areas and parking bays.

SPECIFICATION

Composition	Chlorinated rubber based exterior coating.
Number of Components	1
Number of Coats	1 usually sufficient.
Usage Interior/ Exterior	Exterior.
Application Tools	Medium pile roller, brush.
Suitable For	Bare concrete, asphalt.
Pack Size	5L
Coverage	5 litres will cover approximately 15m ² - 18m ² at 250-300 microns per pack.
Cleaning Tools	Use a thinner and cleaner based on a Xylene solvent such as Watco TH99 Cleaning Solvent.

Shelf Life	24 months in unopened container.
Cleaning	No special requirements. Keep clean with the occasional sweep.
Storage	Highly flammable. Flash point below 21°C. Store in a cool, dry and well ventilated place. Do not allow to freeze.
Safety.	Material Safety Data Sheets are available. Food products must be removed from the area during application and cure.
Principle Limitations Please contact us regarding applications not described here.	Contains Xylene and is not recommended for use on newly applied Watco Flowtop® or similar polymer reinforced screeds. If in doubt, apply to a small test area. Test before using Watco Road Paint Rapid on pre-painted surfaces.

COLOUR

Mid Grey
Black
Mid Blue
Safety Red

Samples are available on request.
While great care is taken with the colour samples shown, no guarantee can be given that they represent exactly the colours offered.

DRYING TIME	Shower Proof	Touch Dry	Walk On	Car Traffic
5°C	4 hours	1 hour	6 hours	24 hours
10°C	2 hours	40 minutes	4 hours	12 - 16 hours
20°C	1 hour	20 minutes	2 hours	6 - 12 hours

Drying times will be shortened by higher temperatures and lengthened by lower temperatures.

PREPARATION & APPLICATION

SURFACE PREPARATION

Ensure surfaces are clean, dry and free from any loose material. Remove any contamination, including dirt, oil, laitance and light to medium grease with Watco Bio-D, or for thick deposits of grease use Watco Concroff®.

APPLICATION

Easily apply by roller or brush. Make sure the lid is not left off the product for any length of time to prevent it drying out.

SAFETY

Keep container in a well-ventilated place. Keep away from sources of ignition – no smoking. Avoid contact with skin. Wear suitable protective clothing and gloves. Only for use externally or in very well-ventilated internal areas. The material and its container must be disposed of as hazardous waste. Material Safety Datasheets are available on request.



WATCO.CO.UK