

ENVIRONMENTAL PRODUCT DECLARATION

In accordance with ISO 14025:2006 and EN 15804:2012+A2:2019/AC:2021 for:

PLANITOP RASA & RIPARA ZERO **PLANITOP** RASA & RIPARA R4 ZERO





An EPD should provide current information and may be updated if conditions change. The stated validity is, therefore, subject to the continued registration and publication at www.environdec.com.

Programme: The International EPD® System; www.environdec.com Programme operator:

EPD International AB

EPD registration number:

S-P-08043

Publication date:

2023-04-03

Valid until:

2028-04-02

Revision date: Geographical

scope:

2023-09-22 Global




1. COMPANY DESCRIPTION / GOAL & SCOPE

Founded in 1937 in Milan, Italy, Mapei produces adhesives and complementary products for laying all types of floor, wall and coating materials, and also specializes in other chemical products used in the building industry, such as waterproofing products, specialty mortars, admixtures for concrete, cement additives, products for underground constructions and for the restoration of concrete and historical buildings.

There are currently 100 subsidiaries in the Mapei Group, with a total of 86 production facilities located around the world in 35 different countries and in 5 different continents. Mapei also has 32 central laboratories. Most locations are ISO 9001 and ISO 14001 or EMAScertified.

Mapei invests 12% in its company's total workforce and 5% of its turnover in Research & Development; in particular, 70% of its R&D efforts are directed to develop eco-sustainable and environmentally friendly products, which give important contribution to all major green rating systems for eco-sustainable buildings such as LEED and BREEAM.





LEED V4.1 is the latest version of Leadership in Environmental and Energy Design, an American protocol that enables buildings to be certified as eco-sustainable according to

parameters and credits described in the most widely adopted green building criteria in the world. Issued by the GBC US, it is mandatory for all LEED projects registered after October 2016.

Numerous changes have been made to the previous version: Mapei products play a part in obtaining important credits thanks to their EPD's (type III environmental declarations) and their products with very low emission of VOC.

BREEAM

Launched in the UK in 1990, **BREEAM** (BRE Environmental Assessment Method) is a protocol for sustainable building practices

adopted mainly in the United Kingdom and in Scandinavian countries with the version BREEAM NOR.

By adopting this protocol, thanks to their EPD's and very low emission of VOC, Mapei products help towards obtaining relative credits.

Furthermore, Mapei has developed a sales and technical service network with offices all over the world and offers an efficient Technical Assistance Service that is valued by architects, engineers, contractors and owners.

The goal of the study is to provide necessary data and documentation to produce an EPD according to the requirements of PCR Environdec (version 1.11, 2021-02-05) under EN 15804:2012+A2:2019/AC:2021 and to have more comprehension about the environmental impacts related to **Planitop Rasa & Ripara Zero** and **Planitop Rasa & Ripara R4 Zero** manufactured in Mapei SpA located in Latina (Italy) and Mediglia (Italy), including packaging of the finished products.

Target audiences of the study are customers and other parties with an interest in the environmental impacts of **Planitop Rasa**





& Ripara Zero and Planitop Rasa & Ripara R4 Zero. This analysis shall not support comparative assertions intended to be disclosed to the public.

Figure 1: Mediglia Plant



2. PRODUCT DESCRIPTION

Planitop Rasa & Ripara Zero and Planitop Rasa & Ripara R4 Zero are one-component, thixotropic mortars with very low emission of volatile organic compounds (EMICODE EC1 Plus) made from special hydraulic binders, fine selected aggregates, synthetic polyacrylonitrile fibres, synthetic polymers and special admixtures, according to a formula developed in the MAPEI Research & Development Laboratories.

Planitop Rasa & Ripara Zero and Planitop Rasa & Ripara R4 Zero are available in 25 Kg bags.

For more information about the product see the TDS (Technical Data Sheet) on Mapei SpA website (www.mapei.com/it).

3. CONTENT DECLARATION

The main components and ancillary materials of the products included in this EPD are the following:

Table 1: Composition referred to 1 kg of finished product with packaging

Materials	Percentage (%) by mass
Inorganic Binders	< 30% (3,07% recycled pre-consumer)
Fillers	< 70%
Additives	< 3%
Packaging	Percentage (%) by mass
PE/Paper (bag)	< 0,5%
PE/Paper (bag) LDPE (wrapping material)	< 0,5% < 0,5%
. 1 (3/	

The products do not contain a concentration higher than 0,1% (by unit weight) of either carcinogenic substances or substances of very high concern (SVHC) on the REACH Candidate List published by the European Chemicals Agency.

4. DECLARED UNIT AND REFERENCE SERVICE LIFE

The declared unit is 1 kg of finished product with packaging.

Due to the selected system boundary, the reference service life of the product is not specified.





5. SYSTEM BOUNDARIES AND ADDITIONAL TECHNICAL INFORMATION

The approach is "cradle to gate" (A1–A3) with modules C1–C4 and module D and optional modules (A1–A3 + A4 – A5 + C + D):

- A1, A2, A3 (Product stage): extraction and processing of raw materials and packaging (A1), transportation up to the factory gate (A2), manufacturing of the finished product (A3).
- A4 A5 (Construction process stage): transport of the finished product to final customers and installation into the building.

- C1, C2, C3, C4 (End of Life stage): With a collection rate of 100% as C&D waste, the transports are carried out by lorry over 100 km (C2). A recycling ratio (C3) of 70% is considered in accordance with the European Directive 2008/98/CE. The remaining 30% is landfilled (C4).
- D (Resource recovery stage): contains credits from the recycling of the product in module C3. The product can be collected and recycled for use in substitution of virgin raw aggregates.

Table 2: System boundaries

	Pro	Product stage Construction process stage					Use stage					End of life stage			Resource recovery stage			
	Raw material supply	Transport	Manufacturing	Transport	Construction installation	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal	Reuse-Recovery- Recycling-potential	
Module	A1	A2	A3	A4	A5	B1	B2	В3	В4	B5	В6	B7	C 1	C2	C3	C4	D	
Modules declared	Χ	X	Χ	Х	X	MND	MND	MND	MND	MND	MND	MND	X	Χ	X	Х	X	
Geography	ΙΤ	IT, EU	ΙΤ	EU	EU	-	-	-	-	-	-	-	EU	EU	EU	EU	EU	
Specific data			> 90%			-	-	-	-	-	-	-	-	-	-	-	-	
Variation – products			<10%			-	-	-	-	-	-	-	-	-	-	-	-	
Variation – sites			<10%			-	-	-	-	-	-	-	-	-	-	-	-	

MND: Module Not Declared





A brief description of production process is the following:

The production process starts from raw materials, that are purchased from external and intercompany suppliers and stored in the plant. Bulk raw materials are stored in specific silos and added automatically in the production mixer, according to the formula of the product. Other raw materials, supplied in bags, big bags or tanks, are stored in the warehouse and added automatically or manually in the mixer. The production is a discontinuous process, in which all the components are mechanically mixed in batches. The semi-finished product is then packaged, put on wooden pallets and stored in the finished products warehouse. The quality of final products is controlled before the sale.

Figure 2: production process detail









Table 3: Transport to the building site (A4)

Scenario information	Value	Unit
Means of transport: truck-trailer euro 5, gross weight 34-4	0 t, payload c	apacity 27 t
Diesel consumption	0,002	l/100km
Transport distance	1000	km
Capacity utilisation (including empty runs)	85	%
Gross density of products transported	~ 1400	kg/m³
Capacity utilisation volume factor	1	-

Table 4: Installation into the building (A5) for Planitop Rasa e Ripara Zero

Scenario information	Value	Unit
Ancillary materials for installation	0	kg
Water use	0,000303	m^3
Other resources use	0	kg
Electricity (Italian grid mix)	0,00063	МЈ
Waste materials on building site before waste processing, generated by the product's installation (specified by type)	0,0091 (wood) 0,001 (plastics) 0,0036 (paper)	kg
Output materials (specified by type) as result of waste processing at the building site e.g. of collection for recycling, for energy recovery, disposal (specified by route)	0,011 (disposal) 0,013 (energy recovery)	kg
Direct emission to ambient air, soil and water	0	kg





Table 5: Installation into the building (A5) for Planitop Rasa e Ripara R4 Zero

Scenario information	Value	Unit
Ancillary materials for installation	0	kg
Water use	0,000303	m³
Other resources use	0	kg
Electricity (Italian grid mix)	0,00063	МЈ
Waste materials on building site before waste processing, generated by the product's installation (specified by type)	0,0091 (wood) 0,001 (plastics) 0,0036 (paper)	kg
Output materials (specified by type) as result of waste processing at the building site e.g. of collection for recycling, for energy recovery, disposal (specified by route)	0,011 (disposal) 0,013 (energy recovery)	kg
Direct emission to ambient air, soil and water	0	kg

6. CUT-OFF RULES AND ALLOCATION

Criteria for the exclusion of inputs and outputs (cut-off rules) in the LCA, information modules and any additional information are intended to support an efficient calculation procedure. They are not applied in order to hide data. Cut-off criteria, where applied, are described in Table 6

Table 6: Cut-off criteria

Process excluded from study	Cut-off criteria	Quantified contribution from process			
A3: production (auxiliary materials)	Less than 10 ⁻⁵ kg/kg of finished product	Sensitivity study demonstrates a relative contribution lower than 0,5%			

For the allocation procedure and principles consider the following table (Table 7):

Table 7: Allocation procedure and principles

Module	Allocation Principle
Al	All data are referred to 1 kg of product Al: electricity is allocated to the specific production line
A3	All data are referred to 1 kg of packaged product A3-wastes: all data are allocated to the whole production plant





7. ENVIRONMENTAL PERFORMANCE AND INTERPRETATION



GWP

Climate change

GWPtotal - Global Warming Potential refers to the emission/presence of GHGs (greenhouse gases) in the atmosphere (mainly CO_2 , N_2O , CH_4) which contribute to the increase in the temperature of the planet. GWP-total considers:

- GWP-fossil
- GWP-biogenic
- GWP-luluc (land use and land use change)



ODP

Ozone Depletion

Ozone Depletion Potential refers to the degradation of the stratospheric layer of the ozone involved in blocking the UV component of sunrays. Depletion is due to particularly reactive components that originate from chlorofluorocarbon (CFC) or chlorofluoromethane (CFM).



Acidification

Acidification Potential refers to the emission of specific acidifying substances (i.e. NOx, SOx) in the air. These substances decrease the pH of the rainfall with predictable damages to the ecosystem.



ΕP

Eutrophication

Eutrophication Potential refers to the nutrient enrichment, which determines unbalance in ecosystems and causes the death of the fauna and decreased biodiversity in flora.

- It considers:
- EP-freshwater: acquatic freshwater
- EP-marine: acquatic marine
- EP-terrestrial



POCP

Photochemical ozone formation

The Photochemical Ozone Creation Potential is the ozone formation in low atmosphere. This is quite common in the cities where a great amount of pollutants (like VOC and NOx) are emitted every day (industrial emissions and vehicles). It is mainly diffused during the summertime.



Depletion of abiotic resources – minerals and metals

Abiotic Depletion Potential elements refers to the depletion of the mineral resources.

ADP minerals&metals



Depletion of abiotic resources - fossil fuel

Abiotic Depletion Potential fossil fuel refers to the depletion of the fossil fuel resources.

ADP - fossil



Water use

It expresses the potential deprivation of water, that consists in not having the water needs satisfied.

WDP





The following tables show the environmental impacts for the products considered according to the requirements of EN15804:2012+A2:2019/AC:2021. The results are referred to the declared unit (see § 4). The additional environmental indicators are not declared.

PLANITOP RASA & RIPARA ZERO - PLANITOP RASA & RIPARA R4 ZERO

(1 kg of product with packaging)

Planitop Rasa & Ripara Zero and Planitop Rasa & Ripara R4 Zero have similar environmental loads with differences lower than 10%. According to the GPI – General Program Instruction (ref. §9.3), the results are shown as average in a single set of tables.

Table 8: Planitop Rasa & Ripara Zero and Planitop Rasa & Ripara R4 Zero: Potential environmental impact – mandatory indicators according to EN 15804 referred to 1 kg of product with packaging

Indicator	Unit	Al-A3	A4	A5	С1	C2	C3	C4	D
GWP _{TOTAL}	(kg CO₂ eq.)	2,52E-01	4,97E-02	3,61E-02	2,13E-03	8,40E-03	1,78E-02	4,84E-03	-1,10E-02
GWP _{FOSSIL}	(kg CO₂ eq.)	2,82E-01	4,92E-02	1,63E-02	2,09E-03	8,31E-03	1,95E-03	4,81E-03	-1,09E-02
GWP _{BIOGENIC}	(kg CO₂ eq.)	-3,04E-02	1,73E-04	1,99E-02	3,36E-05	2,91E-05	1,59E-02	1,62E-05	-3,34E-05
GWP _{LULUC}	(kg CO₂ eq.)	9,94E-05	3,31E-04	5,52E-07	7,46E-07	5,59E-05	9,00E-06	8,88E-06	-4,21E-06
ODP	(kg CFC 11 eq.)	5,31E-09	4,83E-15	4,66E-15	4,28E-14	8,15E-16	2,90E-15	1,13E-14	-1,45E-14
AP	(mol H⁺ eq.)	8,80E-04	1,49E-04	9,67E-06	2,90E-06	2,60E-05	1,00E-05	3,41E-05	-1,12E-05
EP _{FRESHWATER}	(kg P eq.)	9,83E-06	1,76E-07	5,65E-09	1,02E-08	2,96E-08	5,59E-09	8,16E-09	-6,31E-09
EP _{MARINE}	(kg N eq.)	7,89E-05	6,73E-05	3,59E-06	8,54E-07	1,17E-05	4,59E-06	8,72E-06	-4,72E-06
EP _{TERRESTRIAL}	(mol N eq.)	8,63E-04	7,56E-04	4,07E-05	9,19E-06	1,32E-04	5,07E-05	9,59E-05	-5,21E-05
POCP	(kg NMVOC eq.)	3,40E-04	1,34E-04	9,49E-06	2,26E-06	2,32E-05	1,25E-05	2,65E-05	-1,23E-05
ADP _{MINERALS&METALS} *	(kg Sb eq.)	2,58E-06	4,95E-09	1,08E-10	6,09E-10	8,36E-10	2,16E-09	4,93E-10	-9,03E-10
ADP _{FOSSIL} *	(MJ)	2,23E+00	6,45E-01	1,11E-02	2,96E-02	1,09E-01	3,81E-02	6,30E-02	-1,72E-01
WDP*	(m³ world eq.)	9,08E-03	5,50E-04	1,51E-02	8,50E-04	9,28E-05	3,76E-04	5,28E-04	-9,27E-05

GWP_{TOTAL}: Global Warming Potential total; GWP_{FOSSIL}: Global Warming Potential fossil fuels; GWP_{BIOGENIC}: Global Warming Potential biogenic; GWP_{LULUC}: Global Warming Potential land use and land use change; ODP: Depletion Potential of the stratospheric Ozone layer; AP: Acidification Potential; EP_{FRESHWATER}: Eutrophication Potential, freshwater; EP_{MARINE}: Eutrophication Potential, marine; EP_{TERRESTRIAL}: Eutrophication Potential, terrestrial; POCP: Formation potential of tropospheric ozone; ADP_{MINERALSSMETALS}: Abiotic Depletion Potential for non-fossil resources; ADP_{FOSSIL}: Abiotic Depletion Potential for fossil resources; WDP: Water Deprivation Potential.

Table 9: Planitop Rasa & Ripara Zero and Planitop Rasa & Ripara R4 Zero: Potential environmental impact – additional mandatory and voluntary indicators referred to 1 kg of product with packaging

Indicator	Unit	A1-A3	A4	A5	с1	C2	C3	C4	D
GWP-GHG	(kg CO ₂ eq.)	2,71E-01	4,85E-02	1,62E-02	2,07E-03	8,20E-03	1,91E-03	4,74E-03	-1,08E-02

GWP-GHG: The indicator includes all greenhouse gases included in GWP-total but excludes biogenic carbon dioxide uptake and emissions and biogenic carbon stored in the product. This indicator is thus equal to the GWP indicator originally defined in EN 15804:2012+A1:2013.





^{*}The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high or as there is a limited experienced with the indicator

Table 10: Planitop Rasa & Ripara Zero and Planitop Rasa & Ripara R4 Zero: Use of resources referred to 1 kg of product with packaging

Indicator	Unit	A1-A3	A4	A5	C1	C2	C3	C4	D
PERE	МЈ	5,62E-01	4,47E-02	2,85E-03	2,54E-02	7,55E-03	3,06E-03	9,46E-03	-7,90E-03
PERM	МЈ	2,17E-01	0,00E+00						
PERT	МЈ	7,76E-01	4,47E-02	2,85E-03	2,54E-02	7,55E-03	3,06E-03	9,46E-03	-7,90E-03
PENRE	МЈ	2,37E+00	6,48E-01	1,11E-02	2,96E-02	1,09E-01	3,81E-02	6,31E-02	-1,72E-01
PENRM	МЈ	3,97E-02	0,00E+00						
PENRT	МЈ	2,27E+00	6,48E-01	1,11E-02	2,96E-02	1,09E-01	3,81E-02	6,31E-02	-1,72E-01
SM*	kg	3,07E-02	0,00E+00						
RSF	МЈ	9,73E-02	0,00E+00						
NRSF	МЈ	1,86E-01	0,00E+00						
FW	m³	3,20E-04	5,17E-05	3,52E-04	2,24E-05	8,72E-06	1,07E-05	1,60E-05	-2,39E-05

PERE: Use of renewable primary energy excluding renewable primary energy resources used as raw materials; **PERM**: Use of renewable primary energy resources used as raw materials; **PERT**: Total use of renewable primary energy resources (primary energy and primary energy resources used as raw materials); **PERRE**: Use of non-renewable primary energy resources used as raw materials; **PERRM**: Use of non-renewable primary energy resources used as raw materials; **PERRM**: Use of non-renewable primary energy resources (primary energy and primary energy resources used as raw materials); **SM**: Use of secondary material; **RSF**: Use of renewable secondary fuels; **NRSF**: Use of non-renewable secondary fuels; **PERRM**: Net use of fresh water.

Table 11: Planitop Rasa & Ripara Zero and Planitop Rasa & Ripara R4 Zero: Waste production and output flows referred to 1 kg of product with packaging

Indicator	Unit	A1-A3	A4	A5	C1	C2	C3	C4	D
HWD	kg	1,20E-02	3,43E-12	1,10E-12	6,27E-12	5,79E-13	4,77E-13	3,24E-12	-3,46E-11
NHWD	kg	6,41E-03	1,06E-04	1,31E-02	3,29E-05	1,78E-05	1,01E-05	3,23E-01	-1,55E-02
RWD	kg	1,65E-05	1,20E-06	4,24E-07	1,33E-06	2,03E-07	5,02E-07	7,02E-07	-7,70E-07
Components for re-use	kg	0,00E+00							
Materials for recycling	kg	1,11E-02	0,00E+00						
Materials for energy recovery	kg	0,00E+00							
Exported energy, electricity	МЈ	0,00E+00							
Exported energy, thermal	МЈ	0,00E+00							

HWD: Hazardous waste disposed; NHWD: Non-Hazardous waste disposed; RWD: Radioactive waste disposed

Table 12: Planitop Rasa & Ripara Zero and Planitop Rasa & Ripara R4 Zero: Information on biogenic carbon content at the factory gate referred to 1 kg of product with packaging

Biogenic Carbon Content	Unit	Quantity
Biogenic carbon content in product	kg C	0,00E+00
Biogenic carbon content in packaging	kg C	4,96E-03





^{*} Referred only to 1 kg of product without packaging

Tables from 7 to 12 show absolute results for all the environmental categories considered.

The main contribution to the environmental impact categories in the product life cycle comes from **module A1** (extraction and processing of raw materials). Its relative contribution is over 50% in all the categories and in most of them it's higher than 90%. Referring to the biogenic carbon stored in product and packaging, the negative impacts on GWP_{BIOGENIC} (in **modules A1** and **A3**) is compensated in the **modules A5** and **C3**, when the product and packaging reach their end of life. A minor contribution in GWP_{FOSSIL} and ADP_{FOSSIL} is due to the manufacturing process (**Module A3**).

An overview about the average contribution to the different modules considered in the system boundaries are shown in Table 13.

Table 13: Some environmental impacts of Planitop Rasa & Ripara Zero and Planitop Rasa & Ripara R4 Zero.

ENVIRONMEN IMPACT	ITAL	Al-A3	11111 A4	A5	c ₁	C2	C3	(1) C4	D	TOT
CLIMATE CHANGE		2,52E-01	4,97E-02	3,61E-02	2,13E-03	 8,40E-03	1,78E-02		-1,10E-02	3,60E-01 kg CO ₂ eq.
ACIDIFICATION	io io io	8,80E-04	1,49E-04	 9,67E-06	 2,90E-06	 2,60E-05	 1,00E-05	 3,41E-05	-1,12E-05	1,10E-03 mol H+ eq.
DEPLETION OF ABIOTIC RESOURCES (FOSSIL)		2,23E+00	6,45E-01	 1,11E-02	 2,96E-02	1,09E-01	 3,81E-02	 6,30E-02	-1,72E-01	2,95E+00 MJ
WATER USE		1,40E-02		1,51E-02	8,50E-02	 9,28E-05	 3,76E-04	5,28E-04	 -9,27E-05	3,14E-02 m³ world eq.

More details about electrical mix used in this EPD, is shown below:

	Data source	GWP-GHG	Unit
Residual electricity grid mix (IT) – 2020	AIB	0,525*	kg CO ₂ -eqv/kWh

*CML2001 - Aug. 2016





8. DATA QUALITY

Table 14: Data quality

Dataset & Geographical reference	Database (source)	Temporary reference			
A1; A3					
Inorganic Binders (IT)	Sphera Database; S-P-00880	2021-2026			
Fillers (IT)	Sphera Database; Ecoinvent 3.8	2021			
Additives (EU)	Ecoinvent 3.8	2021			
Residual electricity grid mix (IT)	Sphera Database	2021			
Packaging components (EU)	Sphera Database; Ecoinvent 3.8;	2021			
	A2				
Truck, Euro 5, 27t payload (GLO)	Sphera Database	2021			
Light train, gross tonne weight 500t / 363t payload (GLO)	Sphera Database	2021			
Oceanic ship (27500 DWT - GLO)	Sphera Database	2021			
Diesel for transport (EU)	Sphera Database	2018			
Heavy Fuel Oil (EU)	Sphera Database	2018			
Electricity grid mix (EU)	Sphera Database	2018			
	A4				
Truck, Euro 5, 27t payload (GLO)	Sphera Database	2021			
Diesel for transport (EU)	Sphera Database	2018			
	A5				
Tap water from surface water	Sphera Database	2021			
Commercial waste in municipal waste incineration plant	Sphera Database	2021			
Inert matter on landfill	Sphera Database	2021			
Electricity grid mix (EU)	Sphera database	2018			
C1-C4					
Truck (EURO 6 - 9,3 ton payload – GLO)	Sphera Database	2021			
Electricity grid mix (EU)	Sphera Database	2018			
Diesel for transport (EU)	Sphera Database	2018			
Construction waste dumping (EU)	Sphera Database	2021			
Construction waste treatment (EU)	Sphera Database	2021			

All data included in table above refer to a period between 2005 and 2021; the most relevant ones are specific from supplier, while the others (i.e. transport and minor contribution dataset), come from European and global databases.

All dataset are not more than 10 years old according to EN 15804 §6.3.8.2 "Data quality requirements". The Quality level concerning datasets used in the EPD can be considered as "very good" or "good" according to Annex E of the EN 15804 (current version).

Primary data concern the year 2021 and represent the whole annual production.

9 ADDITIONAL INFORMATION

9.1 CO₂ offset

Total CO_2 emissions measured throughout the entire life cycle have been offset through the purchasing of certified carbon credits in support of renewable energy and forestry protection projects.



9.2 Recycled Content

Products	Recycled material content (Pre-Consumer)			
Planitop Rasa e Ripara Zero	3,07%			
Planitop Rasa e Ripara R4 Zero	3,07%			





9.3 Disassembly

The finished product is potentially suitable for disassembly through selective demolition.

9.4 End of life / Recyclability

Our Multiply bags are recyclable up to 90% (ATICELCA class A) according to UNI 11743. The finished products can be recycled at the end of life, after demolition, according to the national laws.



9.5 Biogenic Content

For Planitop Rasa e Ripara Zero and Planitop Rasa e Ripara R4 Zero the biogenic carbon content in packaging at the factory gate referred to 1 kg of product with packaging is 4,96E-03.

9.6 VOC emission

Volatile Organic Compounds (VOC) special tests and evidence have been carried out on the two products, according to ISO 16000 parts 3, 6, 9 and 11 and EN 16516.

The products have been evaluated in emission chambers, in order to detect their VOC emissions after 3 and 28 days storage in the ventilated chambers, according to GEV (Gemeinschaft Emissionskontrollierte Verlegewerkstoffe, Klebstoffe und Bauprodukte e.V.) test method.

The following product meets the requirements for the emission class EMICODE® **EC1**PLUS, as "very low emission", released by GEV:

- Planitop Rasa e Ripara Zero: license number 16291
- Planitop Rasa e Ripara R4 Zero: license number 16292

Next table describes the limits for the EMICODE® EC1PLUS class:

Table 15: EC1PLUS VOC limits

	3 days µg/m³	28 days µg/m³
TVOC (C6-C16)	≤ 750 µg/m³	≤ 60 µg/m³
TSVOC (C16-C22)		≤ 40 µg/m³
C1A-C1B substances	Total ≤ 10 µg/m³	Single substance ≤ 1 µg/m³
Formaldehyde/ acetaldehyde	≤ 50 µg/m³	
Sum of formaldehyde/acetaldehyde	≤ 50 ppb	
sum of non-assessable VOCs		≤ 40
R value		≤1

10. DIFFERENCES VERSUS PREVIOUS VERSION

Chapter 9.1 has been updated. Editorial changes.





11. VERIFICATION AND REGISTRATION

The EPD owner has the sole ownership, liability, and responsibility for the EPD.

EPDs within the same product category but from different programmes may not be comparable. EPDs of construction products may not be comparable if they do not comply with EN 15804. For further information about comparability, see EN 15804 and ISO 14025.

CEN standard EN15804 served as the Core Product Category Rules (PCR)			
PCR:	PCR 2019:14 Construction products (EN 15804:A2), Version 1.11, 2021-02-05, UN CPC code 54		
PCR review was conducted by:	The Technical Committee of the International EPD® System. See www.environdec.com/TC for a list of members. Review chair: Claudia A. Peña, University of Concepción, Chile. The review panel may be contacted via the Secretariat www.environdec.com/contact.		
Independent third-party verification of the declaration and data, according to ISO 14025:2006:	☑ EPD Process Certification☐ EPD Verification		
Third party verifier:	Certiquality S.r.l. Number of accreditation: 003H rev15		
Accredited or approved by:	Accredia		
Procedure for follow-up of data during EPD validity involves third-party verifier			

12. REFERENCES

- EN 15804: SUSTAINABILITY OF CONSTRUCTION WORKS -ENVIRONMENTAL PRODUCT DECLARATIONS - CORE RULES FOR THE PRODUCT CATEGORY OF CONSTRUCTION PRODUCTS
- EUROPEAN DIRECTIVE 2008/98/EC
- EUROPEAN RESIDUAL MIXES VERSION 1.0, 2021-05-31 (AIB: ASSOCIATION OF ISSUING BODIES)
- GENERAL PROGRAMME INSTRUCTIONS OF THE INTERNATIONAL EPD® SYSTEM. VERSION 3.01
- ISO 14025 ENVIRONMENTAL LABELS AND DECLARATIONS -TYPE III ENVIRONMENTAL DECLARATIONS - PRINCIPLES AND PROCEDURES
- ISO 14044 ENVIRONMENTAL MANAGEMENT LIFE CYCLE ASSESSMENT REQUIREMENTS AND GUIDELINES
- PCR 2019:14 CONSTRUCTION PRODUCTS (EN 15804: A2), UN CPC CODE 54; VERSION 1.11





CONTACT INFORMATION

EPD owner:



Mapei SpA

www.mapei.it

LCA author:



Mapei SpA

www.mapei.it;

Environmental Sustainability Office

Programme operator:



EPD International AB

Address: EPD International AB Box 210 60 SE-100 31 Stockholm Sweden

Website: www.environdec.com E-mail: info@environdec.com



HEAD OFFICE MAPEI SpA Via Cafiero, 22 - 20158 Milan Tel. +39-02-37673.1 mapei.com mapei@mapei.it

