



## Technical Datasheet Arbo AFS Primer

Arbo AFS Primer is a one part, solvent containing, air-drying polyacrylate/silane blend based primer.

### Main Applications

Recommended for use in conjunction with the Arbo Membrane System for use with Arbo SA and Arbo Membrane Adhesive. Recommended for the priming of porous surfaces such as sound concrete, cementitious boards, timber and other porous surfaces.

Arbo AFS Primer is easy to apply and very convenient for large surface area applications.

#### *NB*

*For lightweight, highly porous block work and brickwork, 2 coats of AFS Primer are recommended (or one coat of Arbo 2650 primer)*

*Due to the variety of substrates available it is recommended that a trial application is carried out before construction commences.*

*Adshead Ratcliffe Technical Service Department can advise if adhesion tests are required to new, untested substrates.*

### Application Instructions

The joint surfaces must be clean, dry and free from all contamination. The surfaces should be degreased using the appropriate Arbo Cleaner. Apply Arbo AFS Primer using a clean dry brush or roller and allow to dry for a least 1 hour but not more than 8 hours before applying the sealant.

All joint preparation and priming should be carried out in accordance with BS 8000 Part 16, the British Standard for the sealing of joints in buildings using sealants.

### Technical Data

Colour: Colourless

Density: Approx 0.95 g/cm<sup>3</sup>

Application Temperature: + 5 ° C to + 30° C

Cleaning: Tools must be carefully cleaned immediately after use with an appropriate cleaner.

### Storage Life

6 months in original unopened package stored in a cool, dry place out of direct sunlight.

First Issue: 16.11.11

Page 1 of 2



### **Health & Safety**

Arbo AFS Primer is labelled as Harmful and Highly Flammable. For full information please refer to Material Safety Data Sheet.

### **Packaging**

Arbo AFS Primer is supplied in 1 litre containers.

### **Coverage**

Approximately 6 square metres per litre dependent upon porosity of the substrate.

**Important:** The information in this leaflet is given in good faith and based on results gained from experience and tests. However, all recommendations or suggestions are made without guarantee since the conditions of use are beyond our control. Goods are supplied subject to the Company's terms and conditions of sales, a copy of which is available on request.

Adshead Ratcliffe. Derby Road, Belper, Derbyshire DE56 1WJ, England.

**Telephone: 01773 826661**

**Fax: 01773 821215**

**[www.arbo.co.uk](http://www.arbo.co.uk)**