

INTRODUCTION

Arbostrip F42 is a medium density foam compression sealant coated one side with a strong acrylic pressure-sensitive adhesive.

MAIN APPLICATIONS

Recommended for use as a weather seal, dust seal, or in glazing of internal doors and screens. It is also suitable for make and break joints and the weather proofing and draught sealing of opening lights, ventilators and doors.

It is not recommended for use in expansion joints.

APPLICATION INSTRUCTIONS

Joint preparation: All surfaces must be clean, dry and grease free. Arbostrip F42 is supplied in roll form with a paper interleaf on the non-adhesive face. This allows the tape to be applied directly without stretching.

STORAGE LIFE

12 months. The conditions under which the tape is stored can affect it's performance. Storage should be in a dry, well ventilated area protected from exposure to direct sunlight.

TECHNICAL DATA

Application temperature:	+5°C to + 45°C
Service temperature:	-30°C to +70°C
Chemical resistance:	Excellent resistance to weather, oxidation, salt water, dilute alkalis and acids. Poor resistance to some solvents.
UV resistance:	Excellent
Hardness:	40 shore 00
Force required to compress:	3.5N/cm ²
Compression required for weather seal	30%
Compression deflection:	2.0N/cm ²
Compression set:	10% maximum.
Water Absorbtion:	5% maximum
Available sizes:	12 x 3mm, 9 x 3mm, 6 x 3mm.
Colours:	Black

ACCESSORIES

Cleaners

Arbo Cleaner No.17- 1 Litre Tin (Xylene based – not suitable for use with plastics or delicate finishes)

Arbo Cleaner No.16 1 Litre tin
(Alcohol based)

PACKAGING

Arbostrip F42 is supplied in single rolls with a paper interleaf.

20m roll, 12 x 3mm – 15 rolls per box

20m roll, 9 x 3mm – 20rolls per box

20m roll, 6 x 3mm – 30 rolls per box

N.B. Tolerances – Thickness $\pm 10\%$, Width $\pm 1\text{mm}$

Important: The information in this leaflet is given in good faith and based on results gained from experience and tests. However, all recommendations or suggestions are made without guarantee since the conditions of use are beyond our control. Goods are supplied subject to the Company's terms andconditions of sales, a copy of which is available on request.