

## ASPHALT BINDER

Binds, strengthens and transforms old asphalt

### AREAS OF USE

- Car parks
- Walkways
- School playgrounds
- Private car parks



### FEATURES

- Binds and strengthens loose or eroded asphalt
- Gives the appearance of freshly laid asphalt
- Hides ingrained dust and cement spills from building work etc.
- Helps protect against water ingress and frost damage
- Avoids disruptive and costly repairs
- Vastly improves the appearance of premises
- Easy to apply with a broom

Watco Asphalt Binder is a quick and easy way to bind and protect asphalt surfaces. It transforms old asphalt so it looks brand new. If your asphalt is crumbling, faded and stained, there's no need to rip it up. Watco Asphalt Binder binds and strengthens old asphalt in a way that looks freshly laid.

### SPECIFICATION

Composition	Fast drying, water based bitumen compound.	Coverage	5 litres will cover approximately 10m <sup>2</sup> - 20m <sup>2</sup> , depending upon the surface texture.
Number of Components	1	Drying Time	Approximately 2 - 4 hours at 15°C - 25°C. The area can be put back into use as soon as it is completely tack free.
Finish	Dries black with a slight surface sheen.	Shelf Life	6 months in unopened container.
Number of Coats	1 usually sufficient.	Storage	Store away from possible sources of heat or ignition. Do not allow to freeze.
Usage Interior/ Exterior	Exterior.	Safety	Material Safety Data Sheets are available. Food products must be removed from the area during application and cure.
Application Tools	Broom.		
Suitable For	Asphalt.		
Pack Size	5L		

### COLOUR

**Black**

While great care is taken with the colour sample shown, no guarantee can be given that it represents exactly the colour offered.

### PREPARATION & APPLICATION

#### SURFACE PREPARATION

The surface should be dry and free from any loose material. Moss etc., should be removed by scraping, wire brushing and/or jet washing and the surface allowed to dry.

#### APPLICATION

Give the container a thorough shake since some settlement can occur during storage. The product can be applied using a texturing roller or by a soft broom. If a texturing roller is selected, the solution should be applied from a roller tray and worked out well using the roller to avoid the product pooling and reducing coverage.

If using a soft broom, simply pour the product directly from the container onto the surface. The product can then be worked around the required area, sweeping the broom in every direction. (Please note that the bristles can stiffen after a while making the sweeping action more difficult.)

During and immediately after application the product will appear brown, but will become to a uniform black as it dries. If the substrate is fairly porous, a second coat can be applied as soon as the first coat is tack free.

#### SAFETY

Wear gloves and protective eyewear in case of splashes. If the product comes into contact with eyes, flush with water for 15 minutes and seek medical advice. Material Safety Datasheets are available on request.



**WATCO.CO.UK**

Watco UK Limited, Eastgate Court, 195-205 High Street, Guildford, Surrey, GU1 3AW, UK Tel: 01483 418 418 Fax: 01483 428 888 [www.watco.co.uk](http://www.watco.co.uk) E-mail: [sales@watco.co.uk](mailto:sales@watco.co.uk)