

## ASPHALT EASY FILL

A convenient, easy to use crack filler and sealant

### AREAS OF USE

- Asphalt
- Concrete
- Metal
- Stone
- Brick



### FEATURES

- Easy to use
- Flexible, moves with substrate (+/-5%)
- Remains flexible for years
- Protects against damage from water erosion

Watco Asphalt Easy Fill is a flexible rubberised filler that seals cracks in asphalt, helps protect against damage caused by water ingress and erosion. It can also be used to fill joints and cracks in concrete surfaces. Also bonds to metal, stone and brick. It fits a standard skeleton gun for quick clean repairs.

### SPECIFICATION

|                          |                                       |
|--------------------------|---------------------------------------|
| Composition              | Rubberised bitumen emulsion.          |
| Appearance               | Black.                                |
| Number of Components     | 1                                     |
| Usage Interior/ Exterior | Exterior & interior.                  |
| Application Tools        | Skeleton gun.                         |
| Suitable For             | Asphalt, tarmac, metal, stone, brick. |
| Pack Size                | 310ml                                 |
| Coverage                 | See chart opposite.                   |
| Drying Time              | 24 hours in dry conditions.           |
| Shelf Life               | 24 months in unopened container.      |

|   |   |
|---|---|
| Storage   | Store in shaded dry conditions between 5°C - 25°C. Do not allow to freeze.                      |
| Principle Limitations<br>Please contact us regarding applications not described here. | Not suitable for use on EPDM rubber roofs. Check compatibility with other surfaces if in doubt. |

### COVERAGE RATES

Linear metres per 310ml cartridge.

| Width (mm) | 6   | 10  | 15  | 20  | 25  |
|------------|-----|-----|-----|-----|-----|
| 6mm deep   | 8.6 | 5.2 | 3.4 | 2.6 | 2.1 |
| 10mm deep  | 5.2 | 3.1 | 2.0 | 1.5 | 1.2 |
| 12mm deep  | 4.3 | 2.6 | 1.7 | 1.3 | 1.0 |

### PREPARATION & APPLICATION

#### SURFACE PREPARATION

Ensure that all surfaces are clean, dry and free from any contaminants that may cause adhesion problems.

#### APPLICATION

Cut the tip from the cartridge avoiding damage to the thread. Cut the nozzle at an angle of 45° and screw on to the cartridge. The tube fits a standard skeleton gun.

#### SAFETY

Material Safety Data Sheets are available. In common with all solvent based products, food should be kept away during application and curing.



WATCO.CO.UK

Watco UK Limited, Eastgate Court, 195-205 High Street, Guildford, Surrey, GU1 3AW, UK Tel: 01483 418 418 Fax: 01483 428 888 [www.watco.co.uk](http://www.watco.co.uk) E-mail: [sales@watco.co.uk](mailto:sales@watco.co.uk)