

CP507 & CP508

NATURAL QUARTZ SAND



KEY BENEFITS SUMMARY

- Improves characteristics of finished flooring
- Used to promote adhesion between MMA Primers and MMA Resins
- Tested and approved for use with MMA Resins

PRODUCT INFORMATION

Description

CP507 is a medium natural quartz sand.
CP508 is a medium-fine natural quartz sand.

Usage / Purpose

CP507 Medium Sand is used as a blinding for CP215 MMA Flexible Base Coat. CP508 Medium Fine Sand is used as a blinding for CP150 MMA Concrete Primer and CP100 Polyurea Asphalt Primer.

Colour

Natural quartz

Packaging

25 kg bag

Availability

Direct from tremco illbruck (see bottom of leaflet for address and telephone details).

Protective Equipment

Use in well ventilated conditions and ensure all recommended protective equipment is worn during handling & use of this product. DO NOT BREATHE DUST. For full recommendation, refer to safety data sheet.

Method of Application

For application details please contact tremco illbruck Technical Sales Representative.

Health & Safety Precautions

Safety data sheet must be read and understood before use.

Technical Service

tremco illbruck has a team of experienced Technical Sales Representatives who provide assistance in the selection and specification of products. For more detailed information, service and advice, please call Customer Services on 01942 251400.

Guarantee / Warranty

tremco illbruck products are manufactured to rigid standards of quality. Any product which has been applied (a) in accordance with tremco illbruck written instructions and (b) in any application recommended by tremco illbruck, but which is proved to be defective, will be replaced free of charge.

No liability can be accepted for the information provided in this leaflet although it is published in good faith and believed to be correct.

tremco illbruck Limited reserves the right to alter product specifications without prior notice, in line with Company policy of continuous development and improvement.

TECHNICAL DATA

PROPERTY	RESULT
Composition	Graded silicon dioxide
Particle Size	
CP507	0.7 - 1.2 mm
CP508	0.3 - 0.7 mm
Density (DIN 51757 at +20°C)	2.85 g/cm ³
pH	7
Storage	Store in cool, dry, shaded conditions
Shelf Life	12 months when stored in dry conditions in original unopened containers