



SAFETY DATA SHEET CEM TOP XD

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name CEMTOP XD

Product number 1120000UK9

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Cementitious overlay

1.3. Details of the supplier of the safety data sheet

Supplier Fosroc Limited
 Drayton Manor Business Park
 Coleshill Road
 Tamworth
 Staffordshire
 B78 3XN
 England
 Tel: +44 (0) 1827 262222
 Fax: +44 (0) 1827 262444
 enquiryuk@fosroc.com

1.4. Emergency telephone number

Emergency telephone +44 (0) 1827 265 279 (Monday-Sunday 24 hours a day)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Skin Irrit. 2 - H315 Eye Irrit. 2 - H319

Environmental hazards Not Classified

Human health Dust or splashes from the mixture may cause permanent eye damage. Dust may irritate the respiratory system. Symptoms following overexposure may include the following: Coughing. Dust has an irritating effect on moist skin. Prolonged contact with moist or wet product may cause burns. Frequent inhalation of dust over a long period of time increases the risk of developing lung diseases.

Environmental The product will harden into a solid mass in contact with water and moisture. The resultant material is not biodegradable.

2.2. Label elements

CEM TOP XD

Hazard pictograms



Signal word

Warning

Hazard statements

H315 Causes skin irritation.

H319 Causes serious eye irritation.

Precautionary statements

P264 Wash contaminated skin thoroughly after handling.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P362+P364 Take off contaminated clothing and wash it before reuse.

P501 Dispose of contents/ container in accordance with national regulations.

Supplementary precautionary statements

P302+P352 IF ON SKIN: Wash with plenty of water.

P321 Specific treatment (see medical advice on this label).

P332+P313 If skin irritation occurs: Get medical advice/ attention.

P337+P313 If eye irritation persists: Get medical advice/ attention.

2.3. Other hazards

This substance is not classified as PBT or vPvB according to current EU criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

QUARTZ (SiO₂)	30-60%
CAS number: 14808-60-7	EC number: 238-878-4
No. REACH: Exempt of registration	
Classification	
Not Classified	

Classification

Not Classified

CALCIUM CARBONATE	10-30%
CAS number: 471-34-1	EC number: 207-439-9
Classification	
Not Classified	

Classification

Not Classified

HIGH ALUMINA CEMENT (HAC)	5-10%
CAS number: 65997-16-2	EC number: 266-045-5
Classification	Classification (67/548/EEC or 1999/45/EC)
Not Classified	-

Classification

Not Classified

GYPSUM HEMIHYDRATE	5-10%
CAS number: 26499-65-0	
Classification	
Not Classified	

Classification

Not Classified

CEM TOP XD

CALCIUM HYDROXIDE			<1%
CAS number: 1305-62-0	REACH registration number: 01-2119475151-45-XXXX		
Classification Skin Irrit. 2 - H315 Eye Dam. 1 - H318 STOT SE 3 - H335			

2,6-DI-tert-BUTYL-4-METHYLPHENOL			<1%
CAS number: 128-37-0	M factor (Chronic) = 1		
Classification Aquatic Chronic 1 - H410			

FORMALDEHYDE			<1%
CAS number: 50-00-0	EC number: 200-001-8	REACH registration number: 01-2119488953-20	
Classification Acute Tox. 3 - H301 Acute Tox. 3 - H311 Acute Tox. 3 - H331 Skin Corr. 1B - H314 Eye Dam. 1 - H318 Skin Sens. 1 - H317 Muta. 2 - H341 Carc. 1B - H350 STOT SE 3 - H335			

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	No personal protective equipment is needed for first aid responders. First aid workers should avoid contact with wet cement or wet cement containing preparations.
Inhalation	Move affected person to fresh air at once. Dust in throat and nasal passages should clear spontaneously. Get medical attention if irritation persists or later develops, or if discomfort, coughing or other symptoms persist.
Ingestion	Do not induce vomiting. Rinse mouth thoroughly with water. Give plenty of water to drink. Give milk instead of water if readily available. Never give anything by mouth to an unconscious person. Get medical attention immediately.
Skin contact	After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water. Get medical attention promptly if symptoms occur after washing.
Eye contact	Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. Continue to rinse for at least 15 minutes. Get medical attention. Show this Safety Data Sheet to the medical personnel.

CEM TOP XD

4.2. Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	Frequent inhalation of dust over a long period of time increases the risk of developing lung diseases.
Ingestion	No specific symptoms known.
Skin contact	May have an irritating effect on moist skin after prolonged contact, or may cause dermatitis after repeated contact. Prolonged skin contact with wet preparation may cause serious burns without pain being felt, including through clothing.
Eye contact	Eye contact may cause serious and potentially irreversible injuries.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically.
-----------------------------	------------------------

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	The product is not flammable. Use fire-extinguishing media suitable for the surrounding fire.
-------------------------------------	---

5.2. Special hazards arising from the substance or mixture

Specific hazards	Water used for fire extinguishing, which has been in contact with the product, may be corrosive. No unusual fire or explosion hazards noted.
-------------------------	--

Hazardous combustion products	No known hazardous decomposition products.
--------------------------------------	--

5.3. Advice for firefighters

Protective actions during firefighting	No specific firefighting precautions known.
Special protective equipment for firefighters	Use protective equipment appropriate for surrounding materials.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Use work methods which minimize dust production. Avoid contact with eyes and prolonged skin contact. Wear protective clothing as described in Section 8 of this safety data sheet. Avoid inhalation of dust.
-----------------------------	--

6.2. Environmental precautions

Environmental precautions	Collect and dispose of spillage as indicated in Section 13. Do not discharge into drains or watercourses or onto the ground.
----------------------------------	--

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	Collect powder using special dust vacuum cleaner with particle filter or carefully sweep into suitable waste disposal containers and seal securely. Dry material: Collect powder using special dust vacuum cleaner with particle filter. Alternatively, damp powder with fine spray (to avoid dust formation) and remove slurry. Place into container and allow to solidify before disposal as described in section 13. Wet material: Clean up wet material and place in a container. Allow to dry and solidify before disposal as described in section 13.
--------------------------------	---

6.4. Reference to other sections

Reference to other sections	For personal protection, see Section 8. For waste disposal, see section 13.
------------------------------------	---

CEM TOP XD

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Avoid contact with skin and eyes. Avoid generation and spreading of dust. Avoid inhalation of dust. Mechanical ventilation or local exhaust ventilation may be required. Change contaminated clothing. Do not eat, drink or smoke when using the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry and cool place. Unsuitable container materials: Aluminium. Seal opened containers and use up as soon as possible. To be stored out of reach of children in its original packaging in a dry place.

Storage class Miscellaneous hazardous material storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

QUARTZ (SiO₂)

Long-term exposure limit (8-hour TWA): WEL 0,05 mg/m³

CALCIUM CARBONATE

Long-term exposure limit (8-hour TWA): 10 mg/m³ inhalable dust

Long-term exposure limit (8-hour TWA): 4 mg/m³ respirable dust

HIGH ALUMINA CEMENT (HAC)

Long-term exposure limit (8-hour TWA): 10 mg/m³ inhalable dust

Long-term exposure limit (8-hour TWA): 4 mg/m³ respirable dust

GYPSUM HEMIHYDRATE

Long-term exposure limit (8-hour TWA): WEL 10 mg/m³ inhalable dust

Long-term exposure limit (8-hour TWA): 4 mg/m³ respirable dust

CALCIUM HYDROXIDE

Long-term exposure limit (8-hour TWA): WEL 5 mg/m³

2,6-DI-tert-BUTYL-4-METHYLPHENOL

Long-term exposure limit (8-hour TWA): WEL 10 mg/m³

FORMALDEHYDE

Long-term exposure limit (8-hour TWA): WEL 2 ppm 2.5 mg/m³

Short-term exposure limit (15-minute): WEL 2 ppm 2.5 mg/m³

WEL = Workplace Exposure Limit

2,2-DIMETHYL 1,3-PROPANEDIOL (CAS: 126-30-7)

DNEL

Workers - Inhalation; Long term systemic effects: 35 mg/m³

Workers - Dermal; Long term systemic effects: 10 mg/kg bw/day

General population - Inhalation; Long term systemic effects: 8.7 mg/m³

General population - Dermal; Long term systemic effects: 5 mg/kg bw/day

General population - Oral; Long term systemic effects: 5 mg/kg bw/day

PNEC

- Fresh water; 5 mg/l

- marine water; 0.5 mg/l

- STP; 20 mg/l

CEM TOP XD

CALCIUM HYDROXIDE (CAS: 1305-62-0)

PNEC General population - Soil; 1080 mg/l

LITHIUM CARBONATE(ANHYDROUS) (CAS: 554-13-2)

DNEL

- Workers - Dermal; Acute: 100 mg/kg
- Workers - Inhalation; Acute: 30 mg/m³
- Workers - Dermal; Long term : 64,3 mg/kg
- Workers - Inhalation; Long term : 10 mg/m³
- General population - Dermal; Acute: 19,23 mg/kg
- General population - Inhalation; Acute: 28,92 mg/m³
- General population - Oral; Long term : 6,43 mg/kg
- General population - Dermal; Long term : 64,3 mg/kg
- General population - Inhalation; Long term : 9,64 mg/m³

PNEC

- Fresh water; 9 mg/l
- marine water; 0,9 mg/l
- Sediment (Freshwater); 35,2 mg/kg
- Sediment (Marinewater); 3,52 mg/kg
- Soil; 1,76 mg/kg

2,6-DI-tert-BUTYL-4-METHYLPHENOL (CAS: 128-37-0)

DNEL

- Workers - Inhalation; Long term systemic effects: 3.5 mg/m³
- Workers - Dermal; Long term systemic effects: 0.5 mg/kg/day

PNEC

- Fresh water; 0.199 µg/l
- marine water; 0.0199 µg/l

FORMALDEHYDE (CAS: 50-00-0)

DNEL

- Workers - Inhalation; Long term systemic effects: 9 mg/m³
- Workers - Inhalation; Long term local effects: 0,5 mg/m³
- Workers - Inhalation; Short term local effects: 1 mg/m³
- Workers - Dermal; Long term systemic effects: 240 mg/kg/day
- Workers - Dermal; Long term local effects: 37 µg/cm²

PNEC

- Fresh water, marine water; 0.47 mg/l
- STP; 0.19 mg/l
- Water, Intermittent release; 4,7 mg/l
- Sediment (Freshwater), Sediment (Marinewater); 2,44 mg/kg
- Soil; 0,21 mg/kg

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Atmospheric levels of dust must be maintained within the Occupational Exposure Limit. Where mechanical methods are inadequate or impractical, appropriate personal protective equipment must be used.

Personal protection

Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.

CEM TOP XD

Eye/face protection	The following protection should be worn: Chemical splash goggles. (conform EN 166)
Hand protection	It is recommended that gloves are made of the following material: Butyl rubber. Nitrile rubber. Barrier cream applied before work may make it easier to clean the skin after exposure, but does not prevent absorption through the skin. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material.
Other skin and body protection	Use barrier creams to minimise skin contact. Wear appropriate clothing to prevent repeated or prolonged skin contact.
Hygiene measures	<p>This product contains silica sands.</p> <p>The grain size distribution of silica sand present means that it is not classified as hazardous. However, any respirable crystalline dust generated by secondary processing may cause health effects.</p> <p>Prolonged and /or massive inhalation of respirable crystalline silica dust may cause lung fibrosis, commonly referred to as silicosis. Principal symptoms of silicosis are cough and breathlessness.</p> <p>Occupational exposure to respirable crystalline silica dust should be monitored and controlled.</p>
Respiratory protection	Wear a respirator fitted with the following cartridge: Particulate filter, type P2.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Dusty powder.
Colour	Grey.
Odour	Odourless.
Odour threshold	Not relevant.
pH	pH (concentrated solution): >12
Melting point	>1250°C
Initial boiling point and range	Not applicable.
Flash point	Not applicable.
Evaporation rate	Not applicable.
Evaporation factor	Not applicable.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	The product is not flammable.
Other flammability	Not applicable.
Vapour pressure	Not applicable.
Vapour density	Not applicable.
Relative density	Not determined.
Bulk density	Not determined.
Solubility(ies)	Slightly soluble in water. Hardens in contact with water.
Partition coefficient	Not determined.
Auto-ignition temperature	Not determined.

CEM TOP XD

Decomposition Temperature	Not determined.
Viscosity	Not applicable.
Explosive properties	Not considered to be explosive.
Explosive under the influence of a flame	Not considered to be explosive.
Oxidising properties	The mixture itself has not been tested but none of the ingredient substances meet the criteria for classification as oxidising.
Comments	Information given is applicable to the product as supplied.

9.2. Other information

Other information	No data available.
--------------------------	--------------------

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	When mixed with water, hardens to form a stable mass that is not reactive in normal conditions.
-------------------	---

10.2. Chemical stability

Stability	Stable under the prescribed storage conditions. Stable at normal ambient temperatures and when used as recommended.
------------------	---

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	None known. Will not polymerise.
---	----------------------------------

10.4. Conditions to avoid

Conditions to avoid	Water, moisture.
----------------------------	------------------

10.5. Incompatible materials

Materials to avoid	Acids. Chemically-active metals.
---------------------------	----------------------------------

10.6. Hazardous decomposition products

Hazardous decomposition products	No known hazardous decomposition products.
---	--

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Skin sensitisation

Skin sensitisation	Some individuals may exhibit eczema upon exposure to wet cement caused either by the high pH which induces irritant contact dermatitis, or by an immunological reaction to soluble Cr (VI) which elicits allergic contact dermatitis. The cement contains a soluble Cr (VI) reducing agent and as long as the mentioned period of effectiveness is not exceeded, a sensitising effect is not expected.
---------------------------	--

Inhalation	Irritating to respiratory system. Inflammation of the nasal mucous membrane by exposure to cement dust.
-------------------	---

Ingestion	May cause irritation of mouth, throat and digestive tract.
------------------	--

Skin contact	This product is strongly irritating. Prolonged contact may cause burns. May cause sensitisation by skin contact.
---------------------	--

CEM TOP XD

Eye contact Irritating and may injure eye tissue if not removed promptly.

Acute and chronic health hazards Repeated and/or prolonged contact may lead to dermatitis.

Toxicological information on ingredients.

CALCIUM HYDROXIDE

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 7,300.0

Species Mouse

ATE oral (mg/kg) 7,300.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 2,500.0

Species Guinea pig

ATE dermal (mg/kg) 2,500.0

2,6-DI-tert-BUTYL-4-METHYLPHENOL

Carcinogenicity

IARC carcinogenicity IARC Group 3 Not classifiable as to its carcinogenicity to humans.

FORMALDEHYDE

Acute toxicity - oral

Notes (oral LD₅₀) LD₅₀ > 200 mg/kg, Oral, Rat

ATE oral (mg/kg) 100.0

Acute toxicity - dermal

Notes (dermal LD₅₀) LD₅₀ 270 mg/kg, Dermal, Rabbit

ATE dermal (mg/kg) 300.0

Acute toxicity - inhalation

Notes (inhalation LC₅₀) CL50 0,58 mg/l, 4 hours, Gas. Rat

Carcinogenicity

IARC carcinogenicity IARC Group 1 Carcinogenic to humans.

Inhalation Prolonged inhalation of high concentrations may damage respiratory system. May cause respiratory system irritation.

Ingestion Toxic if swallowed.

Skin contact Corrosive to skin. May cause sensitisation or allergic reactions in sensitive individuals.

Eye contact Causes serious eye damage.

SECTION 12: Ecological information

CEM TOP XD

Ecotoxicity The product is not expected to be hazardous to the environment.

Ecological information on ingredients.

QUARTZ (SiO₂)

Ecotoxicity The product is not expected to be hazardous to the environment.

12.1. Toxicity

Toxicity Not considered toxic to fish.

Acute aquatic toxicity

Acute toxicity - fish Not determined.
The product is not expected to be hazardous to the environment. The addition of cements to water will, however, cause the pH to rise and may therefore be toxic to aquatic life in some circumstances.

Ecological information on ingredients.

2,2-DIMETHYL 1,3-PROPANEDIOL

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 48 hours: >10000 mg/l, Freshwater fish

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: >500 mg/l, Daphnia magna

Acute toxicity - aquatic plants EC₅₀, 72 hours: >500 mg/l, Algae

CALCIUM HYDROXIDE

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: 33.884 mg/ml mg/l, Fish

2,6-DI-tert-BUTYL-4-METHYLPHENOL

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: 0.199 mg/l, Fish

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 0.48 mg/l, Daphnia magna

Chronic aquatic toxicity

M factor (Chronic) 1

FORMALDEHYDE

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: 41 mg/l, Brachydanio rerio (Zebra Fish)

Acute toxicity - aquatic invertebrates EC₅₀, 24 hours: 42 mg/l, Daphnia magna

Acute toxicity - aquatic plants EC₅₀, 72 hours: 3,48 - 4,89 mg/l, Algae

12.2. Persistence and degradability

Persistence and degradability The product is not biodegradable.

CEM TOP XD

Ecological information on ingredients.

2,2-DIMETHYL 1,3-PROPANEDIOL

Biodegradation - Degradation >70%: 28 days
The substance is readily biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential The product is not bioaccumulating.

Partition coefficient Not determined.

Ecological information on ingredients.

2,2-DIMETHYL 1,3-PROPANEDIOL

Bioaccumulative potential BCF: < 9,

12.4. Mobility in soil

Mobility The product hardens to a solid, immobile substance. The product is not volatile but may be spread by dust-raising handling.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

Ecological information on ingredients.

2,2-DIMETHYL 1,3-PROPANEDIOL

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current EU criteria.

12.6. Other adverse effects

Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Do not empty into drains, sewers or water courses. Cement that has exceeded its shelf life: when demonstrated that it contains more than 0.0002% Cr (VI), the product shall not be used other than in controlled closed and totally automated processes. It may be recycled and/or treated again with a reducing agent.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Note that fully cured material is not considered as hazardous waste.

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

CEM TOP XD

14.3. Transport hazard class(es)

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78
and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations	The Control of Substances Hazardous to Health Regulations 2002 (SI 2002 No. 2677) (as amended).
EU legislation	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended). Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended). Commission Regulation (EU) No 2015/830 of 28 May 2015.
Guidance	Workplace Exposure Limits EH40. Respiratory protective equipment at work (HSG53).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

General information	For professional users only. Only trained personnel should use this material.
Revision comments	NOTE: Lines within the margin indicate significant changes from the previous revision.
Revision date	31/05/2019
Revision	4a
Supersedes date	22/05/2017
SDS number	12427

CEM TOP XD

Hazard statements in full

H301 Toxic if swallowed.
H311 Toxic in contact with skin.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H331 Toxic if inhaled.
H335 May cause respiratory irritation.
H341 Suspected of causing genetic defects.
H350 May cause cancer.
H410 Very toxic to aquatic life with long lasting effects.

The information on this data sheet represents our current data and is reliable provided that the product is used under the prescribed conditions and in accordance with the application specified on the packaging and/or in the technical guidance literature. Any other use of the product which involves using the product in combination with any other product or any other process is the responsibility of the user.