



Denso Flashing Tape

A cold applied self adhesive aluminium backed flashing in tape form

Composition

Denso Flashing Tape is comprised of a high melting point polymer bitumen adhesive laminated to an aluminium/polyester laminate with grey weatherproof lacquer finish. The adhesive surface is protected by a release coated plastic film which is discarded during use.

Uses

Denso Flashing Tape is used for waterproofing of roof to wall and other building joints.

Service Temperature: 80°C (maximum short term)

Characteristics

Denso Flashing Tape is:

- resistant to water, water vapour and gases,
- conformable over a wide temperature range, and
- adherent to metal, concrete, brick, slate, tile, painted wood, glass and rigid plastics.

Application

See *Instructions for use* for additional detail.

Recommended primer: Denso Flashing Tape Primer

Application Temperature: 5°C to 40°C

Availability

Denso Flashing Tape is available in 10 meter rolls. Other sizes may be available on request.

Storage conditions

Store in a cool and dry place in original packaging.

Waste material

Please do not discard waste material, including packaging, in the surrounding environment. Please follow all relevant legislation for disposal.

Typical Properties

Breaking Strength	4.5 N/mm	ASTM D1000
Elongation @ Break	100%	ASTM D1000
Adhesion Strength	4.5 N/mm	ASTM D1000
Thickness	1.0 mm	
Weight	1.0 kg/m ² average	

Note: Overpainting the flashing requires a good quality water based exterior paint. The use of other sealants in conjunction with the flashing tape is not necessary. Silicone based sealants and solvent based paints are not normally suitable for use in contact with the adhesive compound.

Important: Winn & Coales (Denso) Ltd pursue a policy to develop and continually improve all of our products and therefore the information given in this data sheet is intended as a general guide and does not constitute a warranty of specification. However, our sales personnel are committed to assist the user in establishing the suitability of the product for its intended purpose and additional specific information is available on request. Winn & Coales (Denso) Ltd operate a Quality Management System registered to BS EN ISO 9001 (BSI Certificate no. FM01548) and an Environmental Management System registered to BS EN 14001 (BSI Certificate 583748).

Winn & Coales (Denso) Ltd
Denso House, Chapel Road,
London SE27 0TR, United Kingdom



Tel: +44 (0) 20 8670 7511
Fax: +44 (0) 20 8761 2456
Email: mail@denso.net Web: www.denso.net