

LEADERS IN CORROSION PREVENTION AND SEALING TECHNOLOGY

TECHNICAL DATA SHEET





OVER 130 YEARS SERVICE TO INDUSTRY

Denso PVC Self-Adhesive Tape 200

Composition

Denso PVC Self-Adhesive Tape 200 consists of a PVC film coated on one side with self-adhesive

Uses

Denso PVC Self-Adhesive Tape 200 is a selfadhesive tape used as an outer layer to provide additional mechanical and UV protection to the Denso range of anti-corrosion tapes.

Characteristics

Denso PVC Self-Adhesive Tape 200 is:

- highly conformable,
- highly elongated at break,
- suitable for hand application, and
- suitable for machine application.

Application

Wrap spirally over the Denso anti-corrosion tape layer, ensuring sufficient tension and overlap while avoiding creases and folds.

Testina

Ensure the application has:

- sufficient tension,
- no creases or folds, and
- sufficient overlap.

Service Temperature

Denso PVC Self-Adhesive Tape 200 is recommended for service in temperatures of -5°C to +60°C with a short-term peak of +80°C.

Availability

Denso PVC Self-Adhesive Tape 200 is available in black or yellow 33 metre rolls in widths from 50 mm to 300 mm.

Storage conditions

Store in a cool and dry place in original packaging.

Waste material

Please do not discard waste material, including packaging, in the surrounding environment. Please follow all relevant legislation for disposal.

Typical Properties

Thickness	0.19 mm	ASTM D1000
Tensile strength at break	3.5 N/mm	ASTM D1000
Elongation at break	150%	ASTM D1000
Tear strength	11 N	ASTM D1004
Adhesion Peel strength		ASTM D1000
To self	0.3 N/mm	(24 h)
Dielectric strength (double layer)	16 kV	ASTM D1000

Important: Winn & Coales (Denso) Ltd pursue a policy to develop and continually improve all of our products and therefore the information given in this data sheet is intended as a general guide and does not constitute a warranty of specification. However, our sales personnel are committed to assist the user in establishing the suitability of the product for its intended purpose and additional specific information is available on request. Winn & Coales (Denso) Ltd operate a Quality Management System registered to BS EN ISO 9001 (BSI Certificate no. FM01548) and an Environmental Management System registered to BS EN 14001 (BSI Certificate 583748).

> Page 1 of 1 Revision date: 25/06/2018

Winn & Coales (Denso) Ltd Denso House, Chapel Road, London SE27 0TR, United Kingdom



Tel: +44 (0) 20 8670 7511 Fax: +44 (0) 20 8761 2456

Email: mail@denso.net Web: www.denso.net