The Construction Products EU Exit Regulations 2020 No. 1359

No. FTL036 UKCA 0086 CPR 753276

Cemprotec 851F

1. Unique identification code of the product type:

BS EN 1504-2:2004 Surface Protection System.

2. Type, batch or serial number of any other element allowing identification of the construction product as required under Article 11(4):

See batch number and date of manufacture on packaging.

3. Intended use of uses of the construction product, in accordance with the applicable designated technical specification, as foreseen by the manufacturer:

Cement based surface coating for protection against ingress (PIC): Crack bridging and flexible systems without trafficking.

4. Name, registered trade mark and contact address of manufacturer as required pursuant Article 11(5):

Flexcrete Technologies Limited Tomlinson Road, Leyland Lancashire, PR25 2DY

9. Declared Performance:

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

Not applicable.

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 2+

7. In case of the declaration of performance concerning a construction product covered by a designated standard:

EN 1504-2

The UK Approved Body 0086 undertook the initial inspection of type testing, manufacturing plant, factory production control and the continuous surveillance, assessment and evaluation of factory production control under System 2+ and issued Certificate of Conformity of factory production control.

Reaction to fire has been assessed and determined by type testing carried out by approved test laboratory 0833 under System 3.

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

Not applicable.

Essential Characteristics	Performance	Test Standard	Designated Standard
Permeability to CO2	Equivalent to 100mm of concrete	BS EN 1062-6	BS EN1504-2: 2004
Permeability to Water Vapour	Sp < 5m (Class I Permeable to water vapour)	BS EN ISO 7783-2	
Capillary Absorption	w ≤ 0.1 kg.m ⁻² .h ⁻⁰⁵ (Class III)	BS EN 1062-3	
Static Crack Bridging	Class A3 >500µm	BS EN 1062-7	
Adhesive Bond	≥ 0.8 MPa (Crack Bridging and Flexible systems without trafficking.	BS EN 1542	
Thermal Compatibility	> 0.8 MPa (Crack Bridging and Flexible systems without trafficking.	BS EN 13687-1	
Dangerous Substances	COMPLIES	CLAUSE 5.4	
Reaction to Fire	Euroclass A2-s1, d0	BS EN 13501-1	
Chloride Ion Diffusion	ТВС	UK METHOD	

10.Declaration:

The performance of the product identified above is in conformity with the set of declared performance in Section 9. This declaration of performance is issued, in accordance with The Construction Products (Amendment etc.) (EU Exit) Regulations 2020 No.1359, under the sole responsibility of the manufacturer identified above in Section 4.

Signed for and on behalf of the manufacturer by:

Paul Hutton - Technical Manager Leyland 01/12/22



