

## The Construction Products EU Exit Regulations 2020 No. 1359

No. FTL031 UKCA 0086 CPR 753276

### Monolevel RM

#### 1. Unique identification code of the product type:

BS EN 998-1 One coat render (OC).

#### 2. Type, batch or serial number of any other element allowing identification of the construction product as required under Article 11(4):

See batch number and date of manufacture on packaging.

#### 3. Intended use or uses of the construction product, in accordance with the applicable designated technical specification, as foreseen by the manufacturer:

One coat spray/float applied render for external and internal application to walls, soffits and columns.

#### 4. Name, registered trade mark and contact address of manufacturer as required pursuant Article 11(5):

Flexcrete Technologies Limited  
Tomlinson Road, Leyland  
Lancashire, PR25 2DY

#### 5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

Not applicable.

#### 6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 4

#### 7. In case of the declaration of performance concerning a construction product covered by a designated standard:

BS EN 998-1

Reaction to fire has been assessed and determined by type testing carried out by notified test laboratory 0833 under System 3.

#### 8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

Not applicable.

#### 9. Declared Performance:

Essential Characteristics	Performance	Test Standard	Designated Standard
Dry Bulk Density	1900-1950 kg.m <sup>3</sup>	BS EN 1015-10	BS EN 998-1: 2010
Compressive Strength	CSIV: ≥ 6MPa	BS EN 1015-11	
Adhesion after Weathering Cycles	> 2.0MPa FP B/C Strong Substrate > 0.4MPa FP C Weak substrate	BS EN 1015-21	
Capillary Absorption	W2: ≤ 0.2kg.m <sup>-2</sup> .min <sup>-0.5</sup>	BS EN 1015-18	
Water permeability on relevant substrates after weathering	≤ 1ml.cm <sup>-2</sup> .48h <sup>-1</sup>	BS EN 1015-21	
Water Vapour permeability coefficient	μ < 15	BS EN 1015-19	
Reaction to Fire	Euroclass A2-s1, d0	BS EN 13501-1	

#### 10. Declaration:

The performance of the product identified above is in conformity with the set of declared performance in Section 9. This declaration of performance is issued, in accordance with The Construction Products (Amendment etc.) (EU Exit) Regulations 2020 No.1359, under the sole responsibility of the manufacturer identified above in Section 4.

#### Signed for and on behalf of the manufacturer by:



**Paul Hutton - Technical Manager**  
Leyland 01/12/22