

## HIGH VISIBILITY PAINT

A fluorescent virtually solvent free paint for horizontal or vertical surfaces



### AREAS OF USE

- Kerbs, step edges and trip hazards etc.
- Walkways and playgrounds

### FEATURES

- Special fluorescent pigments offer excellent visibility
- Can be applied to damp surfaces
- Suitable for light to medium traffic
- Excellent resistance to UV and weathering

### DESCRIPTION

Watco High Visibility Paint is ideal for highlighting hazards such as kerbs, trip hazards, step edges, etc. Use also for line marking, walkways and playgrounds.

### SPECIFICATION

Composition	Water based acrylic paint.
Number of Components	1
Finish	Low to mid sheen depending upon substrate and number of coats applied.
Number of Coats	1 usually required.
Usage Interior/ Exterior	Interior & exterior.
Application Tools	Short pile roller or brush.
Suitable For	Concrete, stone, brick, masonry, asphalt and similar porous surfaces.
Pack Size	2.5L
Coverage	2.5 litres covers approximately 10m <sup>2</sup> - 15m <sup>2</sup> per coat depending on the texture of the substrate. Application to rough or textured surfaces will greatly reduce coverage and extend drying time.

Drying Time	Will dry in approximately 24 hours to accept light traffic, but allow 48 hours before bringing the area back into full use. Cold, damp or humid weather will delay drying.
Shelf Life	24 months in unopened container.
Cleaning Tools	Clean applicators in warm soapy water.
Storage	Store in cool, dry conditions away from direct sunlight.
Safety	All product labels provide general safety information. Material Safety Data Sheets are available. Food products must be removed from the area during application and curing.
Principle Limitations Please contact us regarding applications not described here.	Do not apply in areas which will be constantly under water. It is not photoluminescent (i.e. it will not glow in the dark).

### COLOUR

**Fluorescent Yellow**

### PREPARATION & APPLICATION

#### SURFACE PREPARATION

Watco High Visibility Paint can be applied to asphalt, tarmac, porous concrete, masonry, bricks and blockwork. Ensure the surface is clean, sound and dry (slightly damp is acceptable). Watco Bio-D is a virtually solvent free degreaser which can be used on most surfaces. Watco High Visibility Paint can be applied to existing paint providing all poorly bonded material is removed and glossy surfaces are dulled using abrasive paper.

#### APPLICATION

Apply Watco High Visibility Paint by brush or medium pile type roller. One coat is generally sufficient although a second coat may be required on very porous or very rough surfaces. Avoid applying too thickly. Do not apply externally if rain or frost is forecast or if the temperature is below 10°C. The second coat should be applied after approximately 1 hour.

In exceptional temperature conditions advice should be obtained from Watco's Technical Department.



**WATCO.CO.UK**

Watco UK Limited, Eastgate Court, 195-205 High Street, Guildford, Surrey, GU1 3AW, UK Tel: 01483 418 418 Fax: 01483 428 888 [www.watco.co.uk](http://www.watco.co.uk) E-mail: [sales@watco.co.uk](mailto:sales@watco.co.uk)