

Ancillary Products

Hydroswell Bentosteel Technical Data Sheet

Galvanised steel wire mesh for secure installation of Hydroswell Bentostrip

Field of application

Secure installation of Hydroswell Bentostrip in horizontal and vertical applications.

Advantages

Easy to install.

Description

Galvanised steel wire mesh for secure installation of Hydroswell Bentostrip in horizontal and vertical applications.

Application

Install Bentosteel over the Hydroswell Bentostrip strip. Secure Hydroswell Bentostrip and Bentosteel by nailing (1 nail every 250mm).

Technical data/properties

Wire gauge 0,9mm Mesh grid 10,6 by 10,6mm Section 25,5 by 9mm

Appearance

Galvanised steel wire mesh.

Consumption

1 metre Bentosteel per linear metre Hydroswell Bentostrip.

Packaging

Bentosteel: package of 30 x 1 metre.

Storage

Unlimited in a dry and cool place.

Health & Safety

No special recommendations necessary.

Page 1 of 1

SMR PROJECTS LIMITED Xypex House, Beaumont Close, t. 01295 279747 Banbury, Oxfordshire, OX16 1TG Co Reg. No. 4276384

e. info@smrxypex.co.uk w. smrxypex.co.uk VAT No 812 0766 53