

LOGCO

Logco Lithium EP2 Grease

Multi Purpose Grease

Description

Premium quality multipurpose grease formulated for use in all anti-friction and plain bearings subject to high load conditions. Used extensively for applications in the industrial and automotive markets.

Advantages

Extreme pressure and anti-wear performance
High degree of corrosion protection.
Extremely versatile multipurpose grease.

Application

Can be applied manually, by grease gun or via a central lubrication system designed for and capable of pumping NLGI No. 2 grease.

It is essential, as with all greases that checks are carried out on the compatibility of the new grease with grease applied previously. If in doubt about compatibility it is advised that the bearings be purged of the old grease prior to application of the new grease. Never over pack bearings with grease. Always check with bearing manufacturer as to the quantity of grease required to pack a bearing with.

Technical Data

Appearance	Smooth Grease
Colour	Dark Brown
Worked Penetration (IP50)	265—295
NLGI Classification	2
Dropping Point (IP312)	185c (Min)
Operating Temperature Range	-20 to +140c

L

O

G

C

O

Health & Safety

See relevant health and safety sheet.

Packaging

Logco Lithium EP2 Grease is available in 400g cartridges and 12.5kg kegs.

Storage

Logco Lithium EP2 should be stored away from direct sunlight and in a dry area.

Important Note

Whilst all reasonable care is taken in compiling technical data on the Company's products, all recommendations or suggestions regarding the use of such products are made without guarantee, since the conditions of use are beyond the control of the Company. It is the responsibility of the customer to satisfy himself that each product is fit for the purpose for which he intends to use it, that the actual conditions of use are suitable, and that in the light of our continual research and development programme the information relating to each product has not been superseded.