

according to Regulation (EC) No 1907/2006

Lokfix E55S, Comp. A

Revision date: 22.08.2018 Product code: SDS30 Page 1 of 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Lokfix E55S, Comp. A

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Adhesive mortar for fastening elements A-component (resin)

Uses advised against

no restriction

1.3. Details of the supplier of the safety data sheet

Company name: Fosroc International Ltd

Street: Drayton Manor Business Park, Coleshill Road

Place: UK-B78 3XN Tamworth, Staffordshire

Telephone: +44 (0) 1827 262222 Telefax: +44 (0) 1827 262444

e-mail: enquiryuk@fosroc.com

1.4. Emergency telephone +44 (0) 1827 265279 (24 hours, 7 days)

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Respiratory or skin sensitisation: Skin Sens. 1

Specific target organ toxicity - single exposure: STOT SE 3

Hazard Statements:

May cause an allergic skin reaction. May cause respiratory irritation.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

Ethylene dimethacrylate;

Methacrylic acid, monoester with propane-1,2-diol

Signal word: Warning

Pictograms:



Hazard statements

H317 May cause an allergic skin reaction. H335 May cause respiratory irritation.

Precautionary statements

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulation.



according to Regulation (EC) No 1907/2006

Lokfix E55S, Comp. A

Revision date: 22.08.2018 Product code: SDS30 Page 2 of 10

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Reg	ulation (EC) No. 1272/2008 [CLF	P]	
97-90-5	5 Ethylene dimethacrylate			
	202-617-2	607-114-00-5	01-2119965172-38	
	Skin Sens. 1, STOT SE 3; H317	7 H335		
27813-02-1	Methacrylic acid, monoester with propane-1,2-diol			5 - < 10 %
	248-666-3		01-2119490226-37	
	Eye Irrit. 2, Skin Sens. 1; H319	H317		
38668-48-3	1,1'-(p-Tolylimino)dipropan-2-o			< 1 %
	254-075-1		01-2119980937-17	
	Acute Tox. 2, Eye Irrit. 2, Aquat	ic Chronic 3; H300 H319 H412		

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Take off immediately all contaminated clothing and wash it before reuse.

After inhalation

Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

After contact with skin

Take off immediately all contaminated clothing and wash it before reuse.

Medical treatment necessary.

After contact with eves

Rinse immediately carefully and thoroughly with eye-bath or water. In case of eye irritation consult an ophthalmologist.

After ingestion

Rinse mouth immediately and drink plenty of water.

4.2. Most important symptoms and effects, both acute and delayed

Allergic reactions

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Extinguishing powder Water spray jet Carbon dioxide (CO2).



according to Regulation (EC) No 1907/2006

Lokfix E55S, Comp. A

Revision date: 22.08.2018 Product code: SDS30 Page 3 of 10

Unsuitable extinguishing media

Full water jet Foam.

5.2. Special hazards arising from the substance or mixture

Pyrolysis products, toxic Carbon monoxide

5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Wear a self-contained breathing apparatus and chemical protective clothing.

Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Take up mechanically. Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Use only outdoors or in a well-ventilated area.

When using do not eat, drink or smoke.

Wash hands before breaks and after work.

Advice on protection against fire and explosion

No special fire protection measures are necessary.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed.

Keep only in the original container in a cool, well-ventilated place.

Advice on storage compatibility

Do not use for products which come into contact with the food stuffs.

Further information on storage conditions

storage temperature: 5-25°C

7.3. Specific end use(s)

Adhesive mortar for fastening elements A-component (resin)

SECTION 8: Exposure controls/personal protection

8.1. Control parameters



according to Regulation (EC) No 1907/2006

Lokfix E55S, Comp. A

Revision date: 22.08.2018 Product code: SDS30 Page 4 of 10

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
27813-02-1	Methacrylic acid, monoester with propane-1,2-diol			
Worker DNEI	., long-term	inhalation	systemic	14,7 mg/m ³
Worker DNEI	_, long-term	dermal	systemic	4,2 mg/kg bw/day
Consumer Di	NEL, long-term	inhalation	systemic	8,8 mg/m³
Consumer DN	NEL, long-term	dermal	systemic	2,5 mg/kg bw/day
Consumer Di	NEL, long-term	oral	systemic	2,5 mg/kg bw/day
38668-48-3	1,1'-(p-Tolylimino)dipropan-2-ol			
Worker DNEI	_, long-term	inhalation	systemic	2 mg/m³
Worker DNEI	_, long-term	dermal	systemic	0,6 mg/kg bw/day

PNEC values

CAS No	Substance		
Environmenta	I compartment	Value	
27813-02-1	Methacrylic acid, monoester with propane-1,2-diol		
Freshwater		0,904 mg/l	
Marine water		0,904 mg/l	
Freshwater se	ediment	6,28 mg/kg	
Marine sedim	ent	6,28 mg/kg	
Micro-organis	ms in sewage treatment plants (STP)	10 mg/l	
Soil		0,727 mg/kg	
38668-48-3	1,1'-(p-Tolylimino)dipropan-2-ol		
Freshwater		0,017 mg/l	
Marine water		0,0017 mg/l	
Freshwater sediment		0,0782 mg/kg	
Marine sediment		0,00782 mg/kg	
Micro-organis	Micro-organisms in sewage treatment plants (STP)		
Soil		0,005 mg/kg	

Additional advice on limit values

To date, no national critical limit values exist.

8.2. Exposure controls



Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

Eye/face protection

Wear eye protection/face protection.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four



Print date: 22.08.2018



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Lokfix E55S, Comp. A

Page 5 of 10 Revision date: 22.08.2018 Product code: SDS30

control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Wearing time with occasional contact (splashes): 0,4mm NBR (Nitrile rubber) >480min (EN374) Wearing time with permanent contact 0,5mm NBR (Nitrile rubber) >480min (EN374)

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Paste Colour: light beige

pH-Value: not determined

Changes in the physical state

not determined Melting point: Initial boiling point and boiling range: not determined Flash point: not applicable

Flammability

Solid: not determined Gas: not applicable Lower explosion limits: not determined not determined Upper explosion limits:

Auto-ignition temperature

Solid: not determined Gas: not applicable Decomposition temperature: not determined

Oxidizing properties

Not oxidising.

Vapour pressure: not determined Density (at 20 °C): 1,71 g/cm³

The study does not need to be conducted Water solubility: because the substance is known to be

insoluble in water.

Solubility in other solvents

not determined

Partition coefficient: not determined Vapour density: not determined **Evaporation rate:** not determined

9.2. Other information

Solid content: not determined

SECTION 10: Stability and reactivity



according to Regulation (EC) No 1907/2006

Lokfix E55S, Comp. A

Revision date: 22.08.2018 Product code: SDS30 Page 6 of 10

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

none

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	Method
27813-02-1	Methacrylic acid, mono	ester with p	propane-1,2	2-diol		
	oral	LD50 mg/kg	11200	Rat		
	dermal	LD50 mg/kg	> 5000	Rabbit		
38668-48-3	1,1´-(p-Tolylimino)dipro	pan-2-ol				
	oral	LD50 mg/kg	27,5	Rat		
	dermal	LD50 mg/kg	>2000			

Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Further information

The toxicity data listed pertaining to the ingredients are intended for those working in the medicinal professions, experts for occupational health and safety and toxicologists. The toxicity data pertaining to the ingredients were supplied by the manufacturers of raw materials.

SECTION 12: Ecological information

12.1. Toxicity

The product is not: Ecotoxic.



according to Regulation (EC) No 1907/2006

Lokfix E55S, Comp. A

Revision date: 22.08.2018 Product code: SDS30 Page 7 of 10

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method
27813-02-1	Methacrylic acid, monoe	ester with p	ropane-1,2	2-diol			
	Acute fish toxicity	LC50	379 mg/l	96 h			
	Acute algae toxicity	ErC50 mg/l	>97,2	72 h			
	Acute crustacea toxicity	EC50 mg/l	>143	48 h			
	Algea toxicity	NOEC mg/l	>97,2				
	Crustacea toxicity	NOEC mg/l	45,2	21 d			

12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name				
	Method	Value	d	Source	
	Evaluation				
27813-02-1	Methacrylic acid, monoester with propane-1,2-diol				
	OECD 310	81%	28		

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
38668-48-3	1,1´-(p-Tolylimino)dipropan-2-ol	2,1

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The product has not been tested.

12.6. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

Waste disposal number of waste from residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances;

hazardous waste

Waste disposal number of used product



according to Regulation (EC) No 1907/2006

Lokfix E55S, Comp. A

Revision date: 22.08.2018 Product code: SDS30 Page 8 of 10

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF

COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products);

waste adhesives and sealants containing organic solvents or other hazardous substances;

hazardous waste

Waste disposal number of contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND

PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by

hazardous substances; hazardous waste

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

substance itsen.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: No dangerous good in sense of this transport regulation.

14.2. UN proper shipping name: No dangerous good in sense of this transport regulation.

14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation.

14.4. Packing group: No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)

14.1. UN number: No dangerous good in sense of this transport regulation.

14.2. UN proper shipping name: No dangerous good in sense of this transport regulation.

14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation.

14.4. Packing group: No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

14.1. UN number: No dangerous good in sense of this transport regulation.

14.2. UN proper shipping name: No dangerous good in sense of this transport regulation.

14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation.

14.4. Packing group: No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: No dangerous good in sense of this transport regulation.

14.2. UN proper shipping name: No dangerous good in sense of this transport regulation.

14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation.

14.4. Packing group: No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

No information available.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Additional information



according to Regulation (EC) No 1907/2006

Lokfix E55S, Comp. A

Revision date: 22.08.2018 Product code: SDS30 Page 9 of 10

VOC content: 6,9 % (DIN EN ISO 11890-2)

To follow: 850/2004/EC, 79/117/EEC, 689/2008/EC

National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile

work protection guideline' (94/33/EC).

Water contaminating class (D): 1 - slightly water contaminating

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2.

Abbreviations and acronyms

ADN: Accord européen relativ au transport international des marchandises Dangereuses par voie de Navigation

(European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways) ADR: Accord européen sur le transport des marchandises dangereuses par route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

CAS: Chemical Abstracts Service

CLP: Classification, Labeling and Packaging

DMEL: Derived Minimal Effect level DNEL: Derived No Effect Level EC50: Effective concentration, 50%

ErC50: EC50 in terms of reduction of growth rate IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations (DRG) for the air transport (IATA)

IMDG: International Maritime Code for Dangerous Goods

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

NOEC: No Observed Effect Concentration

OECD: Oragnisation for Economic Co-operation and Development

PBT: persistent, bioaccumulative and toxic vPvB: very persistent and very bioaccumulative PNEC: Predicted No Effect Concentration

REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals

RID: Règlement concernant le transport international ferroviaire de marchandises dangereuses (Regulations

Concerning the International Carriage of Dangerous Goods by Rail)

VOC: Volatile organic compound Acute Tox. 2: Acute toxicity, Category 2

Aquatic Chronic 3: Long-term aquatic hazard, Category 3 Eye Irrit. 2: Serious eye damage/eye irritation, Category 2

Skin Sens. 1: Skin sensitilization, Category 1

STOT SE 3: Specific target organ toxicity (single exposure), Category 3

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Skin Sens. 1; H317	Calculation method
STOT SE 3; H335	Calculation method

Relevant H and EUH statements (number and full text)

H300 Fatal if swallowed.

H317 May cause an allergic skin reaction.



according to Regulation (EC) No 1907/2006

Lokfix E55S, Comp. A

Revision date: 22.08.2018 Product code: SDS30 Page 10 of 10

H319 Causes serious eye irritation. H335 May cause respiratory irritation.

H412 Harmful to aquatic life with long lasting effects.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)



according to Regulation (EC) No 1907/2006

Lokfix E55S, Comp. B

Revision date: 21.08.2018 Product code: SDS20 Page 1 of 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Lokfix E55S, Comp. B

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

compound mortar B-component (hardener)

Uses advised against

no restriction

1.3. Details of the supplier of the safety data sheet

Company name: Fosroc International Ltd

Street: Drayton Manor Business Park, Coleshill Road

Place: UK-B78 3XN Tamworth, Staffordshire

Telephone: +44 (0) 1827 262222 Telefax: +44 (0) 1827 262444

e-mail: enquiryuk@fosroc.com

1.4. Emergency telephone +44 (0) 1827 265279 (24 hours, 7 days)

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Serious eye damage/eye irritation: Eye Irrit. 2 Respiratory or skin sensitisation: Skin Sens. 1

Hazard Statements:

Causes serious eye irritation.

May cause an allergic skin reaction.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

Dibenzoyl peroxide

Signal word: Warning

Pictograms:



Hazard statements

H319 Causes serious eye irritation. H317 May cause an allergic skin reaction.

Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulation.



according to Regulation (EC) No 1907/2006

Lokfix E55S, Comp. B

Revision date: 21.08.2018 Product code: SDS20 Page 2 of 9

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
94-36-0	Dibenzoyl peroxide			10 - < 15 %
	202-327-6	617-008-00-0	01-2119511472-50	
	Org. Perox. B, Eye Irrit. 2, Skin Sens. 1, Aquatic Acute 1 (M-Factor = 10), Aquatic Chronic 1; H241 H319 H317 H400 H410			

Full text of H and EUH statements: see section 16.

Further Information

The product has been tested for aquatic toxicity. The tests show no need for classification of the product as toxic and harmful to aquatic life. Test reports are available.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Change contaminated, saturated clothing.

After inhalation

Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

Rinse mouth immediately and drink plenty of water.

4.2. Most important symptoms and effects, both acute and delayed

Allergic reactions

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

Extinguishing powder

Water spray jet

Unsuitable extinguishing media

Full water jet

Foam.

Print date: 22.08.2018



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Lokfix E55S, Comp. B

Revision date: 21.08.2018 Product code: SDS20 Page 3 of 9

5.2. Special hazards arising from the substance or mixture

Pyrolysis products, toxic Carbon monoxide

5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Wear a self-contained breathing apparatus and chemical protective clothing.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Provide adequate ventilation.

Use personal protection equipment.

Special danger of slipping by leaking/spilling product.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

Take up mechanically.

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Use only outdoors or in a well-ventilated area.

When using do not eat, drink or smoke.

Use protective skin cream before handling the product.

Advice on protection against fire and explosion

No special fire protection measures are necessary.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed.

Keep/Store only in original container.

Advice on storage compatibility

Do not use for products which come into contact with the food stuffs.

Store in a well-ventilated place. Keep cool.

Further information on storage conditions

Keep container tightly closed in a cool place.

storage temperature 5-25°C

7.3. Specific end use(s)

see section 1.2

SECTION 8: Exposure controls/personal protection

8.1. Control parameters



according to Regulation (EC) No 1907/2006

Lokfix E55S, Comp. B

Revision date: 21.08.2018 Product code: SDS20 Page 4 of 9

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
94-36-0	Dibenzoyl peroxide	-	5		TWA (8 h)	WEL
		-	-		STEL (15 min)	WEL

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
94-36-0	Dibenzoyl peroxide			
Consumer DNEL, long-term		oral	systemic	2 mg/kg bw/day
Worker DNEL, long-term		dermal		13,3 mg/kg bw/day
Worker DNEL	., long-term	inhalation	systemic	39 mg/m³

PNEC values

CAS No	Substance		
Environmenta	Environmental compartment		
94-36-0	94-36-0 Dibenzoyl peroxide		
Freshwater	Freshwater		
Marine water	Marine water		
Freshwater sediment (0,013 mg/kg	
Marine sediment (0,001 mg/kg	

8.2. Exposure controls





Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

Eye/face protection

Suitable eye protection: Wear eye/face protection.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Wearing time with occasional contact (splashes): 0,4mm NBR (Nitrile rubber) >480min (EN374) Wearing time with permanent contact 0,5mm NBR (Nitrile rubber) >480min (EN374)

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.



according to Regulation (EC) No 1907/2006

Lokfix E55S, Comp. B

Revision date: 21.08.2018 Product code: SDS20 Page 5 of 9

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Paste Colour: black

Odour: characteristic

pH-Value: not applicable

Changes in the physical state

Melting point:
Initial boiling point and boiling range:
Initial boiling point and boiling range:
In tapplicable

Flammability

Solid: not determined
Gas: not applicable
Lower explosion limits: not determined
Upper explosion limits: not determined

Auto-ignition temperature

Solid: not determined
Gas: not applicable

Decomposition temperature: not determined

Oxidizing properties

Not oxidising.

Available oxygen content (%) < 1%

no classification

Vapour pressure:

Density (at 20 °C):

Water solubility:

The study does not need to be conducted because the substance is known to be insoluble in water.

Solubility in other solvents

not determined

Partition coefficient: not determined

Vapour density: not determined

Evaporation rate: not determined

9.2. Other information

Solid content: not determined

SECTION 10: Stability and reactivity

10.1. Reactivity

see section 10.3

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Violent reaction with: Oxidising agent



according to Regulation (EC) No 1907/2006

Lokfix E55S, Comp. B

Revision date: 21.08.2018 Product code: SDS20 Page 6 of 9

10.4. Conditions to avoid

see section 7.2

10.5. Incompatible materials

Oxidising agent, strong

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

CAS No	Chemical name					
	Exposure route	Dose	Species	Source	Method	
94-36-0	Dibenzoyl peroxide					
	- 1 - 11	LD50 >5000 mg/kg	Rat			

Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information

12.1. Toxicity

The product is not: Ecotoxic.

OECD 201 (Desmodesmus subspicatus)

IC10: (0 - 72 h) = 30 mg/lIC50: (0 - 72 h) = 150 mg/l

OECD 202 (Daphnia magna) EC0/NOEC (48h) = 100 mg/l EC50 (48h) = >500 mg/l EC100 (48h) = >>500 mg/l

OECD 203 (Danio rerio) LC0/NOEC : 250 mg/l LC50 :> 500 mg/l LC100 :>> 500 mg/l

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method
94-36-0	Dibenzoyl peroxide						
	Acute fish toxicity	LC50 mg/l	0,0602		Oncorhynchus mykiss (Rainbow trout)	OECD 203	
	Acute algae toxicity	ErC50 mg/l	0,0711		Pseudokirchneriella subcapitata	OECD 201	
	Acute crustacea toxicity	EC50	0,11 mg/l		Daphnia magna (Big water flea)	OECD 202	
	Algea toxicity	NOEC mg/l	0,02		Pseudokirchneriella subcapitata	OECD 201	
	Crustacea toxicity	NOEC mg/l	0,001		Daphnia magna (Big water flea)	OECD 211	
	Acute bacteria toxicity	(35 mg/l)		0,5 h		OECD 209	



according to Regulation (EC) No 1907/2006

Lokfix E55S, Comp. B

Revision date: 21.08.2018 Product code: SDS20 Page 7 of 9

12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
94-36-0	Dibenzoyl peroxide			
	OECD 301D	71%	28	
	Readily biodegradable (according to OECD criteria).			

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
94-36-0	Dibenzoyl peroxide	3,2

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The product has not been tested.

12.6. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

Waste disposal number of waste from residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

Waste disposal number of used product

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

Waste disposal number of contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.



according to Regulation (EC) No 1907/2006

Lokfix E55S, Comp. B

Revision date: 21.08.2018 Product code: SDS20 Page 8 of 9

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number:
 14.2. UN proper shipping name:
 14.3. Transport hazard class(es):
 14.4. Packing group:
 No dangerous good in sense of this transport regulation.
 No dangerous good in sense of this transport regulation.
 No dangerous good in sense of this transport regulation.
 No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)

14.1. UN number:
 14.2. UN proper shipping name:
 14.3. Transport hazard class(es):
 14.4. Packing group:
 No dangerous good in sense of this transport regulation.
 No dangerous good in sense of this transport regulation.
 No dangerous good in sense of this transport regulation.
 No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

14.1. UN number: No dangerous good in sense of this transport regulation.
 14.2. UN proper shipping name: No dangerous good in sense of this transport regulation.
 14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation.
 14.4. Packing group: No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number:
 14.2. UN proper shipping name:
 14.3. Transport hazard class(es):
 14.4. Packing group:
 No dangerous good in sense of this transport regulation.
 No dangerous good in sense of this transport regulation.
 No dangerous good in sense of this transport regulation.
 No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

No information available.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Additional information

VOC content: 4,3 % (DIN EN ISO 11890-2)

To follow: 850/2004/EC, 79/117/EEC, 689/2008/EC

National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile

work protection guideline' (94/33/EC).

Water contaminating class (D): 2 - clearly water contaminating

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes



according to Regulation (EC) No 1907/2006

Lokfix E55S, Comp. B

Revision date: 21.08.2018 Product code: SDS20 Page 9 of 9

This data sheet contains changes from the previous version in section(s): 2.

Abbreviations and acronyms

ADN: Accord européen relativ au transport international des marchandises Dangereuses par voie de Navigation

(European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways)

ADR: Accord européen sur le transport des marchandises dangereuses par route (Éuropean Agreement

concerning the International Carriage of Dangerous Goods by Road)

CAS: Chemical Abstracts Service

CLP: Classification, Labeling and Packaging

DMEL: Derived Minimal Effect level DNEL: Derived No Effect Level EC50: Effective concentration, 50%

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations (DRG) for the air transport (IATA)

ICAO: International Civil Aviation Organization

IC50: Inhibitory concentration, 50%

IMDG: International Maritime Code for Dangerous Goods

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

NOEC: No Observed Effect Concentration

OECD: Oragnisation for Economic Co-operation and Development

PBT: persistent, bioaccumulative and toxic vPvB: very persistent and very bioaccumulative PNEC: Predicted No Effect Concentration

REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals

RID: Règlement concernant le transport international ferroviaire de marchandises dangereuses (Regulations

Concerning the International Carriage of Dangerous Goods by Rail)

VOC: Volatile organic compound

Aquatic Chronic 3: Long-term aquatic hazard, Category 3

Acute Tox. 2: Acute toxicity, Category 2

Skin Irrit. 2: Serious eve damage/eve irritation, Category 2

Skin Sens. 1: Skin sensitilization, Category 1

STOT SE 3: Specific target organ toxicity (single exposure), Category 3

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

	<u> </u>
Classification	Classification procedure
Eye Irrit. 2; H319	Calculation method
Skin Sens. 1; H317	Calculation method

Relevant H and EUH statements (number and full text)

		′ .
H241	Heating may cause a fire or explo	osion.
H317	May cause an allergic skin reaction	on.
H319	Causes serious eye irritation.	
H400	Very toxic to aquatic life.	

H410 Very toxic to aquatic life with long lasting effects.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)