

Separation

Technical Datasheet

Lotrak® separation geotextiles are used between the sub grade and sub base. This prevents intermixing of expensive stone and other aggregates within the soil, while providing good ground stabilisation.

Designed to control particle movement of the soil, Lotrak® separators, prevent clogging while maintaining water flow by creating a bridging zone to promote natural soil filtration. The main purpose of all Lotrak® separation geotextiles is to prevent the loss of construction gravel and aggregates into the underlying soil and/or subgrade.

Product Features

- Prevents the loss of construction aggregates into the underlying soil
- Demonstrates high tensile strength and CBR properties to offer an element of protection
- As a lightweight separator, Lotrak can help reduce the carbon footprint of a project, making it an efficient and cost effective solution

Benefits

- Proven separator performance
- Superior strength and resistance
- High mechanical strength
- Good puncture resistance
- Reduced stone requirements









TEST	STANDARD		BASE	ADVANCE	1800	2300	2800	80	100	140	200	300	
Tensile Strength (kN/m)	EN 10319	MD	10	12	12	21	22	6	8	12	18	25	
		CD	9	9	12	17	21	6	8	12	18	25	
Elongation at max. load (%)	EN	MD	22	22	22	22	22	36	45	45	50	65	
	10319	CD	15	15	18	18	14	42	45	45	50	65	
CBR Puncture Resistance (N)	EN ISO 12236		1500	1550	1800	2600	2800	1050	1500	2000	2900	4300	
Cone Drop Penetration (mm)	EN 918		18	16	14	11	10	48	36	26	18	13	
Pore size 90% finer than (microns)	EN ISO 12956		220	240	200	180	270	128	100	90	70	70	
Water Permeability (x 10 ⁻³) (m/ sec)11058	EN ISO		10	18	18	22	20	144	130	110	80	65	
Effect of UV Light	fect of UV Light The polypropylene (PP) used contains a UV inhibitor												
Roll Size (m)		Width	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	
		Length	100	100	100	100	100	100	100	100	100	50/ 100	



All products are manufactured under BS EN ISO 9001.

Don & Low reserves the right to change specifications or other product information. Don & Low accepts no responsibility or liability for information provided by third parties. No warranties, express or implied, are offered regarding the suitability of any product for your use, as site conditions and customer requirements vary. Should you require further information, please contact us. Products are sold subject to the seller's terms and conditions of sale. No warranty or immunity is offered against infringement of patents or other intellectual property rights. ©Don & Low Limited, 2019. The intellectual property in the products is owned and protected by Don & Low or its licensors.