

## Safety Data Sheet

### PRIMER 3296

Safety Data Sheet dated: 28/09/2020 - version 1



## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Mixture identification:

Trade name: PRIMER 3296

Trade code: 902531

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use: N.A.

Uses advised against: N.A.

### 1.3. Details of the supplier of the safety data sheet

Company: MAPEI U.K. Ltd - Mapei House Steel Park Road

Halesowen - West Midlands B62 8HD

www.mapei.co.uk (office hour 8:30-17:30)

Responsible: sicurezza@mapei.it

### 1.4. Emergency telephone number

call NHS 111 or a doctor/OHES Environmental Ltd +44(0)1684 299 886

phone: +44(0)121 508 6970 - fax: +44(0)121 5086 960

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Regulation (EC) n. 1272/2008 (CLP)

0 The product is not classified as hazardous according to Regulation EC 1272/2008 (CLP).

Adverse physicochemical, human health and environmental effects:

No other hazards

### 2.2. Label elements

The product is not classified as hazardous according to Regulation EC 1272/2008 (CLP).

#### Special Provisions:

EUH208 Contains n-butyl acrylate. May produce an allergic reaction.

EUH208 Contains reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H - isothiazol-3-one [EC no. 220-239-6] (3:1). May produce an allergic reaction.

EUH210 Safety data sheet available on request.

#### Special provisions according to Annex XVII of REACH and subsequent amendments:

None

### 2.3. Other hazards

No PBT/vPvB Ingredients are present

Other Hazards: No other hazards

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

N.A.

### 3.2. Mixtures

Mixture identification: PRIMER 3296

#### Hazardous components within the meaning of the CLP regulation and related classification:

Quantity	Name	Ident. Numb.	Classification	Registration Number
≥0.1 - <0.25 %	n-butyl acrylate	CAS:141-32-2 EC:205-480-7 Index:607-062-00-3	Flam. Liq. 3, H226; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335; Skin Sens. 1B, H317; Aquatic Chronic 3, H412	01-2119453155-43-XXXX

<p>&lt;0.0015 % reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1)</p>	<p>CAS:55965-84-9 EC:611-341-5 Index:613-167-00-5</p>	<p>Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Acute Tox. 3, H301; Skin Corr. 1C, H314; Skin Sens. 1A, H317; Acute Tox. 2, H310; Acute Tox. 2, H330; Eye Dam. 1, H318, M-Chronic:100, M-Acute:100</p>
------------------------------------------------------------------------------------------------------------------------------------------------------------	---------------------------------------------------------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

---

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

In case of skin contact:

Wash with plenty of water and soap.

In case of eyes contact:

Wash immediately with water.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and the hazard label.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

### 4.2. Most important symptoms and effects, both acute and delayed

N.A.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treatment: N.A.

(see paragraph 4.1)

---

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media:

Water.

Carbon dioxide (CO<sub>2</sub>).

Extinguishing media which must not be used for safety reasons:

None in particular.

### 5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

### 5.3. Advice for firefighters

Use suitable breathing apparatus.

---

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove persons to safety.

### 6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Limit leakages with earth or sand.

### 6.3. Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Retain contaminated washing water and dispose it.

### 6.4. Reference to other sections

See also section 8 and 13

---

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

### 7.2. Conditions for safe storage, including any incompatibilities

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

### 7.3. Specific end use(s)

Recommendation(s)

None in particular

Industrial sector specific solutions:

None in particular

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### List of components with OEL value

Component	OEL Type	Country	Ceiling	Long Term mg/m3	Long Term ppm	Short Term mg/m3	Short Term ppm	Behaviour	Note
n-butyl acrylate	National	SWEDEN		50	10	80	15		SWEDEN, Short-term value, 15 minutes average value
	National	NORWAY		11	2				NORWAY, A
	EU	NNN		11	2	53	10		
	National	NORWAY		11	2	22	4		
	ACGIH	NNN			2				DSEN, A4 - Irr
	DFG	GERMANY	C			22	4		
	ACGIH				2				A4 - Not Classifiable as a Human Carcinogen;irritation; dermal sensitizer
	National	SWEDEN		11	2				
	National	FRANCE		11	2	53	10		
	National	SPAIN		11	2	53	10		
	National	GREECE		55	10				
	National	DENMARK		11	2				
	National	FINLAND		11	2	53	10		
	National	GERMANY		11	2				
	National	PORTUGAL		11	2	53	10		
	National	NORWAY		11	2	16.5	4		
	National	BELGIUM		11	2	53	10		
	NDS	POLAND		11					
	NDSch	POLAND				30			
	CHE	SWITZERLAND				22	4		
	NDS	NETHERLANDS		11		53			
	National	CZECH REPUBLIC		10					
	National	HUNGARY		11		53			
	Malaysi a OEL	MALAYSIA		10.48	2				
	National	ESTONIA		11	2	53	10		
	National	LATVIA		11	2	53	10		
	National	CZECH REPUBLIC	C			20			
	National	SLOVAKIA	C			53			
	National	SLOVAKIA		11	2				
	National	SLOVENIA		11	2	55	10		
	National	UNITED KINGDOM		5	1	26	5		
	National	BULGARIA		11	2	53	10		
	National	ROMANIA		11	2	53	10		
	TUR	TURKEY		11	2	53	10		
	National	LITHUANIA		11	2	53	10		
	National	CROATIA		11	2	53	10		

EU	11	2	53	10	Indicative
National SLOVENIA	11	2	53	10	

#### Predicted No Effect Concentration (PNEC) values

Component	CAS-No.	PNEC Limit	Exposure Route	Exposure Frequency	Remark
n-butyl acrylate	141-32-2	0.00272 mg/l	Fresh Water		
		0.00027 mg/l	Marine water		
		0.0338 mg/kg	Freshwater sediments		
		1 mg/kg	Soil		
		0.00338 mg/kg	Marine water sediments		
		0.011 mg/l	Intermittent release		
		3.5 mg/l	Microorganisms in sewage treatments		

#### Derived No Effect Level. (DNEL)

Component	CAS-No.	Worker Industrial	Worker Professional	Consumer	Exposure Route	Exposure Frequency	Remark
n-butyl acrylate	141-32-2	11 mg/m3			Human Inhalation	Long Term, local effects	

#### 8.2. Exposure controls

Eye protection:

Not needed for normal use. Anyway, operate according good working practices.

Protection for skin:

No special precaution must be adopted for normal use.

Protection for hands:

Suitable materials for safety gloves; EN 374:

Polychloroprene - CR: thickness  $\geq 0,5\text{mm}$ ; breakthrough time  $\geq 480\text{min}$ .

Nitrile rubber - NBR: thickness  $\geq 0,35\text{mm}$ ; breakthrough time  $\geq 480\text{min}$ .

Butyl rubber - IIR: thickness  $\geq 0,5\text{mm}$ ; breakthrough time  $\geq 480\text{min}$ .

Fluorinated rubber - FKM: thickness  $\geq 0,4\text{mm}$ ; breakthrough time  $\geq 480\text{min}$ .

Respiratory protection:

Personal Protective Equipment should comply with relevant CE standards (as EN 374 for gloves and EN 166 for goggles), correctly maintained and stored. Consult the supplier to check the suitability of equipment against specific chemicals and for user information.

Hygienic and Technical measures

N.A.

Appropriate engineering controls:

N.A.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state: Liquid

Appearance and colour: liquid white

Odour: Characteristic

Odour threshold: N.A.

pH: 6,00

Melting point / freezing point: N.A.

Initial boiling point and boiling range: N.A.

Flash point: N.A.

Evaporation rate: N.A.

Upper/lower flammability or explosive limits: N.A.

Vapour density: N.A.

Vapour pressure: N.A.

Relative density: 1,06 g/cm<sup>3</sup>

Solubility in water: N.A.

Partition coefficient (n-octanol/water): N.A.  
Auto-ignition temperature: N.A.  
Decomposition temperature: N.A.  
Viscosity: N.A.  
Explosive properties: N.A.  
Oxidizing properties: N.A.  
Solid/gas flammability: N.A.

## 9.2. Other information

No additional information

---

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Stable under normal conditions

### 10.2. Chemical stability

Stable under normal conditions

### 10.3. Possibility of hazardous reactions

None.

### 10.4. Conditions to avoid

Stable under normal conditions.

### 10.5. Incompatible materials

None in particular.

### 10.6. Hazardous decomposition products

None.

---

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Toxicological information of the mixture:

There is no toxicological data available on the mixture. Consider the individual concentration of each component to assess toxicological effects resulting from exposure to the mixture.

#### Toxicological information on main components of the mixture:

n-butyl acrylate	a) acute toxicity	LC50 Inhalation Rat = 10.3 mg/l 4h LD50 Skin Rabbit = 3500 mg/kg LD50 Oral Rat = 3500 mg/kg LD50 Skin Rabbit = 3024 mg/kg LC50 Inhalation Rat = 10.3 mg/l 4h LD50 Oral Rat = 9050 mg/kg
------------------	-------------------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	a) acute toxicity	LD50 Oral Rat = 457 mg/kg   LC50 Inhalation Rat = 2.36 mg/l 4h LD50 Skin Rabbit = 660 mg/kg LD50 Oral Rat = 53 mg/kg
---------------------------------------------------------------------------------------------------------------------------------------	-------------------	-------------------------------------------------------------------------------------------------------------------------------------

**If not differently specified, the information required in Regulation (EU)2015/830 listed below must be considered as N.A.**

- a) acute toxicity
- b) skin corrosion/irritation
- c) serious eye damage/irritation
- d) respiratory or skin sensitisation
- e) germ cell mutagenicity
- f) carcinogenicity
- g) reproductive toxicity
- h) STOT-single exposure

## SECTION 12: Ecological information

### 12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

#### List of components with eco-toxicological properties

Component	Ident. Numb.	Ecotox Infos
n-butyl acrylate	CAS: 141-32-2 - EINECS: 607-062- 00-3 - INDEX: 205- 480-7	a) Aquatic acute toxicity : LC50 Fish = 5 mg/L 96  a) Aquatic acute toxicity : EC50 Daphnia = 5 mg/L 48 a) Aquatic acute toxicity : EC50 Algae = 5 mg/L 96 b) Aquatic chronic toxicity : NOEC Daphnia = 0.136 mg/L - 21 d c) Bacteria toxicity : EC50 Bacteria > 1000 mg/L a) Aquatic acute toxicity : LC50 Fish Oncorhynchus mykiss = 5.2 mg/L 96h IUCLID a) Aquatic acute toxicity : EC50 Daphnia Daphnia magna = 8.2 mg/L 48h IUCLID a) Aquatic acute toxicity : EC50 Algae Pseudokirchneriella subcapitata = 5.5 mg/L 96h IUCLID
reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H - isothiazol-3-one [EC no. 220-239- 6] (3:1)	CAS: 55965-84-9 - EINECS: 613-167- 00-5 - INDEX: 611- 341-5	a) Aquatic acute toxicity : EC50 Daphnia = 0.12 mg/L 48  a) Aquatic acute toxicity : LC50 Fish = 0.22 mg/L 96 a) Aquatic acute toxicity : EC50 Algae = 0.048 mg/L 72 b) Aquatic chronic toxicity : NOEC Algae = 0.0012 mg/L 72 b) Aquatic chronic toxicity : NOEC Fish = 0.098 mg/L - 28 d b) Aquatic chronic toxicity : NOEC Daphnia = 0.004 mg/L - 21 d

### 12.2. Persistence and degradability

N.A.

### 12.3. Bioaccumulative potential

N.A.

### 12.4. Mobility in soil

N.A.

### 12.5. Results of PBT and vPvB assessment

No PBT/vPvB Ingredients are present

### 12.6. Other adverse effects

N.A.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

The generation of waste should be avoided or minimized wherever possible. Recover if possible.

A waste code (EWC) according to European List of Waste (LoW) cannot be specified, due to dependence on the usage. Contact and send to an authorized waste disposal service.

Methods of disposal:

Disposal of this product, solutions, packaging and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor.

Do not dispose of waste into sewers.

Clean waste packaging should be recycled when possible and authorized by the authority.

Hazardous waste: No

Disposal considerations:

Do not allow to enter drains or watercourses.

Dispose of product according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

Dispose of containers contaminated by the product in accordance with local or national legal provisions. For further information, contact your local waste authority.

Special precautions:

This material and its container must be disposed of in a safe way. Care should be taken when handling untreated empty containers.

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Empty containers or liners may retain some product residues. Do not re-use empty containers.

---

## SECTION 14: Transport information

Not classified as dangerous in the meaning of transport regulations.

### 14.1. UN number

N.A.

### 14.2. UN proper shipping name

N.A.

### 14.3. Transport hazard class(es)

N.A.

### 14.4. Packing group

N.A.

### 14.5. Environmental hazards

N.A.

### 14.6. Special precautions for user

N.A.

Road and Rail ( ADR-RID ) :

N.A.

Air ( IATA ) :

N.A.

Sea ( IMDG ) :

N.A.

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

N.A.

---

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 98/24/EC (Risks related to chemical agents at work)

Dir. 2000/39/EC (Occupational exposure limit values)

Regulation (EC) n. 1907/2006 (REACH)

Regulation (EU) 2015/830

Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Regulation (EU) n. 2018/669 (ATP 11 CLP)

Regulation (EU) n. 2019/521 (ATP 12 CLP)

Regulation (EU) n. 286/2011 (ATP 2 CLP)

Regulation (EU) n. 618/2012 (ATP 3 CLP)

Regulation (EU) n. 487/2013 (ATP 4 CLP)

Regulation (EU) n. 944/2013 (ATP 5 CLP)

Regulation (EU) n. 605/2014 (ATP 6 CLP)

Regulation (EU) n. 2015/1221 (ATP 7 CLP)

Regulation (EU) n. 2016/918 (ATP 8 CLP)

Regulation (EU) n. 2016/1179 (ATP 9 CLP)

Regulation (EU) n. 2017/776 (ATP 10 CLP)

Regulation (EU) n. 2018/669 (ATP 11 CLP)

Regulation (EU) n. 2018/1480 (ATP 13 CLP)

Provisions related to directive EU 2012/18 (Seveso III):

N.A.

### German Water Hazard Class.

N.A.

**Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:**

Restrictions related to the product: 40

Restrictions related to the substances contained: None

**SVHC Substances:**

No data available

**15.2. Chemical safety assessment**

No Chemical Safety Assessment has been carried out for the mixture.

---

**SECTION 16: Other information**

Code	Description
H226	Flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H412	Harmful to aquatic life with long lasting effects.

Code	Hazard class and hazard category	Description
2.6/3	Flam. Liq. 3	Flammable liquid, Category 3
3.1/4/Inhal	Acute Tox. 4	Acute toxicity (inhalation), Category 4
3.2/2	Skin Irrit. 2	Skin irritation, Category 2
3.3/2	Eye Irrit. 2	Eye irritation, Category 2
3.4.2/1B	Skin Sens. 1B	Skin Sensitisation, Category 1B
3.8/3	STOT SE 3	Specific target organ toxicity — single exposure, Category 3
4.1/C3	Aquatic Chronic 3	Chronic (long term) aquatic hazard, category 3

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

Legend to abbreviations and acronyms used in the safety data sheet:

ACGIH: American Conference of Governmental Industrial Hygienists

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

AND: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

ATE: Acute Toxicity Estimate

ATEmix: Acute toxicity Estimate (Mixtures)

BCF: Biological Concentration Factor

BEI: Biological Exposure Index

BOD: Biochemical Oxygen Demand

CAS: Chemical Abstracts Service (division of the American Chemical Society).

CAV: Poison Center

CE: European Community

CLP: Classification, Labeling, Packaging.

CMR: Carcinogenic, Mutagenic and Reprotoxic

COD: Chemical Oxygen Demand

COV: Volatile Organic Compound

CSA: Chemical Safety Assessment

CSR: Chemical Safety Report

DMEL: Derived Minimal Effect Level

DNEL: Derived No Effect Level.

DPD: Dangerous Preparations Directive

DSD: Dangerous Substances Directive



EC50: Half Maximal Effective Concentration  
ECHA: European Chemicals Agency  
EINECS: European Inventory of Existing Commercial Chemical Substances.  
ES: Exposure Scenario  
GefStoffVO: Ordinance on Hazardous Substances, Germany.  
GHS: Globally Harmonized System of Classification and Labeling of Chemicals.  
IARC: International Agency for Research on Cancer  
IATA: International Air Transport Association.  
IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).  
IC50: half maximal inhibitory concentration  
ICAO: International Civil Aviation Organization.  
ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).  
IMDG: International Maritime Code for Dangerous Goods.  
INCI: International Nomenclature of Cosmetic Ingredients.  
IRCCS: Scientific Institute for Research, Hospitalization and Health Care  
KSt: Explosion coefficient.  
LC50: Lethal concentration, for 50 percent of test population.  
LD50: Lethal dose, for 50 percent of test population.  
LDLo: Leathal Dose Low  
N.A.: Not Applicable  
N/A: Not Applicable  
N/D: Not defined/ Not available  
NA: Not available  
NIOSH: National Institute for Occupational Safety and Health  
NOAEL: No Observed Adverse Effect Level  
OSHA: Occupational Safety and Health Administration.  
PBT: Persistent, Bioaccumulative and Toxic  
PGK: Packaging Instruction  
PNEC: Predicted No Effect Concentration.  
PSG: Passengers  
RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.  
STEL: Short Term Exposure limit.  
STOT: Specific Target Organ Toxicity.  
TLV: Threshold Limiting Value.  
TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).  
vPvB: Very Persistent, Very Bioaccumulative.  
WGK: German Water Hazard Class.