



SAFETY DATA SHEET NITODEK FS WEARCOAT RESIN

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	NITODEK FS WEARCOAT RESIN
Chemical name	Polyurethane Resin
Product number	1800680UK9, 1800683UK9, 1800685UK9

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Reaction Resin
-----------------	----------------

1.3. Details of the supplier of the safety data sheet

Supplier	FOSROC Limited Drayton Manor Business Park Coleshill Road Tamworth Staffordshire B78 3XN Tel. +44 (0) 1827 262222 Fax. +44 (0) 1827 262444 enquiryuk@fosroc.com
----------	---

1.4. Emergency telephone number

Emergency telephone	+44 (0) 1827 265 279 (08.30 to 17.00hrs Mon - Thu; 0.8.30 to 16.00hrs Fri)
---------------------	--

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)


Physical hazards	Flam. Liq. 2 - H225
Health hazards	Skin Irrit. 2 - H315 Skin Sens. 1 - H317 STOT SE 3 - H335
Environmental hazards	Not Classified

Human health	The product contains a sensitising substance. May cause sensitisation or allergic reactions in sensitive individuals.
--------------	---

Physicochemical	The product is highly flammable. Vapours may form explosive mixtures with air.
-----------------	--

2.2. Label elements

Pictogram



Signal word	Danger
-------------	--------

NITODEK FS WEARCOAT RESIN

Hazard statements	<p>H225 Highly flammable liquid and vapour.</p> <p>H315 Causes skin irritation.</p> <p>H317 May cause an allergic skin reaction.</p> <p>H335 May cause respiratory irritation.</p>
Precautionary statements	<p>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</p> <p>P261 Avoid breathing vapour/ spray.</p> <p>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</p> <p>P302+P352 IF ON SKIN: Wash with plenty of water.</p> <p>P403+P235 Store in a well-ventilated place. Keep cool.</p> <p>P501 Dispose of contents/ container in accordance with national regulations.</p>
Contains	METHYL METHACRYLATE, 2-ETHYLHEXYL ACRYLATE, Reaction product: Bisphenol-A-(epichlorhydrin) Epoxy Resin
Supplementary precautionary statements	<p>P264 Wash contaminated skin thoroughly after handling.</p> <p>P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.</p> <p>P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.</p> <p>P312 Call a POISON CENTRE/doctor if you feel unwell.</p> <p>P321 Specific treatment (see medical advice on this label).</p> <p>P332+P313 If skin irritation occurs: Get medical advice/ attention.</p> <p>P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.</p> <p>P362+P364 Take off contaminated clothing and wash it before reuse.</p> <p>P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.</p> <p>P403+P233 Store in a well-ventilated place. Keep container tightly closed.</p> <p>P405 Store locked up.</p>

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

METHYL METHACRYLATE			25 - 50%
CAS number: 80-62-6	EC number: 201-297-1	REACH registration number: 01-2119452498-28-0000	
Classification Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 Skin Sens. 1 - H317 STOT SE 3 - H335			

2-ETHYLHEXYL ACRYLATE			10 - 25%
CAS number: 103-11-7	EC number: 203-080-7		
Classification Skin Irrit. 2 - H315 Skin Sens. 1 - H317 STOT SE 3 - H335 Aquatic Chronic 3 - H412			

NITODEK FS WEARCOAT RESIN

1,1'-(p-tolylimino)dipropan-2-ol		<1%
CAS number: 38668-48-3	EC number: 254-075-1	
Classification Acute Tox. 3 - H301 Aquatic Chronic 3 - H412		
Reaction product: Bisphenol-A-(epichlorhydrin) Epoxy Resin		<1%
CAS number: 25068-38-6	EC number: 500-033-5	
Classification Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317 Aquatic Chronic 2 - H411		Classification (67/548/EEC or 1999/45/EC) Xi; R36/38. N; R51/53. R43

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Get medical attention if any discomfort continues.
Inhalation	Move affected person to fresh air at once. Get medical attention.
Ingestion	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Rinse mouth thoroughly with water. Give plenty of water to drink. Do not induce vomiting. Get medical attention.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if any discomfort continues.
Eye contact	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention promptly if symptoms occur after washing.

4.2. Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	May cause respiratory system irritation. Vapours may cause drowsiness and dizziness.
Ingestion	Gastrointestinal symptoms, including upset stomach. May cause nausea, headache, dizziness and intoxication. Narcotic effect.
Skin contact	Irritating to skin. May cause sensitisation by skin contact.
Eye contact	Irritating to eyes.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	No specific recommendations. If in doubt, get medical attention promptly.
-----------------------------	---

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog.
-------------------------------------	--

NITODEK FS WEARCOAT RESIN

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards Vapours may be ignited by a spark, a hot surface or an ember. The product is highly flammable. Vapours are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back.

Hazardous combustion products Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours. Oxides of carbon.

5.3. Advice for firefighters

Protective actions during firefighting No specific firefighting precautions known.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Follow precautions for safe handling described in this safety data sheet. Take precautionary measures against static discharges. Provide adequate ventilation.

6.2. Environmental precautions

Environmental precautions To prevent the discharge of sewage / surface or underground water.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Provide adequate ventilation. Collect and place in suitable waste disposal containers and seal securely. For waste disposal, see Section 13. Contain spills immediately with inert materials (e.g., : sand, earth, sawdust)

6.4. Reference to other sections

Reference to other sections Wear protective clothing as described in Section 8 of this safety data sheet. Collect and dispose of spillage as indicated in Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Avoid spilling. Avoid contact with skin and eyes. Keep away from heat, sparks and open flame. Static electricity and formation of sparks must be prevented. Provide adequate ventilation.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Keep container tightly closed. Keep only in the original container. Keep away from heat, sparks and open flame.

Storage class Flammable liquid storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

NITODEK FS WEARCOAT RESIN

Occupational exposure limits

METHYL METHACRYLATE

Long-term exposure limit (8-hour TWA): WEL 50 ppm 208 mg/m³

Short-term exposure limit (15-minute): WEL 100 ppm 416 mg/m³

WEL = Workplace Exposure Limit

METHYL METHACRYLATE (CAS: 80-62-6)

DNEL	Workers - Dermal; Long term systemic effects: 13.67 mg/kg bw/day Workers - Dermal; Long term local effects: 1.5 mg/cm ² General population - Dermal; Long term systemic effects: 8.2 mg/kg bw/day General population - Dermal; Long term local effects: 1.5 mg/cm ²
PNEC	- Fresh water; 0.94 mg/l

2-ETHYLHEXYL ACRYLATE (CAS: 103-11-7)

DNEL	Workers - Inhalation; Long term local effects: 37.5 mg/m ³ Workers - Dermal; Acute local effects: 0.242 mg/cm ²
PNEC	- Fresh water; 2.72 µg/l

1,1'-(p-tolylimino)dipropen-2-ol (CAS: 38668-48-3)

DNEL	Professional - Oral; Long term systemic effects: 2 mg/m ³
-------------	--

Reaction product: Bisphenol-A-(epichlorhydrin) Epoxy Resin (CAS: 25068-38-6)

DNEL	Workers - Dermal; Short term : 8.3 mg/kg bw/day Workers - Inhalative; Short term : 12.3 mg/m ³
PNEC	- Fresh water; 0.003 mg/l - Marine water; 0.0003 mg/l

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate general and local exhaust ventilation.

Eye/face protection

Wear tight-fitting, chemical splash goggles or face shield.

Hand protection

Only use chemical-protective gloves with CE-labelling of category III.

Check the permeability prior to each use of the glove.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. It is recommended that gloves are made of the following material: Nitrile rubber.

Other skin and body protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

NITODEK FS WEARCOAT RESIN

Hygiene measures Wash at the end of each work shift and before eating, smoking and using the toilet. Remove contaminated clothing and wash the skin thoroughly with soap and water after work.

Respiratory protection If ventilation is inadequate, suitable respiratory protection must be worn. Gas filter, type A2.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid.
Colour	Light Yellow
Odour	Characteristic odour
Odour threshold	Not determined.
pH	Not applicable.
Melting point	Not determined.
Initial boiling point and range	100 °C
Flash point	10°C
Evaporation rate	Not determined.
Evaporation factor	Not determined.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	Lower flammable/explosive limit: 2.1 Vol % Upper flammable/explosive limit: 12.5 Vol %
Other flammability	Not determined.
Vapour pressure	38.7 hPa
Vapour density	Not determined.
Bulk density	1.0 g/cm ³
Solubility(ies)	Partially soluble in water.
Partition coefficient	Not determined.
Auto-ignition temperature	245°C
Decomposition Temperature	Not determined.
Viscosity	1000 mPa s @ 20°C
Explosive properties	Not considered to be explosive.
Explosive under the influence of a flame	Not considered to be explosive.
Oxidising properties	Does not meet the criteria for classification as oxidising.

9.2. Other information

Other information No data available.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity Exothermic polymerization.

10.2. Chemical stability

NITODEK FS WEARCOAT RESIN

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Exothermic polymerisation.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition. Avoid excessive heat for prolonged periods of time.

10.5. Incompatible materials

Materials to avoid Strong oxidising agents. Acids. Amides. Aldehydes. Other halogenated organics.

10.6. Hazardous decomposition products

Hazardous decomposition products Carbon monoxide (CO). Carbon dioxide (CO₂).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

ATE oral (mg/kg) 20,000.0

Inhalation May cause respiratory system irritation. Vapours may cause drowsiness and dizziness.

Ingestion Gastrointestinal symptoms, including upset stomach. May cause nausea, headache, dizziness and intoxication. Narcotic effect.

Skin contact Irritating to skin. May cause sensitisation by skin contact.

Eye contact Irritating to eyes.

SECTION 12: Ecological Information

Ecotoxicity Not available.

12.1. Toxicity

Toxicity No data available.

12.2. Persistence and degradability

Persistence and degradability No further relevant information available.

12.3. Bioaccumulative potential

Bioaccumulative potential The product does not contain any substances expected to be bioaccumulating. No information available.

Partition coefficient Not determined.

12.4. Mobility in soil

Mobility No data is available on this product.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

NITODEK FS WEARCOAT RESIN

Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Do not empty into drains, sewers or water courses.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 1866

UN No. (IMDG) 1866

UN No. (ICAO) 1866

UN No. (ADN) 1866

14.2. UN proper shipping name

Proper shipping name (ADR/RID) RESIN SOLUTION

Proper shipping name (IMDG) RESIN SOLUTION

Proper shipping name (ICAO) RESIN SOLUTION

Proper shipping name (ADN) RESIN SOLUTION

14.3. Transport hazard class(es)

ADR/RID class 3

ADR/RID classification code F1

ADR/RID label 3

IMDG class 3

ICAO class/division 3

ADN class 3

Transport labels



14.4. Packing group

ADR/RID packing group II

IMDG packing group II

ADN packing group II

ICAO packing group II

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant
No.

NITODEK FS WEARCOAT RESIN

14.6. Special precautions for user

EmS	F-E, S-E
ADR transport category	2
Emergency Action Code	•3YE
Hazard Identification Number (ADR/RID)	33
Tunnel restriction code	(D/E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations	Control of Substances Hazardous to Health Regulations 2002 (as amended).
EU legislation	Commission Regulation (EU) No 453/2010 of 20 May 2010. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended). Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).
Guidance	Workplace Exposure Limits EH40. Approved Classification and Labelling Guide (Sixth edition) L131. Respiratory protective equipment at work (HSG53).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

General information	Only trained personnel should use this material. For professional users only.
Revision date	18/01/2018
Revision	2
Supersedes date	03/02/2017
SDS number	24948
Hazard statements in full	H225 Highly flammable liquid and vapour. H301 Toxic if swallowed. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H335 May cause respiratory irritation. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.



SAFETY DATA SHEET NITODEK FS WEARCOAT FILLER

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name NITODEK FS WEARCOAT FILLER

Product number 1800687 UK9

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Filler

1.3. Details of the supplier of the safety data sheet

Supplier Fosroc Limited
Drayton Manor Business Park
Coleshill Road
Tamworth
Staffordshire
B78 3XN
England
Tel: +44 (0) 1827 262222
Fax: +44 (0) 1827 262444
enquiryuk@fosroc.com

1.4. Emergency telephone number

Emergency telephone +44 (0) 1827 265 279 (08.30 to 17.00hrs Mon - Thu; 0.8.30 to 16.00hrs Fri)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Carc. 1A - H350 STOT RE 1 - H372

Environmental hazards Not Classified

2.2. Label elements

Pictogram



Signal word Danger

Hazard statements H350 May cause cancer.
H372 Causes damage to organs through prolonged or repeated exposure.

NITODEK FS WEARCOAT FILLER

Precautionary statements	P260 Do not breathe dust. P284 [In case of inadequate ventilation] wear respiratory protection. P308+P313 IF exposed or concerned: Get medical advice/ attention. P314 Get medical advice/ attention if you feel unwell. P405 Store locked up. P501 Dispose of contents/ container in accordance with national regulations.
Contains	QUARTZ
Supplementary precautionary statements	P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P264 Wash contaminated skin thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

QUARTZ	60-100%
CAS number: 14808-60-7	
Classification Carc. 1A - H350 STOT RE 1 - H372	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	No special treatment required.
Inhalation	Move affected person to fresh air at once.
Ingestion	Rinse mouth thoroughly with water.
Skin contact	No specific recommendations.
Eye contact	Rinse immediately with plenty of water.

4.2. Most important symptoms and effects, both acute and delayed

General information	No further relevant information available.
----------------------------	--

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	No specific recommendations.
-----------------------------	------------------------------

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog.
Unsuitable extinguishing media	Full water jet

5.2. Special hazards arising from the substance or mixture

NITODEK FS WEARCOAT FILLER

Specific hazards No further relevant information available.

Hazardous combustion products None known.

5.3. Advice for firefighters

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions For personal protection, see Section 8.

6.2. Environmental precautions

Environmental precautions No specific requirements are anticipated under normal conditions of use.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Collect powder using special dust vacuum cleaner with particle filter or carefully sweep into suitable waste disposal containers and seal securely.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions No specific requirements are anticipated under normal conditions of use.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions No special storage precautions required.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

QUARTZ

Long-term exposure limit (8-hour TWA): WEL 0,1 mg/m³

WEL = Workplace Exposure Limit

8.2. Exposure controls

Protective equipment



Appropriate engineering controls Provide adequate ventilation.

Eye/face protection Wear approved chemical safety goggles where eye exposure is reasonably probable.

Hand protection Wear protective gloves made of the following material: Polyvinyl chloride (PVC). Butyl rubber.

NITODEK FS WEARCOAT FILLER

Other skin and body protection	Wear appropriate clothing to prevent any possibility of skin contact.
Hygiene measures	When using do not eat, drink or smoke. Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated.
Respiratory protection	Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit. Particulate filter, type P2.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Powder.
Colour	Beige.
Odour	Odourless.
Odour threshold	Not determined.
pH	Not applicable.
Melting point	>1700°C
Initial boiling point and range	2230°C
Flash point	Not applicable.
Evaporation rate	Not applicable.
Evaporation factor	Not applicable.
Flammability (solid, gas)	No.
Upper/lower flammability or explosive limits	The product is not flammable.
Other flammability	Not applicable.
Vapour pressure	Not applicable.
Vapour density	Not applicable.
Relative density	Not determined.
Bulk density	1.2 g/cm ³
Solubility(ies)	Insoluble in water.
Partition coefficient	Not determined.
Auto-ignition temperature	Not applicable.
Decomposition Temperature	Not determined.
Viscosity	Not applicable.
Explosive properties	Not considered to be explosive.
Explosive under the influence of a flame	Not considered to be explosive.
Oxidising properties	Does not meet the criteria for classification as oxidising.

9.2. Other information

Other information	No data available.
--------------------------	--------------------

NITODEK FS WEARCOAT FILLER

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Stable at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Under normal conditions of storage and use, no hazardous reactions will occur. Will not polymerise.

10.4. Conditions to avoid

Conditions to avoid None known.

10.5. Incompatible materials

Materials to avoid Strong acids. Strong alkalis. Amines.

10.6. Hazardous decomposition products

Hazardous decomposition products None known.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects This product has low toxicity.

Inhalation May cause respiratory irritation.

Eye contact Dust in the eyes will cause irritation.

SECTION 12: Ecological Information

Ecotoxicity The product is not expected to be hazardous to the environment.

12.1. Toxicity

Toxicity Not considered toxic to fish.

12.2. Persistence and degradability

Persistence and degradability The product is not expected to be biodegradable.

12.3. Bioaccumulative potential

Partition coefficient Not determined.

12.4. Mobility in soil

Mobility Insoluble in water.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects No data available.

SECTION 13: Disposal considerations

NITODEK FS WEARCOAT FILLER

13.1. Waste treatment methods

General information Dispose of waste product or used containers in accordance with local regulations

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations Control of Substances Hazardous to Health Regulations 2002 (as amended).

EU legislation Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).
Commission Regulation (EU) No 453/2010 of 20 May 2010.
Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).

Guidance Workplace Exposure Limits EH40.

Authorisations (Title VII Regulation 1907/2006) No specific authorisations are known for this product.

Restrictions (Title VIII Regulation 1907/2006) No specific restrictions on use are known for this product.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

NITODEK FS WEARCOAT FILLER

General information	Only trained personnel should use this material. For professional users only.
Revision comments	This is first issue.
Revision date	15/01/2018
Revision	1
SDS number	26062
Hazard statements in full	H350 May cause cancer. H372 Causes damage to organs through prolonged or repeated exposure.