



SAFETY DATA SHEET NITOSEAL MS300

This SDS is not mandated under REACH Regulation (EC) No 1907/2006 and is provided for information only.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name NITOSEAL MS300

Product number 2008080UK9, 2008020UK9, 2008024UK9, 2008100UK9, 2008106UK9

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Joint sealant for floors.

1.3. Details of the supplier of the safety data sheet

Supplier Fosroc Limited
 Drayton Manor Business Park
 Coleshill Road
 Tamworth
 Staffordshire
 B78 3XN
 England
 Tel: +44 (0) 1827 262222
 Fax: +44 (0) 1827 262444
 enquiryuk@fosroc.com

1.4. Emergency telephone number

Emergency telephone +44 (0) 1827 265 279 (Monday-Sunday 24 hours a day)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Not Classified

Environmental hazards Not Classified

Human health The product is considered to be a low hazard under normal conditions of use. Prolonged skin contact may cause redness and irritation.

Environmental The product contains a substance which is toxic to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.

2.2. Label elements

Hazard statements NC Not Classified

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

NITOSEAL MS300

3.2. Mixtures

CALCIUM CARBONATE (STEARATE COATED)		30-60%
CAS number: 471-34-1	EC number: 207-439-9	
Classification Not Classified	Classification (67/548/EEC or 1999/45/EC) -	
DI-ISO-DECYL PHTHALATE		10-30%
CAS number: 68515-49-1	EC number: 271-091-4	
Classification Not Classified		
SILICA FLOUR (4-50 Micron)		5-10%
CAS number: 14808-60-7	EC number: 238-878-4	
Classification STOT RE 2 - H373		
Trimethoxy(2-methylpropyl)silane		1-5%
CAS number: 18395-30-7	EC number: 242-272-5	
Classification Flam. Liq. 3 - H226 Acute Tox. 4 - H302 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 STOT SE 3 - H335		
HYDROCARBONS, C9, aromatics		1-5%
CAS number: 64742-95-6	EC number: 918-668-5	REACH registration number: 01-2119455851-35-0000
Classification Flam. Liq. 3 - H226 STOT SE 3 - H335, H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411		
BIS-(2,2,6,6-TETRAMETHYL-4-PIPERIDINYL) SEBACATE		<1%
CAS number: 52829-07-9		
Classification Eye Irrit. 2 - H319 Aquatic Chronic 2 - H411	Classification (67/548/EEC or 1999/45/EC) -	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

NITOSEAL MS300

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	No specific recommendations. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing.
Inhalation	Move affected person to fresh air at once.
Ingestion	Rinse mouth thoroughly with water. Give plenty of water to drink. Do not induce vomiting. Get medical attention if any discomfort continues. Show this Safety Data Sheet to the medical personnel.
Skin contact	Remove affected person from source of contamination. Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if irritation persists after washing.
Eye contact	Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. Continue to rinse for at least 15 minutes. Get medical attention if irritation persists after washing. Show this Safety Data Sheet to the medical personnel.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	Irritation of nose, throat and airway.
Ingestion	May cause discomfort if swallowed.
Skin contact	Prolonged skin contact may cause redness and irritation.
Eye contact	Vapour or spray in the eyes may cause irritation and smarting.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically.
-----------------------------	------------------------

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards	During fire, gases hazardous to health may be formed. No unusual fire or explosion hazards noted.
Hazardous combustion products	Heating may generate the following products: Carbon monoxide (CO). Carbon dioxide (CO ₂). Oxides of nitrogen. Oxides of silicon

5.3. Advice for firefighters

Protective actions during firefighting	No specific firefighting precautions known.
Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	For personal protection, see Section 8.
-----------------------------	-----------------------------------------

6.2. Environmental precautions

NITOSEAL MS300

Environmental precautions Avoid discharge into drains or watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Collect and place in suitable waste disposal containers and seal securely. Take care as floors and other surfaces may become slippery.

6.4. Reference to other sections

Reference to other sections For waste disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Good personal hygiene procedures should be implemented. Avoid contact with skin and eyes.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry, cool and well-ventilated place.

Storage class Chemical storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

CALCIUM CARBONATE (STEARATE COATED)

Long-term exposure limit (8-hour TWA): WEL 10 mg/m³ Inhal. Dust 4 mg/m³ Resp. Dust

DI-ISO-DECYL PHTHALATE

Long-term exposure limit (8-hour TWA): WEL 5 mg/m³

SILICA FLOUR (4-50 Micron)

Long-term exposure limit (8-hour TWA): WEL 0.1 mg/m³ respirable dust

HYDROCARBONS, C9, aromatics

Long-term exposure limit (8-hour TWA): WEL 100 mg/m³

WEL = Workplace Exposure Limit

Ingredient comments WEL = Workplace Exposure Limits

HYDROCARBONS, C9, aromatics (CAS: 64742-95-6)

DNEL	Professional - Dermal; systemic effects: 25 mg/kg/day
	Professional - Inhalation; systemic effects: 150 mg/m ³
	Consumer - Oral; systemic effects: 11 mg/kg/day
	Consumer - Inhalation; systemic effects: 32 mg/m ³
	Consumer - Dermal; systemic effects: 11 mg/kg/day

AMINOPROPYLTRIMETHOXYSILANE (CAS: 13822-56-5)

DNEL	Workers - Dermal; Short term systemic effects: 8.3 mg/kg/day
	Workers - Dermal; Long term systemic effects: 8.3 mg/kg/day
	Workers - Inhalation; Short term systemic effects: 58 mg/m ³
	Workers - Inhalation; Long term systemic effects: 58 mg/m ³

NITOSEAL MS300

PNEC	<ul style="list-style-type: none"> - Fresh water; 0.33 mg/l - marine water; 0.033 mg/l - Intermittent release; 3.3 mg/l
-------------	----------------------------------------------------------------------------------------------------------------------------------------------------------

BIS-(2,2,6,6-TETRAMETHYL-4-PIPERIDINYL) SEBACATE (CAS: 52829-07-9)

DNEL	Workers - Inhalation; Long term, Short term local effects: 5.6 mg/m ³ Workers - Dermal; Long term, Short term systemic effects: 2.0 mg/kg
PNEC	<ul style="list-style-type: none"> - Fresh water; 0.005 mg/l - marine water; 0.0005 mg/l - STP; 1 mg/l

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate ventilation. Observe any occupational exposure limits for the product or ingredients.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles.

Hand protection

Wear protective gloves. Nitrile rubber. Rubber (natural, latex). The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material.

Other skin and body protection

Wear appropriate clothing to prevent any possibility of skin contact. Wear apron or protective clothing in case of contact.

Hygiene measures

Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

Respiratory protection

No specific recommendations. Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Paste.
Colour	Various colours.
Odour	Slight.
Odour threshold	Not determined.
pH	Not applicable.
Melting point	Not determined.
Initial boiling point and range	Not applicable.
Flash point	> 100°C
Evaporation rate	Not applicable.
Evaporation factor	Not applicable.

NITOSEAL MS300

Flammability (solid, gas)	No.
Upper/lower flammability or explosive limits	The product is not flammable.
Vapour pressure	< 0.001 kPa @ 20°C
Vapour density	Not determined.
Relative density	1.42 @ 20°C
Bulk density	Not determined.
Solubility(ies)	Insoluble in water.
Partition coefficient	Not determined.
Auto-ignition temperature	Not determined.
Decomposition Temperature	Not determined.
Viscosity	Not determined.
Explosive properties	Not considered to be explosive.
Explosive under the influence of a flame	Not considered to be explosive.
Oxidising properties	Does not meet the criteria for classification as oxidising.

9.2. Other information

Other information No data available.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Stable at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Under normal conditions of storage and use, no hazardous reactions will occur.

10.4. Conditions to avoid

Conditions to avoid Avoid excessive heat for prolonged periods of time.

10.5. Incompatible materials

Materials to avoid Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Hazardous decomposition products Heating may generate the following products: Oxides of carbon. Oxides of nitrogen. Oxides of silicon

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

ATE oral (mg/kg) 28,571.43

Acute toxicity - inhalation

NITOSEAL MS300

ATE inhalation (gases ppm)	257,142.86
ATE inhalation (vapours mg/l)	628.57
ATE inhalation (dusts/mists mg/l)	85.71

General information	This product has low toxicity. Only large quantities are likely to have adverse effects on human health.
Inhalation	Unlikely to be hazardous by inhalation because of the low vapour pressure of the product at ambient temperature. Vapour may irritate respiratory system/lungs.
Ingestion	May cause discomfort if swallowed. Ingestion of significant amounts may result in severe systemic effects.
Skin contact	Prolonged contact may cause redness, irritation and dry skin.
Eye contact	May irritate eyes.
Target organs	No specific target organs known.

Toxicological information on ingredients.

SILICA FLOUR (4-50 Micron)

Carcinogenicity

IARC carcinogenicity IARC Group 1 Carcinogenic to humans.

HYDROCARBONS, C9, aromatics

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 3,592.0

Species Rat

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 3,160.0

Species Rabbit

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ vapours mg/l) 6.2

Species Rat

ATE inhalation (vapours mg/l) 6.2

AMINOPROPYLTRIMETHOXYSILANE

Acute toxicity - oral

Notes (oral LD₅₀) LD₅₀ 2970 mg/kg, Oral, Rat

Acute toxicity - dermal

Notes (dermal LD₅₀) LD₅₀ >2000 mg/kg, Dermal, Rabbit

NITOSEAL MS300

BIS-(2,2,6,6-TETRAMETHYL-4-PIPERIDINYL) SEBACATE

Acute toxicity - oral

Notes (oral LD₅₀) LD₅₀ >2000 mg/kg, Oral, Rat

Acute toxicity - dermal

Notes (dermal LD₅₀) LD₅₀ >2000 mg/kg, Dermal, Rat

Acute toxicity - inhalation

Notes (inhalation LC₅₀) LC₅₀ 7.7 mg/l/4hr/day, Inhalation, Rat

Diocetyl tin Oxide

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 2,500.0

Species Rat

SECTION 12: Ecological information

Ecotoxicity The product contains substances which are toxic to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.

12.1. Toxicity

Toxicity Not considered toxic to fish.

Ecological information on ingredients.

HYDROCARBONS, C9, aromatics

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, : 9.2 mg/l, Oncorhynchus mykiss (Rainbow trout)

Acute toxicity - aquatic invertebrates EC₅₀, : 3.2 mg/l, Daphnia magna

Acute toxicity - aquatic plants EC₅₀, : 2.6 mg/l, Pseudokirchneriella subcapitata

AMINOPROPYLTRIMETHOXYSILANE

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: >934 mg/l, Brachydanio rerio (Zebra Fish)

Acute toxicity - aquatic invertebrates LC₅₀, 48 hours: 331 mg/l, Daphnia magna

Acute toxicity - aquatic plants EC₅₀, 72 hours: >1000 mg/l, Desmodemus subspicatus

Acute toxicity - microorganisms EC₅₀, 5.75 hours: 43 mg/l, Pseudomonas putida

BIS-(2,2,6,6-TETRAMETHYL-4-PIPERIDINYL) SEBACATE

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: 13 mg/l, Oncorhynchus mykiss (Rainbow trout)

NITOSEAL MS300

Acute toxicity - aquatic invertebrates LC₅₀, 24 hours: 17 mg/l, Daphnia magna

12.2. Persistence and degradability

Persistence and degradability The product is not readily biodegradable.

Biodegradation Not available.

Ecological information on ingredients.

HYDROCARBONS, C9, aromatics

Biodegradation Water - Degradation (%) 78: 28 days
The substance is readily biodegradable.

AMINOPROPYLTRIMETHOXYSILANE

Persistence and degradability The product is not readily biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential The product contains potentially bioaccumulating substances.

Partition coefficient Not determined.

Ecological information on ingredients.

AMINOPROPYLTRIMETHOXYSILANE

Bioaccumulative potential The product is not bioaccumulating. Hydrolyses

12.4. Mobility in soil

Mobility The product is insoluble in water. Not considered mobile.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

Ecological information on ingredients.

HYDROCARBONS, C9, aromatics

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current EU criteria.

AMINOPROPYLTRIMETHOXYSILANE

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current EU criteria.

BIS-(2,2,6,6-TETRAMETHYL-4-PIPERIDINYL) SEBACATE

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current EU criteria.

12.6. Other adverse effects

Other adverse effects None known.

SECTION 13: Disposal considerations

NITOSEAL MS300

13.1. Waste treatment methods

General information	Do not empty into drains, sewers or water courses. Note that fully cured material is not considered as hazardous waste.
Disposal methods	Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

SECTION 14: Transport information

General	The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).
----------------	--------------------------------------------------------------------------------------------------------------------

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations	The Control of Substances Hazardous to Health Regulations 2002 (SI 2002 No. 2677) (as amended).
EU legislation	Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended). Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended). Commission Regulation (EU) No 2015/830 of 28 May 2015.
Guidance	Workplace Exposure Limits EH40. Safety Data Sheets for Substances and Preparations.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

NITOSEAL MS300

SECTION 16: Other information

General information	Only trained personnel should use this material.
Revision comments	NOTE: Lines within the margin indicate significant changes from the previous revision.
Revision date	09/09/2019
Revision	3b
Supersedes date	12/06/2017
SDS number	11904
Hazard statements in full	H226 Flammable liquid and vapour. H302 Harmful if swallowed. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H319 Causes serious eye irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H373 May cause damage to organs (Lungs) through prolonged or repeated exposure if inhaled. H411 Toxic to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.