illbruck

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.04.2018

Version number 7

Revision: 23.04.2018

SECTION 1: Identification undertaking	on of the substance/mixture and of the company/
· 1.1 Product identifier	
· Trade name: illbruck OT015	
 MSDS code: A-I-OT015 1.2 Relevant identified uses of No further relevant information av Application of the substance I 	
 1.3 Details of the supplier of th Manufacturer/Supplier: tremco illbruck Ltd Coupland Road, Hindley Green, V T: +44 (0) 1942251400, F: +44 (msds@tremco-illbruck.com 	WIGAN, WN2 4HT
 Further information obtainable tremco illbruck Ltd Coupland Road, Hindley Green, V T: +44 (0) 1942251400, F: +44 (0) www.tremco-illbruck.co.uk, uk.inf 	Wigan, WN2 4HT)) 1942251410
• 1.4 Emergency telephone num During office hours tel.: +44 (0) 1 centre.	ber: 942251400. At all other times please contact your national poisoning
SECTION 2: Userando ident	
SECTION 2: Hazards ident	ification
• 2.1 Classification of the substa • Classification according to Reg	nce or mixture
· 2.1 Classification of the substa	nce or mixture gulation (EC) No 1272/2008
 2.1 Classification of the substation Classification according to Registry Flam. Liq. 2 H225 Highly flamm Eye Irrit. 2 H319 Causes series 	nce or mixture gulation (EC) No 1272/2008 nable liquid and vapour. bus eye irritation.
 2.1 Classification of the substation according to Registration according to Registr	nce or mixture gulation (EC) No 1272/2008 hable liquid and vapour. bus eye irritation. an allergic skin reaction.
 2.1 Classification of the substation Classification according to Registry Flam. Liq. 2 H225 Highly flamm Eye Irrit. 2 H319 Causes series 	nce or mixture gulation (EC) No 1272/2008 hable liquid and vapour. bus eye irritation. an allergic skin reaction.
 2.1 Classification of the substate Classification according to Regulate Flam. Liq. 2 H225 Highly flamm Eye Irrit. 2 H319 Causes series Skin Sens. 1 H317 May cause a STOT SE 3 H336 May cause a 2.2 Label elements Labelling according to Regulate 	nce or mixture gulation (EC) No 1272/2008 hable liquid and vapour. bus eye irritation. In allergic skin reaction. Irowsiness or dizziness.
 2.1 Classification of the substate Classification according to Regulate Flam. Liq. 2 H225 Highly flamm Eye Irrit. 2 H319 Causes serie Skin Sens. 1 H317 May cause a STOT SE 3 H336 May cause a Cause 1 H316 Cause 1 Label elements Labelling according to Regulate The product is classified and labe 	nce or mixture gulation (EC) No 1272/2008 hable liquid and vapour. bus eye irritation. In allergic skin reaction. Irowsiness or dizziness.
 2.1 Classification of the substate Classification according to Regulate Flam. Liq. 2 H225 Highly flamm Eye Irrit. 2 H319 Causes serie Skin Sens. 1 H317 May cause a STOT SE 3 H336 May cause a Cause 1 H316 Cause 1 Label elements Labelling according to Regulate The product is classified and labe 	nce or mixture gulation (EC) No 1272/2008 hable liquid and vapour. bus eye irritation. In allergic skin reaction. Irowsiness or dizziness.
 2.1 Classification of the substate Classification according to Regulate Flam. Liq. 2 H225 Highly flamm Eye Irrit. 2 H319 Causes serie Skin Sens. 1 H317 May cause a STOT SE 3 H336 May cause a 2.2 Label elements Labelling according to Regulate The product is classified and labe Hazard pictograms 	nce or mixture gulation (EC) No 1272/2008 hable liquid and vapour. bus eye irritation. In allergic skin reaction. Irowsiness or dizziness.
 2.1 Classification of the substate Classification according to Regulate Flam. Liq. 2 H225 Highly flamm Eye Irrit. 2 H319 Causes serie Skin Sens. 1 H317 May cause a STOT SE 3 H336 May cause a 2.2 Label elements Labelling according to Regulate The product is classified and labe Hazard pictograms GHS02 GHS07 	nce or mixture gulation (EC) No 1272/2008 hable liquid and vapour. bus eye irritation. In allergic skin reaction. Irowsiness or dizziness.
 2.1 Classification of the substate Classification according to Regulate Flam. Liq. 2 H225 Highly flamm Eye Irrit. 2 H319 Causes series Skin Sens. 1 H317 May cause as STOT SE 3 H336 May cause of 2.2 Label elements Labelling according to Regulate The product is classified and labe Hazard pictograms GHS02 GHS07 Signal word Danger Contains: ethyl acetate 	nce or mixture gulation (EC) No 1272/2008 hable liquid and vapour. bus eye irritation. In allergic skin reaction. Irowsiness or dizziness.
 2.1 Classification of the substate Classification according to Regulate Flam. Liq. 2 H225 Highly flamm Eye Irrit. 2 H319 Causes series Skin Sens. 1 H317 May cause as STOT SE 3 H336 May cause of 2.2 Label elements Labelling according to Regulate The product is classified and labe Hazard pictograms GHS02 GHS07 Signal word Danger Contains: ethyl acetate Phenol, methylstyrenated 	nce or mixture gulation (EC) No 1272/2008 hable liquid and vapour. bus eye irritation. In allergic skin reaction. Irowsiness or dizziness.
 2.1 Classification of the substate Classification according to Regulate Flam. Liq. 2 H225 Highly flamm Eye Irrit. 2 H319 Causes series Skin Sens. 1 H317 May cause as STOT SE 3 H336 May cause of 2.2 Label elements Labelling according to Regulate The product is classified and labe Hazard pictograms GHS02 GHS07 Signal word Danger Contains: ethyl acetate 	nce or mixture gulation (EC) No 1272/2008 hable liquid and vapour. bus eye irritation. In allergic skin reaction. Irowsiness or dizziness.
 2.1 Classification of the substate Classification according to Regulate Flam. Liq. 2 H225 Highly flamm Eye Irrit. 2 H319 Causes series Skin Sens. 1 H317 May cause as STOT SE 3 H336 May cause of 2.2 Label elements Labelling according to Regulate The product is classified and labe Hazard pictograms GHS02 GHS07 Signal word Danger Contains: ethyl acetate Phenol, methylstyrenated butanone 	nce or mixture gulation (EC) No 1272/2008 hable liquid and vapour. bus eye irritation. In allergic skin reaction. Irowsiness or dizziness. eine (EC) No 1272/2008 elled according to the CLP regulation.

llbruck

according to 1907/2006/EC, Article 31

Printing date 23.04.2018

Version number 7

Revision: 23.04.2018

Trade name: illbruck OT015

	(Contd. of page 1)
H319 Causes s	serious eye irritation.
H317 May caus	se an allergic skin reaction.
H336 May caus	se drowsiness or dizziness.
· Precautionary	statements
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves / eye protection.
P305+P351+P3	338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
 Supplemental 	information:
EUH066 Repea	ated exposure may cause skin dryness or cracking.
2.3 Other haza	ards
· Results of PB	T and vPvB assessment
· PBT: Not appli	cable.
• vPvB• Not ann	

• **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

• **Description:** Mixture of substances listed below with non-hazardous additions.

· Dangerous components:		
CAS: 141-78-6 EINECS: 205-500-4 Reg.nr.: 01-2119475103-46-xxxx	ethyl acetate Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	10-<20%
CAS: 78-93-3 EINECS: 201-159-0 Reg.nr.: 01-2119457290-43-xxxx	butanone Flam. Liq. 2, H225; Eye Irrit. 2, H319	5-<10%
CAS: 68512-30-1 EINECS: 270-966-8 Reg.nr.: 01-2119555274-38-xxxx	Phenol, methylstyrenated Skin Irrit. 2, H315; Skin Sens. 1, H317; Aquatic Chronic 3, H412	1-<5%
CVIIC		

· SVHC -

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

- General information: Take affected persons out of danger area and lay down.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

- If skin irritation continues, consult a doctor.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.04.2018

Version number 7

Revision: 23.04.2018

Trade name: illbruck OT015
 4.2 Most important symptoms and effects, both acute and delayed Headache Dizziness Nausea Allergic reactions Information for doctor: No further relevant information available. Hazards No further relevant information available. 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.
 SECTION 5: Firefighting measures 5.1 Extinguishing media Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam. For safety reasons unsuitable extinguishing agents: Water with full jet 5.2 Special hazards arising from the substance or mixture Formation of toxic gases is possible during heating or in case of fire. 5.3 Advice for firefighters Protective equipment: Wear self-contained respiratory protective device. Additional information Cool endangered receptacles with water spray. Collect contaminated fire fighting water separately. It must not enter the sewage system.
 SECTION 6: Accidental release measures 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away. Keep away from ignition sources. Ensure adequate ventilation. 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water. 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation. Dispose of contaminated material as waste according to Section 13. 6.4 Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.
 SECTION 7: Handling and storage 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. Avoid contact with the eyes and skin. Information about fire - and explosion protection: Fumes can combine with air to form an explosive mixture. Keep ignition sources away - Do not smoke. Protect against electrostatic charges.



according to 1907/2006/EC, Article 31

lillbruck

Printing date 23.04.2018

Version number 7

Revision: 23.04.2018

Trade name: illb	oruck OT015
------------------	-------------

(Contd. of page 3)

- 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- \cdot Requirements to be met by storerooms and receptacles: Store in a cool location.
- Information about storage in one common storage facility: Protect from heat and direct sunlight.
- \cdot Further information about storage conditions:
- Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Store receptacle in a well ventilated area.

• 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

141-78-6 ethyl acetate

WEL Short-term value: 1500 mg/m³, 400 ppm Long-term value: 200 ppm

78-93-3 butanone

WEL Short-term value: 899 mg/m³, 300 ppm Long-term value: 600 mg/m³, 200 ppm Sk, BMGV

·DNELs

· Long term effects

· Long term enects		
78-93-3 b	utanone	
Oral	consumer	31 mg/kg (human)
Dermal	industrial	1,116 mg/kg (human)
	consumer	412 mg/kg (human)
Inhalative	industrial	600 mg/m3 (human)
	consumer	106 mg/m3 (human)
· PNECs		
78-93-3 butanone		
PNEC 55	.8 mg/L (fre	sh water)

709 mg/L (sewage treatment plant)

55.8 mg/L (sporadic release)

- 55.8 mg/L (salt water)
- PNEC 22.5 mg/kg (soil)
 - 284.7 mg/kg (sediment (salt water))
 - 284.7 mg/kg (sediment (fresh water))

· Ingredients with biological limit values:

78-93-3 butanone BMGV 70 μmol/L Medium: urine

Sampling time: post shift Parameter: butan-2-one

(Contd. on page 5)

illbruck

according to 1907/2006/EC, Article 31

Printing date 23.04.2018

Version number 7

Revision: 23.04.2018

Trade name: illbruck OT015

(Contd. of page 4)

 Additional information: The lists valid during the making were used as basis. HSE EH40/2005 Workplace Exposure Limits (as amended)

· 8.2 Exposure controls

- · Personal protective equipment:
- General protective and hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not eat, drink, smoke or sniff while working.

Avoid contact with the eyes and skin.

· Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation. Filter A

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

Nitrile rubber, NBR

PVA gloves

Fluorocarbon rubber (Viton)

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· Body protection:



Protective work clothing

(Contd. on page 6)

illbruck

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.04.2018

Version number 7

Revision: 23.04.2018

Trade name: illbruck OT015

(Contd. of page 5)

SECTION 9: Physical and chemi	cal properties
• 9.1 Information on basic physical and • General Information	chemical properties
 Appearance: Form: 	Liquid
Colour:	Black
· Odour:	Sweetish
· Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	: Undetermined.
· Flash point:	-7 °C (IP523 Seta)
· Ignition temperature:	>200 °C
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Density at 20 °C:	1.13 g/cm ³
 Solubility in / Miscibility with water: 	Not miscible / difficult to mix.
 Viscosity: Dynamic at 20 °C: 	1100000 mPas
 Solvent content: VOC (EC) 9.2 Other information 	244 g/l No further relevant information available.
 SECTION 10: Stability and react 10.1 Reactivity Stable 10.2 Chemical stability Thermal decomposition / conditions to No decomposition if used according to s 10.3 Possibility of hazardous reaction 10.4 Conditions to avoid No further relivant 10.5 Incompatible materials: No further 10.6 Hazardous decomposition produce Possible in traces. Nitrogen oxides Carbon monoxide and carbon dioxide 	to be avoided: pecifications. Is Reacts with strong acids and oxidising agents. evant information available. er relevant information available.
SECTION 11: Toxicological info	rmation
 • 11.1 Information on toxicological efference • Acute toxicity Based on available data, 	
· LD/LC50 values relevant for classifica	
141-78-6 ethyl acetate	

141-78-6 ethyl acetate

Oral	LD50	5,620 mg/kg (rabbit)	
Inhalative	LC0/4 h	8,000 ppm (rat)	



GR

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.04.2018

Version number 7

Revision: 23.04.2018

Trade name: illbruck OT015 (Contd. of page 6) LC50/4 h 70.56 mg/L (rabbit) 1,600 mg/L (rat) 78-93-3 butanone LD50 Oral 3,300 mg/kg (rat) Dermal LD50 5,000 mg/kg (rabbit) Inhalative LC50/4 h 34 mg/L (rat) · Primary irritant effect: · Skin corrosion/irritation Irritating effect. Repeated exposure may cause skin dryness or cracking. · Serious eye damage/irritation Causes serious eye irritation. · Respiratory or skin sensitisation May cause an allergic skin reaction. · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction) · Germ cell mutagenicity Based on available data, the classification criteria are not met. · Carcinogenicity Based on available data, the classification criteria are not met. • **Reproductive toxicity** Based on available data, the classification criteria are not met. · STOT-single exposure May cause drowsiness or dizziness. • STOT-repeated exposure Based on available data, the classification criteria are not met. · Aspiration hazard Based on available data, the classification criteria are not met. **SECTION 12: Ecological information** · 12.1 Toxicity · Aquatic toxicity: 78-93-3 butanone LC0/96 h 2,993 mg/L (pimephales promelas) EC50/48 h 308 mg/L (daphnia magna) · 12.2 Persistence and degradability No further relevant information available. • 12.3 Bioaccumulative potential No further relevant information available. · 12.4 Mobility in soil No further relevant information available. · Additional ecological information: · General notes: The product contains materials that are harmful to the environment. Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage svstem. · 12.5 Results of PBT and vPvB assessment • **PBT:** Not applicable. • **vPvB:** Not applicable. • 12.6 Other adverse effects No further relevant information available. (Contd. on page 8)

illbruck

(Contd. of page 7)

according to 1907/2006/EC, Article 31

Printing date 23.04.2018

Version number 7

Revision: 23.04.2018

Trade name: illbruck OT015

SECTION 13: Disposal considerations 13.1 Waste treatment methods Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system. Disposal must be made according to official regulations. · European waste catalogue 08 04 09* waste adhesives and sealants containing organic solvents or other hazardous substances HP 3 Flammable HP 4 Irritant - skin irritation and eye damage · Uncleaned packaging: · Recommendation: Dispose of packaging according to regulations on the disposal of packagings. Packagings that may not be cleansed are to be disposed of in the same manner as the product. Non contaminated packagings may be recycled. **SECTION 14: Transport information** · 14.1 UN-Number · ADR, ADN, IMDG, IATA UN1133 · 14.2 UN proper shipping name · ADR **1133 ADHESIVES** · IMDG, IATA **ADHESIVES** · 14.3 Transport hazard class(es) · ADR · Class 3 (F1) Flammable liquids. · Label 3 · IMDG, IATA 3 Flammable liquids. Class · Label 3 · 14.4 Packing group · ADR, IMDG, IATA Ш · 14.5 Environmental hazards: · Marine pollutant: No (Contd. on page 9) - GB



according to 1907/2006/EC, Article 31

Printing date 23.04.2018

Version number 7

Revision: 23.04.2018

Trade name: illbruck OT015 (Contd. of page 8) 14.6 Special precautions for user Warning: Flammable liquids. · Danger code (Kemler): 33 · EMS Number: F-E,S-D Stowage Category А · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable. Transport/Additional information: · ADR · Limited quantities (LQ) 5L · Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml · Transport category 3 · Tunnel restriction code D/E 14.4 : PG III; ADR 2.2.3.1.4 · Remarks: · IMDG Limited quantities (LQ) 5L · Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml · Remarks: 14.4 : PG III; IMDG 2.3.2.2 - 2.3.2.3 · IATA · Remarks: 14.4 : PG III; IATA 3.3.3

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

"CLP" Regulation (EC) No 1272/2008 (OJ L 353, 31.12.2008, p.1). "REACH" Regulation (EC) No 1907/2006 (OJ L 396, 30.12.2006, p.1, with subsequent amendments). COMMISSION REGULATION (EU) 2015/830 of 28 May 2015. HSE EH40/2005 Workplace Exposure Limits (as amended) Guidance on the classification and assessment of waste | Technical Guidance WM3 (1st edition 2015) 2001/118/EC as regards the list of wastes 2008/98/EC on waste

UN 1133 ADHESIVES, 3, III

· Directive 2012/18/EU

· UN "Model Regulation":

 \cdot Qualifying quantity (tonnes) for the application of lower-tier requirements $5.000\ t$

- \cdot Qualifying quantity (tonnes) for the application of upper-tier requirements $50.000\ t$
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

(Contd. on page 10)

- GB

according to 1907/2006/EC, Article 31

Printing date 23.04.2018

Version number 7

Revision: 23.04.2018

Trade name: illbruck OT015

(Contd. of page 9)

· National regulations:

- Information about limitation of use: Employment restrictions concerning juveniles must be observed.
- · Other regulations, limitations and prohibitive regulations
- · Substances of very high concern (SVHC) according to REACH, Article 57 Not applicable.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases H225 Highly flammable liquid and vapour. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H412 Harmful to aquatic life with long lasting effects. · Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) PNEC: Predicted No-Effect Concentration (REACH) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids - Category 2 Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 Skin Sens. 1: Skin sensitisation - Category 1 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3 \cdot * Data compared to the previous version altered. GR

