

# DPR PRIMER

SUBSTRATE PREPARATION FOR THE PAREXTHERM ACRYLIC  
AND PAREXDIRECT ACRYLIC RENDER SYSTEMS

**PAREX**  
Building expertise, together



## DESCRIPTION

100% acrylic-based, ready-to-use primer designed to adjust the base absorption to substrates, prior to the application of Parex DPR Finishes. DPR PRIMER is water-vapour permeable. It does not create a vapour retarder.

This product is also known as REVLANE+ REGULATEUR.

## SUBSTRATES

### SUITABLE FOR

- Exterior and interior.
- In situ and pre-formed concrete.
- Base coats in accordance with BS EN 13914-1.
- PAREX grey one-coat renders e.g. PARMUREX or Parex waterproofing undercoat systems.
- MAITE base coat.
- Parex coloured one-coat renders e.g. Monorex GF.
- PAREXTHERM and PAREXDIRECT render system.
- Internal walls, drylining, plaster (gypsum) substrates.
- Painted substrates.
- Parex profiles.

## TECHNICAL CHARACTERISTICS

### COMPOSITION

Binder base: 100 per cent acrylic.

- Pigment base: titanium dioxide.
- Water based.
- Colour: white or tinted to desired colour.

### EQUIPMENT REQUIRED

- Woollen roller, brush or suitable spray equipment.

Clean all tools with water after the application.

### PRODUCT PREPARATION

- Thoroughly mix the product in the bucket until it is of an even consistency.
- Up to 7.5 litres of clean potable water can be added to dilute the product but this will decrease the depth of colour. Ensure the same amount of water is added to all buckets used on the same project otherwise colour variations will be noticeable.
- When mixing avoid creating air bubbles or foam.

A full range of project specifications for different substrates and systems using Parex products are available through the NBS Scheme or directly from Parex Ltd. Visit the Parex website for regular updates, a Pre-Render Inspection form or refer to the PAREX TECHNICAL INFORMATION SHEETS for additional guidance.

## INSTRUCTIONS

### SUBSTRATE PREPARATION

- The substrate must be clean and free from dirt and dust.

### APPLICATION

- Apply DPR PRIMER using a woollen roller, brush or spray equipment.
- Allow to dry for 2 to 12 hours according to the temperature and the substrate, before applying the top coat finish.
- DPR PRIMER must be completely dry before any Parex finish is applied.

### COVERAGE

These values are provided as guidance only and may vary subject to substrate conditions.

One coat undiluted: 150 to 185m<sup>2</sup> per bucket, approximately, depending on the method of application and surface to which it is applied.

### DRYING TIME

- Approximately 1/2 to 4 hours depending on temperature, humidity and substrate.

### PRECAUTIONS

- For professional use only.
- Do not apply to a frozen substrate, where there is a risk of frost or rain, on wet substrates, in rain or foggy weather or if there is a strong, hot and dry wind.
- Temperature range: +5°C to + 30°C.
- Protect surfaces and exposed areas from rain during and immediately after application.
- Apply protection to all adjacent surfaces and exposed areas prior to application and leave in place until the material has fully cured.



### PACKAGING

27.7kg net weight in plastic buckets.

### STORAGE

1 year from date of manufacture if stored in unopened original packing in dry, frost-free conditions. Store away from high temperatures and sources of heat.

- Protect from sun at all times
- Do not stack more than 3 buckets high.

### WARRANTY

Manufacturer's 10 year product indemnity including design when a Parex specification is issued and subject to conditions.

### REFERENCE DOCUMENTS

#### European Technical Approvals:

- ETA-04/0014 - PAREXTHERM Mineral, Acrylic & Dash Systems on EPS.
- ETA-11/0110 - PAREXTHERM Mineral, Acrylic & Dash Systems on Mineral Wool.
- ETAG 004 2012 - PAREXTHERM Mineral, Acrylic & Dash Systems on Phenolic.

#### British Board or Agreements:

- BBA 10/4725 - PAREXTHERM & PAREXTHERM on Siniat Weather Defence board.

#### Irish Agreements:

- 09/0342 - PAREXTHERM systems.

#### Additional certifications:

- LABC and LABSS registered details.
- Premier Guarantee Warranty product approval.
- Conforms with the requirements of NHBC Render Chapter 6.11.

### HEALTH AND SAFETY

Wear suitable protective clothing, gloves and eye / face protection. This product contains materials which may cause an allergic reaction, is irritating to eyes and harmful if swallowed. In case of contact, seek medical advice. Keep out of the reach of children.

Read and follow the guidelines in the Health and Safety data sheet for this product.

### TECHNICAL ASSISTANCE

PAREX will, on request, provide information and assistance to companies in relation to the use of a specific product.

Such assistance shall not be associated with structural and design conception, nor assume or accept liability for compliance of substrates, nor compliance to instructions provided.

### Technical Information

**01827 711755**

Download the technical datasheet and consult the health and safety document on: [www.parex.co.uk](http://www.parex.co.uk)