

# PREPRUFE® SC1

Non-bituminous, quick drying, damp and green concrete tolerant solvent based primer for use with PREPRUFE® 800PA cold applied, self adhesive waterproof membrane

---

## Product Description

Preprufe® SC1 is a green coloured, non-bituminous, solvent based primer, which provides good initial adhesion of Preprufe 800PA non-bituminous adhesive membrane.

## Use

Used to prime concrete surfaces, including “green” concrete or damp to touch substrates, as well as wood surfaces, on which Preprufe® 800PA membrane will be applied. Preprufe SC1 can be used on vertical and horizontal applications at -5 °C or above.

## Application

Preprufe SC1 may be applied by a roller or brush. Apply it to clean, dirt free, frost-free surfaces at a coverage rate of 10-12 m<sup>2</sup> per litre. Allow the primer to dry 30 minutes or until tack-free. Dry time may be longer in cold temperatures. Deep puddles of primer should be avoided as this will lengthen drying time. Do not apply directly to Preprufe 800PA membrane.

In general, priming should be limited to an area that can be covered with membrane within 24 hours. Areas that accumulate significant amounts of dust or dirt must be re-primed before membrane is applied.

## Advantages

- Quick drying – fast membrane application.
- Damp and green concrete tolerant.
- Active formulation for enhanced membrane adhesion.
- Compatible with Preprufe 800 PA membrane.
- Green colour to ensure proper coverage and to aid identification, and to avoid substitution.

### SUPPLY

|              |                  |
|--------------|------------------|
| Preprufe SC1 | 5 & 20 litre can |
|--------------|------------------|

---

|          |                       |
|----------|-----------------------|
| Coverage | 10-12 sq m per litre* |
|----------|-----------------------|

---

\* Depending upon method of application, surface porosity and ambient temperature.

---

### TYPICAL PROPERTIES

| Property | Typical Value |
|----------|---------------|
|----------|---------------|

---

|        |       |
|--------|-------|
| Colour | Green |
|--------|-------|

VOC

592 g/L

Curing at 20 °C

30 minutes

*All declared values shown in this data sheet are based on test results determined under laboratory conditions and with the product sample taken directly from stock in its original packing without any alteration or modification of its component parts.*

## Health and Safety

Preprufe SC1 must be handled properly and stored in well ventilated place. Read the product label and Safety Data Sheets before use. Users must comply with all risk and safety phrases. SDS's can be obtained from GCP Applied Technologies or from our web site at [gcpat.com](http://gcpat.com).

**[gcpat.uk](http://gcpat.uk) | United Kingdom customer service: +44 (0) 1480 478421**

This document is only current as of the last updated date stated below and is valid only for use in the United Kingdom. It is important that you always refer to the currently available information at the URL below to provide the most current product information at the time of use. Additional literature such as Contractor Manuals, Technical Bulletins, Detail Drawings and detailing recommendations and other relevant documents are also available on [www.gcpat.uk](http://www.gcpat.uk). Information found on other websites must not be relied upon, as they may not be up-to-date or applicable to the conditions in your location and we do not accept any responsibility for their content. If there are any conflicts or if you need more information, please contact GCP Customer Service.

Last Updated: 2018-08-24

**[gcpat.uk/solutions/products/preprufe-pre-applied-waterproofing-solutions/preprufe-sc1](http://gcpat.uk/solutions/products/preprufe-pre-applied-waterproofing-solutions/preprufe-sc1)**