

Revision Date 21.01.2015

Version 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

Sarnafil T Prep

1.2 Relevant identified uses of the substance or mixture and uses advised against

At present there is no complete information available on identified uses. When the data becomes available, it will be integrated into the safety data sheet.

1.3 Details of the supplier of the safety data sheet

| Company | : Sika Limited Watchmead Welwyn Garden City Hertfordshire AL7 1BQ United Kingdom |
|---------|--|
| | United Kingdom |

Telephone : +44 (0)1707 394444

1.4 Emergency telephone number

Emergency telephone num- : +44 (0)1707 363899 (available during office hours) ber

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Type of product : Mixture

Classification (REGULATION (EC) No 1272/2008)

| Flammable liquids, Category 2 Eye irritation, Category 2 Specific target organ toxicity - single ex- posure, Category 3, Central nervous system | H225: Highly flammable liquid and vapour. H319: Causes serious eye irritation. H336: May cause drowsiness or dizziness. |
|---|---|
| Classification (67/548/EEC, 1999/45/EC) | |
| Highly flammable | R11: Highly flammable. |
| Irritant | R36: Irritating to eyes. |
| | R67: Vapours may cause drowsiness and dizzi- ness. |
| | R66: Repeated exposure may cause skin dryness or cracking. |
| | |



2.2 Label elements

Revision Date 21.01.2015

| Labelling (REGULATION (EC) No 1272/2008) | | | | | |
|--|---|----------------------------|---|--|--|
| Hazard pictograms | : | | | | |
| Signal word | : | Danger | × | | |
| Hazard statements | : | H225 H319 H336 | Highly flammable liquid and vapour. Causes serious eye irritation. May cause drowsiness or dizziness. | | |
| Supplemental Hazard Statements | : | EUH066 | Repeated exposure may cause skin dry- ness or cracking. | | |
| Precautionary statements | : | Prevention: P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. | | |
| | | P233 P261 | Keep container tightly closed. Avoid breathing dust/ fume/ gas/ mist/ va- pours/ spray. | | |
| | | Response: | | | |
| | | - | IF ON SKIN (or hair): Take off immedi- ately all contaminated clothing. Rinse skin with water/shower. | | |
| | | P312 | Call a POISON CENTER or doctor/ physician if you feel unwell. | | |
| | | P370 + P378 | In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish. | | |

Version 1.0

Hazardous components which must be listed on the label:

203-539-1 1-methoxy-2-propanol •

Additional Labelling:

The data sheet for medical personnel is available at the here provided emergency address.

2.3 Other hazards

This mixture contains no substance considered to be persistent, bioaccumulating nor toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

| Chemical Name | Classification | Classification | Concentration | |
|---------------|----------------|----------------|---------------|--|
| | | | | |



Revision Date 21.01.2015

Version 1.0

| CAS-No. | (67/548/EEC) | (REGULATION | [%] |
|-----------------------------------|--------------|-------------------|----------------|
| EC-No. | | EC) No | |
| Registration number | | 1272/2008) | |
| butanone | F; R11 | Flam. Liq.2; H225 | >= 25 - < 50 |
| 78-93-3 | Xi; R36 | Eye Irrit.2; H319 | |
| 201-159-0 | R66 | STOT SE3; H336 | |
| 01-2119457290-43-XXXX | R67 | | |
| Substances with a workplace expos | sure limit : | | |
| 1-methoxy-2-propanol | R10 | Flam. Liq.3; H226 | >= 50 - <= 100 |
| 107-98-2 | R67 | STOT SE3; H336 | |
| 203-539-1 | | | |
| 01-2119457435-35-XXXX | | | |
| | | | |

For the full text of the R-phrases mentioned in this Section, see Section 16. For the full text of the H-Statements mentioned in this Section, see Section 16.

Components according to Detergents Regulation EC 648/2004

Contains: (R)-p-mentha-1,8-diene

SECTION 4: First aid measures

4.1 Description of first aid measures

| General advice | Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance. |
|----------------------------|--|
| If inhaled | : Move to fresh air. Consult a physician after significant exposure. |
| In case of skin contact | Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician. |
| In case of eye contact | Immediately flush eye(s) with plenty of water. Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist. |
| If swallowed | : Clean mouth with water and drink afterwards plenty of water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. |
| 4.2 Most important symptom | s and effects, both acute and delayed |
| Symptoms | Excessive lachrymation Erythema Loss of balance Vertigo See Section 11 for more detailed information on health effects and symptoms. |



| Revision Date 21.01.2015 | Version 1.0 | Print Date 21.01.20 |
|------------------------------------|--|---------------------|
| | | |
| Risks | : irritant effects | |
| 4.3 Indication of any immediate r | nedical attention and special treatment need | led |
| Treatment | : Treat symptomatically. | |
| | | |
| SECTION 5: Firefighting meas | sures | |
| 5.1 Extinguishing media | | |
| Suitable extinguishing media | : Alcohol-resistant foam, Carbon dioxide (CC | 02), Dry chemical |
| Unsuitable extinguishing media | : Water | |
| 5.2 Special hazards arising from | the substance or mixture | |
| Hazardous combustion prod- ucts | : No hazardous combustion products are known | own |
| 5 3 Advice for firefighters | | |

| 5.3 A | dvice | for | firefighters |
|-------|-------|-----|--------------|
|-------|-------|-----|--------------|

| Special protective equipment for firefighters | : In the event of fire, wear self-contained breathing apparatus. |
|---|--|
| Further information | : Use water spray to cool unopened containers. |

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

| Personal precautions | : Use personal protective equipment. Remove all sources of ignition. Deny access to unprotected persons. |
|-----------------------------------|--|
| | Beware of vapours accumulating to form explosive concentra- tions. Vapours can accumulate in low areas. |
| 6.2 Environmental precautions | |
| Environmental precautions | : Prevent product from entering drains. If the product contaminates rivers and lakes or drains inform respective authorities. |
| 6.3 Methods and materials for con | tainment and cleaning up |
| Methods for cleaning up | : Contain spillage, and then collect with non-combustible ab- sorbent material, (e.g. sand, earth, diatomaceous earth, ver- miculite) and place in container for disposal according to local |
| Country GB 000000121979 | 4 / |



Revision Date 21.01.2015

Version 1.0

/ national regulations (see section 13).

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

| Advice on safe handling : | Do not breathe vapours or spray mist. Avoid exceeding of the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharge. Open drum carefully as content may be under pressure. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Follow standard hygiene measures when handling chemical products |
|--|---|
| Advice on protection against : fire and explosion | Use explosion-proof equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against electrostatic discharges. |
| Hygiene measures : | Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday. |
| 7.2 Conditions for safe storage, incl | uding any incompatibilities |
| Requirements for storage : areas and containers | Store in cool place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accordance with local regulations. |
| Other data : | No decomposition if stored and applied as directed. |
| 7.3 Specific end use(s) | |

Specific use(s)

: No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components with workplace control parameters

| Components | CAS-No. | Value | Control parame- ters * | Basis * |
|----------------------|----------|-------|---------------------------|------------|
| 1-methoxy-2-propanol | 107-98-2 | TWA | 100 ppm 375 mg/m3 | 2000/39/EC |



| Revision Date 21.01.2015 | Vers | Version 1.0 | | Print Date 21.01.2015 | |
|--------------------------|---------|-------------|----------------------|-----------------------|--|
| | | STEL | 150 ppm 568 mg/m3 | 2000/39/EC | |
| | | TWA | 100 ppm 375 mg/m3 | GB EH40 | |
| | | STEL | 150 ppm 560 mg/m3 | GB EH40 | |
| butanone | 78-93-3 | TWA | 200 ppm 600 mg/m3 | 2000/39/EC | |
| | | STEL | 300 ppm 900 mg/m3 | 2000/39/EC | |
| | | TWA | 200 ppm 600 mg/m3 | GB EH40 | |
| | | STEL | 300 ppm 899 mg/m3 | GB EH40 | |

Biological occupational exposure limits

| Substance name | CAS-No. | Control parameters | Sampling time | Basis |
|----------------|---------|---|---------------|----------------|
| butanone | 78-93-3 | butan-2-one: 70micromol per litre (Urine) | Post shift | GB EH40 BAT |

8.2 Exposure controls

| | Personal protective equipment | nt | |
|--------|-------------------------------|----|---|
| | Eye protection | : | Safety glasses with side-shields Eye wash bottle with pure water |
| | Hand protection | : | Chemical-resistant, impervious gloves complying with an ap- proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu- facturer specifications. |
| | | | Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (0,4 mm), Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min. |
| | Skin and body protection | : | Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work. |
| | Respiratory protection | : | Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. |
| - - | untry C.P. 00000121070 | | 6/1 |



Revision Date 21.01.2015

Version 1.0

organic vapor filter (Type A) A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

Environmental exposure controls

| General advice | : Prevent product from entering drains. |
|----------------|---|
| | If the product contaminates rivers and lakes or drains inform |
| | respective authorities. |

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

| Appearance | : | liquid |
|---|---|-------------------|
| Colour | : | various |
| Odour | : | characteristic |
| Odour Threshold | : | No data available |
| Flash point | : | -4 °C |
| Ignition temperature | : | No data available |
| Lower explosion limit | : | 1 %(V) |
| Upper explosion limit | : | 13,8 %(V) |
| Flammability (solid, gas) | : | No data available |
| Oxidizing properties | : | No data available |
| Auto-ignition temperature | : | No data available |
| рН | : | No data available |
| Melting point/range / Freez- ing point | : | No data available |
| Boiling point/boiling range | : | ca. 79 °C |
| Vapour pressure | : | ca.105 hPa |
| Density | : | ca.0,87 g/cm3 |



| Revision Date 21.01.2015 | | Version 1.0 | Print Date 21.01.2015 | |
|---|---|------------------------|-----------------------|--|
| | | at 20 °C | | |
| Water solubility | : | No data available | | |
| Partition coefficient: n- octanol/water | : | No data available | | |
| Viscosity, dynamic | : | No data available | | |
| Viscosity, kinematic | : | > 7 mm2/s at 40 °C | | |
| Relative vapour density | : | No data available | | |
| Evaporation rate | : | No data available | | |
| 9.2 Other information No data available | | | | |
| SECTION 10: Stability and reactivity | | | | |
| 10.1 Reactivity | | | | |
| No dangerous reaction known under conditions of normal use. | | | | |

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

| Hazardous reactions | : Stable under recommended storage conditions. |
|---------------------|--|
| | Vapours may form explosive mixture with air. |

10.4 Conditions to avoid

| Conditions to avoid : Heat | , flames and sparks. |
|----------------------------|----------------------|
|----------------------------|----------------------|

10.5 Incompatible materials

| Materials to avoid | : | No data available |
|--------------------|---|-------------------|
| | | |

10.6 Hazardous decomposition products

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Components:

butanone :



| Revision Date 21.01.2015 | Version 1.0 | Print Date 21.01.2015 |
|--|---|-----------------------|
| Acute oral toxicity | : LD50 Oral rat: 3.300 mg/kg | |
| Acute inhalation toxicity | : LC50 rat: 36 mg/l Exposure time: 4 h | |
| Acute dermal toxicity | : LD50 Dermal rabbit: > 5.000 mg/kg | |
| 1-methoxy-2-propanol : Acute oral toxicity | : LD50 Oral rat: > 5.000 mg/kg | |
| Acute inhalation toxicity | : LC50 : 7,5 mg/l Exposure time: 4 h | |
| Acute dermal toxicity | : LD50 Dermal rabbit: > 5.000 mg/kg | |
| Skin corrosion/irritation | | |
| Product | | |
| Repeated exposure may cau | se skin dryness or cracking. | |
| Serious eye damage/eye irritati | on | |
| Product | | |
| Causes serious eye irritation | | |
| Respiratory or skin sensitisatio | n | |
| Product | | |
| No data available | | |
| Germ cell mutagenicity | | |
| Product | | |
| Mutagenicity | : No data available | |
| Carcinogenicity | | |
| <u>Product</u> | | |
| Carcinogenicity | : No data available | |
| Reproductive Toxicity/Fertility | | |
| Reproductive toxicity | : No data available | |
| | | |
| No data available | | |



| Revision Date 21.01.2015 | Version 1.0 | Print Date 21.01.2015 |
|--------------------------|---------------------|-----------------------|
| Teratogenicity | : No data available | |
| No data available | | |
| STOT - single exposure | | |
| No data available | | |
| STOT - repeated exposure | | |
| No data available | | |
| Aspiration toxicity | | |
| No data available | | |
| | | |

SECTION 12: Ecological information

12.1 Toxicity

Components:

1-methoxy-2-propanol :

| Toxicity to fish | : | LC50: > 100 mg/l, 96 h, Fish |
|---|---|---------------------------------|
| Toxicity to daphnia and other aquatic invertebrates | : | EC50: > 100 mg/l, 48 h, Daphnia |

12.2 Persistence and degradability

This product does not contain any tensides according to the definition in the EU Detergents Regulation (EU/648/2004))

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

No data available



Revision Date 21.01.2015

Version 1.0

SECTION 13: Disposal considerations

13.1 Waste treatment methods Product : The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. : 07 07 04* other organic solvents, washing liquids and mother European Waste Catalogue liquors Contaminated packaging : 15 01 10* packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

| ADR 14.1 UN number 14.2 Description of the goods 14.3 Class 14.4 Packing group Classification Code Labels Tunnel restriction code 14.5 Environmentally hazard- ous | 1993 FLAMMABLE LIQUID, N.O.S. (1-methoxy-2-propanol, butanone) 3 II F1 3 (D/E) no |
|---|--|
| IATA 14.1 UN number 14.2 Description of the goods 14.3 Class 14.4 Packing group Labels 14.5 Environmentally hazard- ous | 1993 Flammable liquid, n.o.s. (1-methoxy-2-propanol, butanone) 3 II 3 no |

IMDG



| Revision Date 21.01.2015 | Version 1.0 |
|---|---|
| 14.1 UN number 14.2 Description of the goods | : 1993 : FLAMMABLE LIQUID, N.O.S. (1-methoxy-2-propanol, butanone) |
| 14.3 Class | : 3 |
| 14.4 Packing group | : 11 |
| Labels | : 3 |
| EmS Number 1 | : F-E |
| EmS Number 2 | : S-E |
| 14.5 Marine pollutant | : no |

14.6 Special precautions for user

No data available

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Labelling according to EC Directives (1999/45/EC)

| | ns : | |
|--|---|--|
| | × | |
| Highly flammable | Irritant | |
| R-phrase(s) | : R11 R36 R66 R67 | Highly flammable. Irritating to eyes. Repeated exposure may cause skin dry- ness or cracking. Vapours may cause drowsiness and dizzi- ness. |
| the market and us | tions on the manufacture, pl se of certain dangerous sub | |
| | articles (Annex XVII) | |
| REACH - Candida | articles (Annex XVII) ate List of Substances of Ve orisation (Article 59). | |
| REACH - Candida Concern for Autho | ate List of Substances of Ve | ery High : None of the components are listed (=> 0.1 %). |
| REACH - Candida Concern for Author REACH - List of s | ate List of Substances of Ve orisation (Article 59). substances subject to author ion: All substar - preregiste - preregiste - preregiste | ery High : None of the components are listed (=> 0.1 %). |



| Revision Date 21.01.2015 | Version 1.0 | Print Date 21.01.201 |
|---|---|------------------------------|
| | - exempted from the registration | n. |
| VOC-CH (VOCV) | : 99,67 % | |
| VOC-EU (solvent) | : 99,67 % | |
| If other regulatory information Sheet, then it is described | ation applies that is not already provided d in this subsection. | elsewhere in the Safety Data |

| Health, safety and environ- mental regulation/legislation specific for the substance or mixture: | The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002 Control of Substances Hazardous to Health Regulations 2002 The Management of Health and Safety at Work Regulations 1999 Health and Safety at Work Act 1974 Environmental Protection Act 1990 & Subsidiary Regulations |
|---|--|
| | Environmental Protection Act 1990 & Subsidiary Regulations |

15.2 Chemical Safety Assessment

This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

Full text of R-Phrases

| R10 | Flammable. |
|-----|---|
| R11 | Highly flammable. |
| R36 | Irritating to eyes. |
| R66 | Repeated exposure may cause skin dryness or cracking. |
| R67 | Vapours may cause drowsiness and dizziness. |
| | |

Full text of H-Statements

| H225 | Highly flammable liquid and vapour. |
|------|-------------------------------------|
| H226 | Flammable liquid and vapour. |
| H319 | Causes serious eye irritation. |
| H336 | May cause drowsiness or dizziness. |

Full text of other abbreviations

| Eye Irrit. | Eye irritation |
|------------|--|
| Flam. Liq. | Flammable liquids |
| STOT SE | Specific target organ toxicity - single exposure |

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any any use and processing.

Changes as compared to previous version !

Revision Date 21.01.2015

Version 1.0

