



Scree/master Universal Primer

VERSATILE PRIMER FOR USE WITH ALL SCREE/MASTER SMOOTHING COMPOUNDS

Date: 08 July 2015

Fact Sheet No.: TDS00878

YOUR SMART ADVANTAGES

- A bonding agent for non-porous surfaces
- A primer for porous surfaces
- For fast track installations

USES

Bostik Scree/master Universal Primer is a water based solvent free, acrylic dispersion primer. Use as a primer/bonding agent prior to the application of any of the Scree/master range of smoothing compounds. In undiluted form it can be used on all smooth and dense surfaces, power floated concrete, ceramic tile, quarry tile, rigid metal, terrazzo, asphalt and surface membranes. In diluted form (1 : 2 with clean water) it can be used on porous substrates, including sand/cement and wooden boards etc.

PRODUCT CHARACTERISTICS

Colour	Black
Form	Liquid
Composition	Polymer mix
Specific Gravity	1.0 approx.
Product Code	30811756 5 Litres x 4
Storage/Shelf Life	Store for up to 12 months from date of manufacture when stored in original, unopened packaging under cool, dry conditions within the temperature range of +5°C to +40°C and out of direct sunlight. Protect from frost.

TYPICAL PERFORMANCE DATA (Approx.)

Coverage	Undiluted as a bonding aid: 75 to 100m ² Diluted as a primer: 120 to 150m ²
Application Temperature	+5°C to +40°C
Service Temperature	Up to 40°C
Drying Times	Less than 1 hour under good drying conditions

DIRECTIONS FOR USE

IMPORTANT: Before using Bostik Scree/master Universal Primer refer to the relevant Health and Safety Data Sheet, available at www.bostik.co.uk.

All phases of installation should comply with the latest editions of:

- BS 8102 Code of Practice for protection of buildings against water from the ground.
- BS 5325 Code of Practice for installation of textile floor coverings.
- BS 8203 Code of Practice for installation of resilient floor coverings.
- BS 8201 Code of Practice for flooring of timber, timber products and wood based panel products.

PREPARATION

Subfloor:

1. Ensure the subfloor is clean, sound, dry and free from contaminants that may hinder adhesion.
2. Bostik Scree/master Universal Primer can be used over traces of old adhesive residues providing that they are well bonded and non-moisture soluble. (However it is not suitable for use over tackifier, bituminous or water-soluble adhesives which should be completely removed).



FM 01696
BS EN ISO 9001:2008

Bostik Limited, Common Road, Stafford, ST16 3EH, UK. Tel: +44 (0) 1785 272625 www.bostik.co.uk

Bostik, Evo-Stik & Sealocrete are registered trademarks of Bostik Ltd.

3. The subfloor should be tested in accordance with British Standards, using a properly calibrated and insulated hygrometer.
4. A reading of 75% RH or less confirms that the subfloor is satisfactorily dry. Where this has not been attained, it is necessary to apply a Screedmaster surface membrane to suppress residual moisture. For further information contact Flooring Technical Services.

APPLICATION

Smooth Dense Surfaces:

5. Apply using a brush or roller, ensuring that a thin even coat is obtained.

Porous Surfaces:

6. Apply the diluted Bostik Screedmaster Universal Primer by brush or roller, ensuring that it is well worked into the surface.
7. On porous surfaces or any surfaces likely to produce air holes in a smoothing compound, a second application will be required.

DRYING TIME

8. Bostik Screedmaster Universal Primer will dry within one hour under good drying conditions. However, under cold damp conditions this will be extended.
9. Conversely, drying times can be reduced with good ventilation, low ambient humidity and moderate heat.
10. Avoid using heaters that produce water vapour, such as fuel burning space heaters, as these will slow the drying rate.
11. Bostik Screedmaster smoothing compounds can be applied as soon as the primed surface is dry.

CLEANING

12. Clean tools and equipment immediately after use with water or white spirit if the material has dried.

PRECAUTIONS IN USE

For any application not covered please contact Technical Services on +44 (0)1785 272625 or visit www.bostik.co.uk for advice.

Recommendations and suggestions are for guidance only, since conditions of use are completely beyond our control.

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate Health and Safety Data Sheet for Bostik Screedmaster Universal Primer, available at www.bostik.co.uk.

BOSTIK HOTLINE

Smart help +44 (0) 1785 272625



FM 01696
BS EN ISO 9001:2008

Bostik Limited, Common Road, Stafford, ST16 3EH, UK. Tel: +44 (0) 1785 272625 www.bostik.co.uk

Bostik, Evo-Stik & Sealocrete are registered trademarks of Bostik Ltd.

This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company which may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability which cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use which is inappropriate or use which is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company.

Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue. Destroy all previous TDS, and if in any doubt, contact the Company, quoting the code number in the top right hand corner on the front of this document.

Sales	Tel: 0844 371 1192	Fax: 01785 241818	customer.service@bostik.com
Technical Advice	Tel: 0844 371 1197	Fax: 01785 272867	technical.service@bostik.com
Technical Data & COSHH (MSDS) Data Sheets	Tel: 01785 272625	Fax: 01785 212962	stafford.gatehouse@bostik.com



FM 01696
BS EN ISO 9001:2008

Bostik Limited, Common Road, Stafford, ST16 3EH, UK. Tel: +44 (0) 1785 272625 www.bostik.co.uk
Bostik, Evo-Stik & Sealocrete are registered trademarks of Bostik Ltd.