

PRODUCT DATA SHEET

Sika® FastFix All Weather

READY TO USE, SELF-SETTING PAVING JOINTING COMPOUND FOR ANY WEATHER

PRODUCT DESCRIPTION

Sika® FastFix All Weather is a ready-to-use, self-setting paving jointing compound with Active Resin Technology for advanced durability. It sets hard and will not wash out, whilst remaining water permeable. Sika® FastFix All Weather is perfect for outdoor patios, pavements and paths with joints over 5mm wide and 20mm deep. Fast and easy to use, it can be applied in any weather conditions even in the rain. Sika® FastFix All Weather can also be stored and reused after opening to reduce waste.

USES

Suitable for use on:

- Flagstones
- Cobbles
- Indian sandstone
- Stone setts
- Paving blocks
- Slabs
- Footpaths
- Patios
- Pavements
- Driveways with light vehicular traffic

CHARACTERISTICS / ADVANTAGES

- For joints over 5mm wide and 20mm deep
- Fast and easy application – no mixing
- All weather – apply even in the rain
- Robust - does not shrink or crack
- Highly water permeable – no pooling on the patio
- Weed control - provides a natural barrier for weed growth

PRODUCT INFORMATION

Packaging	14kg (grey) and 15kg (buff) pails containing 2 bags
Appearance / Colour	Grey, Buff
Shelf Life	12 months from the date of manufacture in sealed unopened bags.
Storage Conditions	Store in cool, dry conditions. Once opened use within 1 hour or store in the bucket, immersed in water, for up to 1 month.
Yield	15kg Buff: approx. 21m ² 450mm x 450mm paving (5mm x 20mm joints) 14kg Grey: approx. 20m ² 450mm x 450mm paving (5mm x 20mm joints)
Initial Set Time	6-12 hours above 15°C in dry conditions.

APPLICATION

1. Ensure the paving is installed as per watchpoints leaflet and all joints to be pointed with Sika® FastFix All Weather are free from standing water, dirt, debris or weeds. The dimensions of the joints must allow for a full compaction of the material once applied. The minimum joint depth should be at least 20mm and the joint width 5mm.
2. Thoroughly wet the entire area where Sika® FastFix All Weather is to be applied with water. This includes not only the joints, but also the entire slabs. Allow any standing water to drain before Sika® FastFix All Weather is applied.
3. Remove the product from the packaging and cut the foil pack. Once punctured or opened the material must be used within one hour. Any unused material can be stored in the bucket, immersed in water, for up to 1 month.
4. Use Sika® FastFix All Weather in small manageable amounts. Avoid spreading over a large area before application. Ensure material is all loose by raking through. Do not try to break up and use any small set lumps. Do not add any extra sand.
5. Using a soft broom, or hand brush for smaller areas, work Sika® FastFix All Weather into the joints. Make sure each joint is completely filled. If the freshly laid product is flooded, for instance due to rain, the setting period might be extended.
6. Using a suitable pointing trowel make sure the freshly applied Sika® FastFix All Weather is thoroughly compacted within the joints. The process should also smoothen/flatten the surface to the desired level. **The step of thorough compaction is essential.**
7. Sika® FastFix All Weather will start to set in 6-12 hours above 15°C in dry conditions. Allow up to 5 days for full set in temperatures between 4°C and 15°C. Contact with rain or moisture can temporarily soften the product if wetted before full set.

CLEANING OF TOOLS

Clean tools immediately after use with warm, soapy water.

LIMITATIONS

- The area for the patio **must** have good drainage
- Compaction is **essential**

VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

EVERBUILD BUILDING PRODUCTS LTD

Site 41, Knowsthorpe Way
Cross Green Industrial Estate
Leeds, LS9 0SW
Tel: 0113 240 3456
Web: www.everbuild.co.uk
Twitter: @everbuild

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited

SIKA IRELAND LIMITED

Ballymun Industrial Estate
Ballymun
Dublin 11, Ireland
Tel: +353 1 862 0709
Web: www.sika.ie
Twitter: @SikaIreland