

BUILDING TRUST

PRODUCT DATA SHEET Sika[®] Reemat Lite

GLASS FIBRE MAT REINFORCEMENT

PRODUCT DESCRIPTION

Sika[®] Reemat Lite is a glass fibre mat reinforcement for Sikagard[®] Hygienic Coating systems

USES

- Reinforcement for Sikagard[®] Hygienic Coating Systems
- Reinforcement for Sikagard[®] Hygienic Coating detailing
- For new construction and refurbishment projects

CHARACTERISTICS / ADVANTAGES

- Easy and quick application
- Easy to adjust to complicated details
- Ensures the correct thickness of the base coat
- Enhance the crack-bridging properties of the system
- Enhance mechanical properties of the system

PRODUCT INFORMATION

Chemical Base	Random glass fibre matting
Packaging	Rolls: 1m wide by 50m long
Appearance / Colour	White
Shelf Life	Product does not expire if correctly stored
Storage Conditions	The product must be stored properly in original, unopened and undam- aged sealed packaging, flat and wrinkle free, in dry conditions at temperat- ures between +5 °C and +35 °C.
Density	~30 g / m ²

SYSTEM INFORMATION

Systems

For detailed information regarding system build-ups, please refer to the System or Product Data Sheet of the relevant Sikagard[®] Hygieinc Coating System.

APPLICATION INSTRUCTIONS

APPLICATION

Prior the application of the Sikagard[®] Hygienic Coating System the priming coat if used must have cured for the appropriate Waiting Time / Overcoating (please refer to the PDS of the appropriate primer). Damageable areas (handrails etc.) have to be protected with tape or plastic wrapping.

Sika[®] Reemat Lite is applied in combination with Sikagard[®] Hygienic Coatings.

Apply first coat of Sikagard[®] Hygienic Coating with a consumption rate according to the PDS of the relevant hygienic coating system. Work only so far in advance that the material stays liquid.

Roll out the Sika[®] Reemat Lite and ensure that there are no bubbles or creases. Overlapping of Sika[®] Reemat Lite must be minimum 5 cm and ensure overlaps are sufficiently wet to bond.

The roller may require only a little extra material to remain wet but no further significant material needs to be added at this stage.

After the coat as had the appropriate Waiting Time / Overcoating contine with subsequent coats as per the relevant Sikagard[®] Hygienic Coating Datasheet / System Datasheet.

LIMITATIONS

Limitations will be dictated by the individual Sikagard[®] Hygienic Coating being used – Please consult relevant Product Datasheet / System Datasheet.

VALUE BASE

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

ECOLOGY, HEALTH AND SAFETY

REGULATION (EC) NO 1907/2006 - REACH

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA LIMITED

Watchmead Welwyn Garden City Hertfordshire, AL7 1BQ Tel: 01707 394444 Web: www.sika.co.uk Twitter: @SikaLimited



Product Data Sheet Sika® Reemat Lite January 2019, Version 03.01 020816110010000009 SIKA IRELAND LIMITED

Ballymun Industrial Estate Ballymun Dublin 11, Ireland Tel: +353 1 862 0709 Web: www.sika.ie Twitter: @Sikalreland





BUILDING TRUST