

SAFETY DATA SHEET  
according to Regulation (EC) No. 1907/2006  
**Sika® Screeding Mortar**



Revision Date 05.01.2016

Version 4.1

Print Date 05.01.2016

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Trade name : Sika® Screeding Mortar

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

### 1.3 Details of the supplier of the safety data sheet

Company : Sika Limited  
Watchmead  
Welwyn Garden City  
Hertfordshire AL7 1BQ  
United Kingdom

Telephone : +44 (0) 1707394444

### 1.4 Emergency telephone number

Emergency telephone number : +44 (0)1707 363899 (available during office hours)

---

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

Type of product : Mixture

#### Classification (REGULATION (EC) No 1272/2008)

Skin irritation, Category 2	H315: Causes skin irritation.
Serious eye damage, Category 1	H318: Causes serious eye damage.

### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements	: H315	Causes skin irritation.
	H318	Causes serious eye damage.

Precautionary statements	: <b>Prevention:</b>	
	P264	Wash skin thoroughly after handling.
	P280	Wear protective gloves/ eye protection/ face protection.
	<b>Response:</b>	
	P302 + P352	IF ON SKIN: Wash with plenty of water.

**SAFETY DATA SHEET**  
according to Regulation (EC) No. 1907/2006  
**Sika® Screeding Mortar**



Revision Date 05.01.2016

Version 4.1

Print Date 05.01.2016

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ physician.  
P332 + P313 If skin irritation occurs: Get medical advice/ attention.  
P362 + P364 Take off contaminated clothing and wash it before reuse.

Hazardous components which must be listed on the label:

- 266-043-4 Cement, portland, chemicals

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Hazardous components

Chemical Name CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration [%]
Cement, portland, chemicals 65997-15-1 266-043-4	Skin Irrit.2; H315 Eye Dam.1; H318 STOT SE3; H335	>= 10 - < 20
Substances with a workplace exposure limit :		
Quartz (SiO <sub>2</sub> ) 14808-60-7 238-878-4		>= 50 - <= 100
cristobalite 14464-46-1 238-455-4		>= 1 - < 2,5

For the full text of the H-Statements mentioned in this Section, see Section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.  
Consult a physician after significant exposure.

**SAFETY DATA SHEET**  
according to Regulation (EC) No. 1907/2006  
**Sika® Screeding Mortar**



Revision Date 05.01.2016

Version 4.1

Print Date 05.01.2016

- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
If symptoms persist, call a physician.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.  
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
Continue rinsing eyes during transport to hospital.  
Remove contact lenses.  
Keep eye wide open while rinsing.
- If swallowed : Do not induce vomiting without medical advice.  
Rinse mouth with water.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.

**4.2 Most important symptoms and effects, both acute and delayed**

- Symptoms : Excessive lachrymation  
Erythema  
Dermatitis  
See Section 11 for more detailed information on health effects and symptoms.
- Risks : irritant effects  
  
Causes skin irritation.  
Causes serious eye damage.

**4.3 Indication of any immediate medical attention and special treatment needed**

- Treatment : Treat symptomatically.

---

**SECTION 5: Firefighting measures**

**5.1 Extinguishing media**

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

**5.2 Special hazards arising from the substance or mixture**

- Hazardous combustion products : No hazardous combustion products are known

**5.3 Advice for firefighters**

- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
- Further information : Standard procedure for chemical fires.



---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

- Personal precautions : Use personal protective equipment.  
Avoid breathing dust.  
Deny access to unprotected persons.

### 6.2 Environmental precautions

- Environmental precautions : Try to prevent the material from entering drains or water courses.

### 6.3 Methods and materials for containment and cleaning up

- Methods for cleaning up : Pick up and arrange disposal without creating dust.  
Keep in suitable, closed containers for disposal.

### 6.4 Reference to other sections

- For personal protection see section 8.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

- Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Follow standard hygiene measures when handling chemical products
- Advice on protection against fire and explosion : Avoid dust formation. Provide appropriate exhaust ventilation at places where dust is formed.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

### 7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Store in accordance with local regulations.
- Other data : Keep in a dry place. No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

SAFETY DATA SHEET  
according to Regulation (EC) No. 1907/2006  
**Sika® Screeding Mortar**



Revision Date 05.01.2016

Version 4.1

Print Date 05.01.2016

Specific use(s) : No data available

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Components with workplace control parameters

Components	CAS-No.	Value	Control parameters *	Basis *
Quartz (SiO <sub>2</sub> )	14808-60-7	TWA	0,1 mg/m <sup>3</sup>	GB EH40
		TWA	6 mg/m <sup>3</sup>	GB EH40
		TWA	2,4 mg/m <sup>3</sup>	GB EH40
		TWA	0,1 mg/m <sup>3</sup>	GB EH40
Cement, portland, chemicals	65997-15-1	TWA	10 mg/m <sup>3</sup>	GB EH40
		TWA	4 mg/m <sup>3</sup>	GB EH40
crystalite	14464-46-1	TWA	0,1 mg/m <sup>3</sup>	GB EH40

### 8.2 Exposure controls

#### Personal protective equipment

Eye protection : Safety glasses with side-shields  
Eye wash bottle with pure water

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.

Recommended: Butyl rubber/nitrile rubber gloves.  
Contaminated gloves should be removed.

Skin and body protection : Dust impervious protective suit  
Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.

Respiratory protection : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.  
particulate filter P  
P1: Inert material; P2, P3: hazardous substances  
Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Meth-

**SAFETY DATA SHEET**  
according to Regulation (EC) No. 1907/2006  
**Sika® Screeding Mortar**



Revision Date 05.01.2016

Version 4.1

Print Date 05.01.2016

ods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficient to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

**Environmental exposure controls**

General advice : Try to prevent the material from entering drains or water courses.

---

**SECTION 9: Physical and chemical properties**

**9.1 Information on basic physical and chemical properties**

Appearance	: powder
Colour	: grey
Odour	: odourless
Odour Threshold	: No data available
Flash point	: Note: Not applicable
Autoignition temperature	: No data available
Lower explosion limit (Vol-%)	: No data available
Upper explosion limit (Vol-%)	: No data available
Flammability	: No data available
Oxidizing properties	: No data available
pH	: Note: Not applicable
Melting point/range / Freezing point	: No data available
Boiling point/boiling range	: No data available
Vapour pressure	: No data available
Density	: No data available
Bulk density	: 1.600 kg/m <sup>3</sup>
Water solubility	: Note: soluble
Partition coefficient: n-octanol/water	: No data available

SAFETY DATA SHEET  
according to Regulation (EC) No. 1907/2006  
**Sika® Screeding Mortar**



Revision Date 05.01.2016

Version 4.1

Print Date 05.01.2016

Viscosity, dynamic : No data available  
Viscosity, kinematic : Note: Not applicable  
Relative vapour density : No data available  
Evaporation rate : No data available

**9.2 Other information**

No data available

---

**SECTION 10: Stability and reactivity**

**10.1 Reactivity**

No dangerous reaction known under conditions of normal use.

**10.2 Chemical stability**

The product is chemically stable.

**10.3 Possibility of hazardous reactions**

Hazardous reactions : Stable under recommended storage conditions.

**10.4 Conditions to avoid**

Conditions to avoid : No data available

**10.5 Incompatible materials**

Materials to avoid : No data available

**10.6 Hazardous decomposition products**

Hazardous decomposition products :  
No decomposition if stored and applied as directed.

---

**SECTION 11: Toxicological information**

**11.1 Information on toxicological effects**

**Acute toxicity**

Not classified based on available information.

**Skin corrosion/irritation**

Causes skin irritation.

**Serious eye damage/eye irritation**

Causes serious eye damage.

**Respiratory or skin sensitisation**

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

SAFETY DATA SHEET  
according to Regulation (EC) No. 1907/2006  
**Sika® Screeding Mortar**



Revision Date 05.01.2016

Version 4.1

Print Date 05.01.2016

**Germ cell mutagenicity**

Not classified based on available information.

**Carcinogenicity**

Not classified based on available information.

**Reproductive toxicity**

Not classified based on available information.

**STOT - single exposure**

Not classified based on available information.

**STOT - repeated exposure**

Not classified based on available information.

**Aspiration toxicity**

Not classified based on available information.

---

**SECTION 12: Ecological information**

**12.1 Toxicity**

No data available

**12.2 Persistence and degradability**

No data available

**12.3 Bioaccumulative potential**

No data available

**12.4 Mobility in soil**

No data available

**12.5 Results of PBT and vPvB assessment**

**Product:**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

**12.6 Other adverse effects**

No data available

---

**SECTION 13: Disposal considerations**

**13.1 Waste treatment methods**

Product : The generation of waste should be avoided or minimized wherever possible.  
Empty containers or liners may retain some product residues.  
This material and its container must be disposed of in a safe



**SAFETY DATA SHEET**  
according to Regulation (EC) No. 1907/2006  
**Sika® Screeding Mortar**



Revision Date 05.01.2016

Version 4.1

Print Date 05.01.2016

way.

Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

European Waste Catalogue : 16 03 03\* inorganic wastes containing dangerous substances  
Contaminated packaging : 15 01 10\* packaging containing residues of or contaminated by dangerous substances

---

## SECTION 14: Transport information

### ADR

Not dangerous goods

### IATA

Not dangerous goods

### IMDG

Not dangerous goods

### 14.6 Special precautions for user

No data available

### 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

---

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Prohibition/Restriction

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : None of the components are listed (=> 0.1 %).

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

REACH Information: All substances contained in our Products are  
- preregistered or registered by our upstream suppliers, and/or  
- preregistered or registered by us, and/or  
- excluded from the regulation, and/or

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Sika® Screeding Mortar



Revision Date 05.01.2016

Version 4.1

Print Date 05.01.2016

- exempted from the registration.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

VOC-CH (VOCV) : no VOC duties

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environmental regulation/legislation specific for the substance or mixture: : The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002  
Control of Substances Hazardous to Health Regulations 2002  
The Management of Health and Safety at Work Regulations 1999  
Health and Safety at Work Act 1974  
Environmental Protection Act 1990 & Subsidiary Regulations

Other regulations : This product contains cement. Wet cement or mortar may cause alkali burns if in direct and/or prolonged contact with the skin. Wear protective clothing at all times when working with cement based products.

### 15.2 Chemical Safety Assessment

This product contains substances for which Chemical Safety Assessments are still required.

### SECTION 16: Other information

#### Full text of H-Statements

H315 Causes skin irritation.  
H318 Causes serious eye damage.  
H335 May cause respiratory irritation.

#### Full text of other abbreviations

Eye Dam. Serious eye damage  
Skin Irrit. Skin irritation  
STOT SE Specific target organ toxicity - single exposure  
ADR Accord européen relatif au transport international des marchandises Dangereuses par Route  
CAS Chemical Abstracts Service  
DNEL Derived no-effect level  
EC50 Half maximal effective concentration  
GHS Globally Harmonized System  
IATA International Air Transport Association  
IMDG International Maritime Code for Dangerous Goods

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Sika® Screeding Mortar



Revision Date 05.01.2016

Version 4.1

Print Date 05.01.2016

LD50	Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	Occupational Exposure Limit
PBT	Persistent, bioaccumulative and toxic
PNEC	Predicted no effect concentration
REACH	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	Substances of Very High Concern
vPvB	Very persistent and very bioaccumulative

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.



Changes as compared to previous version !