according to Regulation (EC) No. 1907/2006

# Sika® Watertight Concrete Powder

Revision Date 27.03.2020 Version 0.0 Print Date 27.03



### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : Sika® Watertight Concrete Powder

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Mortar

#### 1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Limited

Watchmead Welwyn Garden City

Hertfordshire. AL7 1BQ

Telephone : +44 (0)1707 394444
Telefax : +44 (0)1707 329129
E-mail address of person : EHS@uk.sika.com

responsible for the SDS

### 1.4 Emergency telephone number

+44 (0)1707 363899 (available during office hours).

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

### Classification (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture according to Regulation (EC) No. 1272/2008.

#### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture according to Regulation (EC) No. 1272/2008.

### **Additional Labelling**

EUH210 Safety data sheet available on request.

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

### Components

according to Regulation (EC) No. 1907/2006

# Sika® Watertight Concrete Powder



Revision Date 27.03.2020 Version 0.0 Print Date 27.03.2020

Chemical name	CAS-No.	Classification	Concentration	
	EC-No.		(% w/w)	
	Registration number			
Substances with a workplace exposure limit :				
calcium carbonate	471-34-1		>= 40 - < 50	
	207-439-9			
	01-2119486795-18-			
	XXXX			
Quartz (SiO2)	14808-60-7		>= 10 - < 20	
	238-878-4			
silicon dioxide	7631-86-9		>= 1 - < 2,5	
	231-545-4			
	01-2119379499-16-			
	XXXX			

#### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

General advice : No hazards which require special first aid measures.

If inhaled : Move to fresh air.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water.

In case of eye contact : Remove contact lenses.

Keep eye wide open while rinsing.

If swallowed : Do not induce vomiting without medical advice.

Rinse mouth with water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

#### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms : See Section 11 for more detailed information on health effects

and symptoms.

Risks : No known significant effects or hazards.

# 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

#### **SECTION 5: Firefighting measures**

### 5.1 Extinguishing media

Suitable extinguishing media : In case of fire, use water/water spray/water jet/carbon diox-

Revision Date 27.03.2020

according to Regulation (EC) No. 1907/2006

# Sika® Watertight Concrete Powder



ide/sand/foam/alcohol resistant foam/chemical powder for extinction.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion prod- : No hazardous combustion products are known

5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Further information Standard procedure for chemical fires.

**SECTION 6: Accidental release measures** 

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Avoid breathing dust.

6.2 Environmental precautions

Environmental precautions No special environmental precautions required.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up Keep in suitable, closed containers for disposal.

Sweep up or vacuum up spillage and collect in suitable con-

tainer for disposal.

6.4 Reference to other sections

For personal protection see section 8.

**SECTION 7: Handling and storage** 

7.1 Precautions for safe handling

Advice on safe handling For personal protection see section 8.

No special handling advice required.

Follow standard hygiene measures when handling chemical

products

fire and explosion

Advice on protection against : Avoid dust formation. Provide appropriate exhaust ventilation

at places where dust is formed.

Hygiene measures : When using do not eat or drink. When using do not smoke.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Keep container tightly closed in a dry and well-ventilated

place. Store in accordance with local regulations.

: No special restrictions on storage with other products. Advice on common storage

according to Regulation (EC) No. 1907/2006

# Sika® Watertight Concrete Powder



Revision Date 27.03.2020 Version 0.0 Print Date 27.03.2020

Further information on stor-

age stability

: Keep in a dry place. No decomposition if stored and applied

as directed.

7.3 Specific end use(s)

Specific use(s) : Consult most current local Product Data Sheet prior to any

use.

# **SECTION 8: Exposure controls/personal protection**

### 8.1 Control parameters

### **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *
calcium carbonate	471-34-1	TWA (inhalable dust)	10 mg/m3	GB EH40
	dust and inhal will be collected the methods of pling and grave aerosols, The health include in air equal to dust or 4 mg.r any dust will be above these less well wells and explimits., Most in sizes. The behafter entry into sponse that it HSE distinguistermed 'inhalate the fraction of during breathing trespiratory transpendent to tions and explications and explications of the relevant ling short-term expendent of the state of the	ration: For the purposation: For the purposation in MDHS1 imetric analysis or racios dust of any kind wor greater than 10 mans 8-hour TWA of racios as shour to COSHI evels. Some dusts housing the human respiral dustrial dusts containation, deposition as the human respiral elicits, depend on the gas exchange reanatory material the gas exchange reanatory material are components that ham its should be composure limit is listed, a limit should be use TWA (Respirable dust)	fractions of airbor undertaken in accupated and the espirable, thoracid for a substance has then present at a cong.m-3 8-hour TW respirable dust. The firm of the espirable dust. The firm of the espirable dust are not comply with the espirable dust are nature and size on a for limit-setting at enters the nose available for depose approximates to the espirable dust a service of the lung. It is given in MDHS14 we their own assignment of the lung. It is given in MDHS14 we their own assignment of the lung. It is given in MDHS14 we their own assignment of the lung. It is given in MDHS14 we their own assignment of the lung. It is given in MDHS14 we their own assignment of the lung. It is given in MDHS14 we their own assignment of the lung. It is given in MDHS14 we their own assignment of the lung. It is given in MDHS14 we their own assignment of the lung. It is given in MDHS14 we their own assignment of the lung. It is given in MDHS14 we their own assignment of the lung. It is given in MDHS14 we their own assignment of the lung. It is given in MDHS14 we their own assignment of the lung. It is given in MDHS14 we their own assignment of the lung. It is given in MDHS14 we their own assignment of the lung. It is given in MDHS14 we their own assignment of the lung. It is given in MDHS14 we their own assignment of the lung. It is given in MDHS14 we their own assignment of the lung. It is given in MDHS14 we their own as given in MDHS14 we the lung. It is given in MDHS14 we the lung. It is given in MDHS14 we the lung in MDHS14 we	ne dust which cordance with cods for sam- c and inhalable cardous to concentration (A of inhalable is means that cosed to dust d specific appropriate ide range of rticular particle he body resofthe particle. I purposes pproximates to e and mouth sition in the fraction that Fuller defini-4/4., Where gned WEL, all no specific
Quartz (SiO2)	14808-60-7	TWA (Respirable dust)	0,1 mg/m3 (Silica)	GB EH40
	dust and inhal will be collected the methods of	Further information: For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable		

according to Regulation (EC) No. 1907/2006

# Sika® Watertight Concrete Powder



Revision Date 27.03.2020 Version 0.0 Print Date 27.03.2020

				100.2020
	aerosols, The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m-3 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'., Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.			
silicon dioxide	7631-86-9	TWA (Respirable dust)	0,1 mg/m3	2004/37/EC
	Further information: Carcinogens or mutagens			1
		TWA (inhalable	6 mg/m3	GB EH40
		dust)	(Silica)	
	Further information: For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols, The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m-3 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'., Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.			

according to Regulation (EC) No. 1907/2006

# Sika® Watertight Concrete Powder



Revision Date 27.03.2020 Version 0.0 Print Date 27.03.2020

•	•	
TWA (Respirable	2.4 mg/m3	GB EH40
1 VV/ (1 (Copilabic	2, <del>4</del> mg/mo	OD LITTO
dust)	(Silica)	
l dust)	(Onica)	

<sup>\*</sup>The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

#### general dust value

Form of exposure	Value type	Control parameters	Basis
Inhalable	TWA	10 mg/m3	GB EH40
Respirable	TWA	4 mg/m3	GB EH40

#### 8.2 Exposure controls

#### Personal protective equipment

Eye protection : Safety glasses

Hand protection : Chemical-resistant, impervious gloves complying with an ap-

proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu-

facturer specifications.

Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345,

long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing

and stirring work.

Respiratory protection : In case of inadequate ventilation wear respiratory protection.

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work-

ing limits of the selected respirator.

particulate filter P

P1: Inert material: P2. P3: hazardous substances

Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

# **Environmental exposure controls**

General advice : No special environmental precautions required.

### **SECTION 9: Physical and chemical properties**

### 9.1 Information on basic physical and chemical properties

Appearance : powder
Colour : beige
Odour : slight

Odour Threshold : No data available

pH : No data available

according to Regulation (EC) No. 1907/2006

# Sika® Watertight Concrete Powder

Revision Date 27.03.2020 Version 0.0 Print Date 27.03.2020

Melting point/range / Freezing : No data available

Boiling point/boiling range : No data available

Flash point : Not applicable

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper

flammability limit

: No data available

Lower explosion limit / Lower : No data available

flammability limit

Vapour pressure : No data available

Relative vapour density : No data available

Density : 5 g/cm3

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: No data available

: No data available Auto-ignition temperature

Decomposition temperature : No data available

Viscosity

: No data available Viscosity, dynamic

Viscosity, kinematic : No data available

Explosive properties : No data available

Oxidizing properties : No data available

#### 9.2 Other information

No data available

# **SECTION 10: Stability and reactivity**

### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

#### 10.2 Chemical stability

The product is chemically stable.

according to Regulation (EC) No. 1907/2006

# Sika® Watertight Concrete Powder

Revision Date 27.03.2020 Version 0.0 Print D



### 10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

#### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

### **SECTION 11: Toxicological information**

### 11.1 Information on toxicological effects

#### **Acute toxicity**

Not classified based on available information.

#### **Components:**

#### silicon dioxide:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

Method: Expert judgement

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5.000 mg/kg

Method: Expert judgement

# Skin corrosion/irritation

Not classified based on available information.

### Serious eye damage/eye irritation

Not classified based on available information.

# Respiratory or skin sensitisation

### Skin sensitisation

Not classified based on available information.

#### Respiratory sensitisation

Not classified based on available information.

#### Germ cell mutagenicity

Not classified based on available information.

#### Carcinogenicity

Not classified based on available information.

### Reproductive toxicity

Not classified based on available information.

according to Regulation (EC) No. 1907/2006

# Sika® Watertight Concrete Powder

Revision Date 27.03.2020 Version 0.0 Print Date 27.03.2020



### STOT - single exposure

Not classified based on available information.

#### STOT - repeated exposure

Not classified based on available information.

#### **Aspiration toxicity**

Not classified based on available information.

### **SECTION 12: Ecological information**

#### 12.1 Toxicity

No data available

#### 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

No data available

#### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

#### **Product:**

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher...

#### 12.6 Other adverse effects

#### **Product:**

Additional ecological infor-

mation

: There is no data available for this product.

### **SECTION 13: Disposal considerations**

# 13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized

wherever possible.

Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe

way.

Dispose of surplus and non-recyclable products via a licensed

waste disposal contractor.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Avoid dispersal of spilled material and runoff and contact with

according to Regulation (EC) No. 1907/2006

# Sika® Watertight Concrete Powder

Print Date 27.03.2020 Revision Date 27.03.2020 Version 0.0



soil, waterways, drains and sewers.

# **SECTION 14: Transport information**

#### 14.1 UN number

Not regulated as a dangerous good

#### 14.2 UN proper shipping name

Not regulated as a dangerous good

#### 14.3 Transport hazard class(es)

Not regulated as a dangerous good

### 14.4 Packing group

Not regulated as a dangerous good

#### 14.5 Environmental hazards

Not regulated as a dangerous good

#### 14.6 Special precautions for user

Not applicable

#### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

#### **SECTION 15: Regulatory information**

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

preparations and articles (Annex XVII)

: Not applicable

: Not applicable

Not applicable

(=> 0.1 %).

Not applicable

Not applicable

None of the components are listed

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import

of dangerous chemicals

International Chemical Weapons Convention (CWC)

Schedules of Toxic Chemicals and Precursors

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

REACH - List of substances subject to authorisation

(Annex XIV)

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

Regulation (EU) 2019/1021 on persistent organic pollu-Not applicable

tants (recast)

**REACH Information:** All substances contained in our Products are

- registered by our upstream suppliers, and/or

- registered by us, and/or

- excluded from the regulation, and/or

- exempted from the registration.

Country GB 100000031493

Revision Date 27.03.2020

according to Regulation (EC) No. 1907/2006

# Sika® Watertight Concrete Powder



Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

Volatile organic compounds : Law on the incentive tax for volatile organic compounds

(VOCV) no VOC duties

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)

Not applicable

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environmental regulation/legislation specific for the substance or mixture:  Environmental Protection Act 1990 & Subsidiary Regulations Health and Safety at Work Act 1974 & Subsidiary Regulations Control of Substances Hazardous to Health Regulations (COSHH)

May be subject to the Control of Major Accident Hazards

Regulations (COMAH), and amendments.

### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

#### **SECTION 16: Other information**

#### Full text of other abbreviations

2004/37/EC : Europe. Directive 2004/37/EC on the protection of workers

from the risks related to exposure to carcinogens or mutagens

at work

GB EH40 : UK. EH40 WEL - Workplace Exposure Limits

2004/37/EC / TWA : Long term exposure limit

GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)
ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road

CAS : Chemical Abstracts Service
DNEL : Derived no-effect level

EC50 : Half maximal effective concentration GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

according to Regulation (EC) No. 1907/2006

# Sika® Watertight Concrete Powder



Revision Date 27.03.2020 Version 0.0 Print Date 27.03.2020

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic
PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

#### **Further information**

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

GB / EN