according to Regulation (EC) No. 1907/2006

SikaScreed® Rapid-75



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : SikaScreed® Rapid-75

1.2 Relevant identified uses of the substance or mixture and uses advised against

1.3 Details of the supplier of the safety data sheet

Company : Sika Limited

Watchmead

Welwyn Garden City Hertfordshire AL7 1BQ United Kingdom

: +44 (0)1707 394444 Telephone

1.4 Emergency telephone number

Emergency telephone num-

: +44 (0)1707 363899 (available during office hours)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Type of product : Mixture

Classification (REGULATION (EC) No 1272/2008)

Skin irritation, Category 2 H315: Causes skin irritation.

Serious eye damage, Category 1 H318: Causes serious eye damage.

Specific target organ toxicity - single ex-

posure, Category 3, Respiratory system

H335: May cause respiratory irritation.

2.2 Label elements

ber

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms





Signal word Danger

Hazard statements H315 Causes skin irritation.

H318 Causes serious eye damage. H335 May cause respiratory irritation.

according to Regulation (EC) No. 1907/2006

SikaScreed® Rapid-75

Revision Date 20.07.2017 Version 2.0



Precautionary statements : Prevention:

P261 Avoid breathing dust/ fume/ gas/ mist/ va-

pours/ spray.

P280 Wear protective gloves/ eye protection/ face

protection.

Response:

P304 + P340 + P312 IF INHALED: Remove person to fresh

air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel un-

well.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously

with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a

POISON CENTER/doctor.

Storage:

P403 + P233 Store in a well-ventilated place. Keep con-

tainer tightly closed.

Disposal:

P501 Dispose of contents/container in accord-

ance with local regulation.

Hazardous components which must be listed on the label:

• 266-043-4 Cement (chromium reduced)

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients


3.2 Mixtures

Hazardous components

| Chemical name CAS-No. | Classification (REGULATION (EC) | Concentration [%] | | | |
|---|---------------------------------|-------------------|--|--|--|
| EC-No. | No 1272/2008) | | | | |
| Registration number | | | | | |
| Cement (chromium reduced) | Skin Irrit.2; H315 | >= 10 - < 20 | | | |
| 65997-15-1 | Eye Dam.1; H318 | | | | |
| 266-043-4 | STOT SE3; H335 | | | | |
| | | | | | |
| hexacalcium hexaoxotris[sulphato(2-)]dialuminate(12-) | Skin Irrit.2; H315 | >= 5 - < 10 | | | |
| 12004-14-7 | Eye Dam.1; H318 | | | | |
| 234-448-5 | STOT SE3; H335 | | | | |
| | | | | | |
| Substances with a workplace exposure limit : | | | | | |
| Quartz (SiO2) | | >= 60 - < 80 | | | |
| 14808-60-7 | | | | | |
| 238-878-4 | | | | | |

according to Regulation (EC) No. 1907/2006

SikaScreed® Rapid-75



For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tis-

sue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses.

Keep eye wide open while rinsing.

If swallowed : Do not induce vomiting without medical advice.

Rinse mouth with water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Cough

Respiratory disorder Excessive lachrymation

Erythema Dermatitis

See Section 11 for more detailed information on health effects

and symptoms.

Risks : irritant effects

Causes skin irritation.
Causes serious eye damage.
May cause respiratory irritation.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

according to Regulation (EC) No. 1907/2006

SikaScreed® Rapid-75





SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

5.2 Special hazards arising from the substance or mixture

ucts

Hazardous combustion prod: No hazardous combustion products are known

5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Further information : Standard procedure for chemical fires.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Avoid breathing dust.

Deny access to unprotected persons.

6.2 Environmental precautions

Environmental precautions : Try to prevent the material from entering drains or water

courses.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Pick up and arrange disposal without creating dust.

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Do not breathe vapours/dust. Avoid exceeding the given oc-

> cupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the ap-

according to Regulation (EC) No. 1907/2006

SikaScreed® Rapid-75



plication area. Follow standard hygiene measures when han-

dling chemical products

Advice on protection against

fire and explosion

: Avoid dust formation. Provide appropriate exhaust ventilation

at places where dust is formed.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage

areas and containers

Store in original container. Keep in a well-ventilated place.
 Observe label precautions. Store in accordance with local

regulations.

Other data : Keep in a dry place. No decomposition if stored and applied

as directed.

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components with workplace control parameters

| Components | CAS-No. | Value | Control parame- | Basis * |
|---------------------------|------------|-------|-----------------|---------|
| | | | ters * | |
| Quartz (SiO2) | 14808-60-7 | TWA | 0,1 mg/m3 | GB EH40 |
| Cement (chromium reduced) | 65997-15-1 | TWA | 10 mg/m3 | GB EH40 |
| | | TWA | 4 mg/m3 | GB EH40 |

general dust value

| Form of exposure | Value type | Control parameters | Basis |
|------------------|------------|--------------------|---------|
| Inhalable | TWA | 10 mg/m3 | GB EH40 |
| Respirable | TWA | 4 mg/m3 | GB EH40 |

8.2 Exposure controls

Personal protective equipment

Eye protection : Safety glasses with side-shields conforming to EN166

Eye wash bottle with pure water

Hand protection : Chemical-resistant, impervious gloves complying with an ap-

Country GB 100000016515

5 / 12

according to Regulation (EC) No. 1907/2006

SikaScreed® Rapid-75

Revision Date 20.07.2017



proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu-

facturer specifications.

Recommended: Butyl rubber/nitrile rubber gloves.

Contaminated gloves should be removed.

Skin and body protection : Dust impervious protective suit

Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing

and stirring work.

Respiratory protection : Respirator selection must be based on known or anticipated

exposure levels, the hazards of the product and the safe work-

ing limits of the selected respirator.

particulate filter P

P1: Inert material; P2, P3: hazardous substances

Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

Environmental exposure controls

General advice : Try to prevent the material from entering drains or water

courses.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : powder

Colour : grey

Odour : odourless

Odour Threshold : No data available

Flash point : Not applicable

Autoignition temperature : No data available

Decomposition temperature : No data available

according to Regulation (EC) No. 1907/2006

SikaScreed® Rapid-75

Revision Date 20.07.2017 Version 2.0 Print Date 20.07.2017

Lower explosion limit (Vol-%) : No data available

Upper explosion limit (Vol-%) : No data available

Flammability : No data available

Explosive properties : No data available

Oxidizing properties : No data available

pH : No data available

Melting point/range / Freez-

Boiling point/boiling range

ing point

: No data available

: No data available

Vapour pressure : No data available

Density : 0,16 g/cm3

Bulk density : 1.600 kg/m3

Water solubility : insoluble

Partition coefficient: n-

octanol/water

: No data available

Viscosity, dynamic : No data available

Viscosity, kinematic : Not applicable

Relative vapour density : No data available

Evaporation rate : No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid : No data available

Country GB 100000016515

7 / 12

according to Regulation (EC) No. 1907/2006

SikaScreed® Rapid-75

Revision Date 20.07.2017 Version 2.0



10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified based on available information.

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause respiratory irritation.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

SECTION 12: Ecological information

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

according to Regulation (EC) No. 1907/2006

SikaScreed® Rapid-75

Revision Date 20.07.2017 Version 2.0



12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

12.6 Other adverse effects

Product:

Additional ecological infor-

mation

: There is no data available for this product.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized

wherever possible.

Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe

way.

Dispose of surplus and non-recyclable products via a licensed

waste disposal contractor.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

Contaminated packaging : 15 01 10* packaging containing residues of or contaminated

by dangerous substances

SECTION 14: Transport information

14.1 UN number

Not regulated as a dangerous good

14.2 UN proper shipping name

Not regulated as a dangerous good

according to Regulation (EC) No. 1907/2006

SikaScreed® Rapid-75

Revision Date 20.07.2017 Version 2.0



14.3 Transport hazard class(es)

Not regulated as a dangerous good

14.4 Packing group

Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

No data available

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Prohibition/Restriction

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

preparations and articles (Annex XVII)

: Banned and/or restricted (Cement (chromium reduced))

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

: None of the components are listed

(=> 0.1 %).

: Not applicable

REACH - List of substances subject to authorisation

(Annex XIV)

REACH Information:

All substances contained in our Products are

- preregistered or registered by our upstream suppliers, and/or

preregistered or registered by us, and/or
excluded from the regulation, and/or
exempted from the registration.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

VOC-CH (VOCV) : no VOC duties

VOC-EU (solvent) : Not applicable

according to Regulation (EC) No. 1907/2006

SikaScreed® Rapid-75





If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environmental regulation/legislation specific for the substance or mixture: : Environmental Protection Act 1990 & Subsidiary Regulations Health and Safety at Work Act 1974 & Subsidiary Regulations Control of Substances Hazardous to Health Regulations

(COSHH)

May be subject to the Control of Major Accident Hazards

Regulations (COMAH), and amendments.

Other regulations : This product contains cement. Wet cement or mortar may

cause alkali burns if in direct and/or prolonged contact with the skin. Wear protective clothing at all times when working with

cement based products.

15.2 Chemical safety assessment

This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

Full text of H-Statements

H315 Causes skin irritation.
 H318 Causes serious eye damage.
 H335 May cause respiratory irritation.

Full text of other abbreviations

Eye Dam. Serious eye damage

Skin Irrit. Skin irritation

STOT SE Specific target organ toxicity - single exposure

ADR Accord européen relatif au transport international des marchandises

Dangereuses par Route

CAS Chemical Abstracts Service DNEL Derived no-effect level

EC50 Half maximal effective concentration GHS Globally Harmonized System

IATA International Air Transport Association

IMDG International Maritime Code for Dangerous Goods

LD50 Median lethal dosis (the amount of a material, given all at once, which

causes the death of 50% (one half) of a group of test animals)

LC50 Median lethal concentration (concentrations of the chemical in air that

kills 50% of the test animals during the observation period)

MARPOL International Convention for the Prevention of Pollution from Ships,

1973 as modified by the Protocol of 1978

OEL Occupational Exposure Limit

PBT Persistent, bioaccumulative and toxic PNEC Predicted no effect concentration

REACH Regulation (EC) No 1907/2006 of the European Parliament and of the

Council of 18 December 2006 concerning the Registration, Evaluation,

according to Regulation (EC) No. 1907/2006

SikaScreed® Rapid-75

Revision Date 20.07.2017





Version 2.0

Authorisation and Restriction of Chemicals (REACH), establishing a

European Chemicals Agency

SVHC Substances of Very High Concern

vPvB Very persistent and very bioaccumulative

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!