

Skid Inhibiting Grit

Specialist Dried Sand

Product Description	Sika Liquid Plastics Skid Inhibiting Grit is a specialist dried sand
----------------------------	--

Uses	<ul style="list-style-type: none">■ For use with Sika Liquid Plastics Liquid Applied Roof Membranes to provide a skid inhibiting surface■ Used to create walkway areas on roofs
-------------	--

Product Data

Form

Appearance	Natural sand
-------------------	--------------

Packaging	25kg Bags
------------------	-----------

Size	1.0mm – 2.0mm
-------------	---------------

Storage

Storage Conditions / Shelf Life	Store in original packaging in a location away from sources of dampness and extremes of temperature. Keep protected from rain.
--	--

Application Conditions and Limitations

Coverage Rates	Minimum coverage rates: 0.25 kg/m ² Fully broadcast (broadcast to excess) 3.5 kg/m ² - 4.0 kg/m ²
-----------------------	---

Roofing



Installation Methods / Tools

Skid Inhibiting Grit in Decothane Top Coat/Decaflex

In order to achieve a 'skid inhibiting' finish to designated areas, apply an additional coat of the chosen system, in a contrasting colour to the finished waterproofing, using a minimum quantity of 0.25 l/m² and whilst wet, evenly broadcast Skid Inhibiting Grit at a minimum rate of approximately 0.25 kg per square metre (or as required to meet specific requirements). This should be allowed to dry and any non-adhered particles brushed away. Finally, apply a further coat of the chosen system, at a minimum rate of 0.3 litre per square metre and allow to dry before trafficking.

Note: Prior to commencing and where applicable, walkway borders should be masked either side with polythene sheeting to collect excess grit which may then be re-used if still dry and uncontaminated

Value Base

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

Local Restrictions

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

Ecology, Health and Safety Information

A Safety Data Sheet following EC-Regulation 1907/2006, Article 31 is not needed to bring the product to the market, to transport or to use it. The product does not damage the environment when used as specified.

REACH

European Community Regulation on chemicals and their safe use (REACH: EC 1907/2006)

This product is an article within the meaning of Regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. Therefore, there are no registration requirements for substances in articles within the meaning of Article 7.1 of the Regulation.

Based on our current knowledge, this product does not contain SVHC (substances of very high concern) from the candidate list published by the European Chemicals Agency in concentrations above 0.1 % (w/w).

Protective Measures

Local safety regulations must be observed.

Transportation Class

The product is not classified as hazardous good for transport.

Disposal

The material is recyclable. Disposal must be according to local regulations. Please contact your local Sika sales organisation for more information.



Product Data Sheet

Edition 11.2014

Identification no. 02 09 45 11 900 0 000009

Version no. 02

General Information

Specification Assistance NBS is the industry standard specification system, which allows architects, specifiers and engineers to insert clauses into specifications by manufacturer and product, making the process quicker and more efficient. We are members of NBS Plus and therefore detailed up-to-date product information is readily available to create accurate specifications.

Disclaimer

The information, and, in particular, the recommendations relating to the application and end- use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Contact Details

For further information please contact:

Sika Liquid Plastics
Sika House
Miller Street
Preston
PR1 1EA

Enquiry Line: 01772 259781

Fax: +44 (0)1772 255670

e-mail: liquidplastics@uk.sika.com

Registered office: Sika Ltd, Watchmead, Welwyn Garden City, Hertfordshire, AL7 1BQ
Registered in England: 226822

