DECLARATION OF PERFORMANCE

TECHLINE 2000





0836

Flexible sheet for water-proofing

Techline 2000

TCS Geotechnics Technical Civils Solutions Ltd Units 2 & 5 Tetbury Close Martland Park Wigan, WN5 0LA

Factory Reference: 010-TCS

17

0836-CPR-17/F400

Product Description: Flexible sheets for waterproofing, Plastic and rubber damp proof sheets – Definations and charecteristics

System or systems of assessment and verification of constancy of performance of the construction product: System 2+

Notified Body: British Board of Agrement (BBA) NB 0836

EN13967 2012

Essential Charecteristics	Technical	Bottom Tolerance	Top Tolerance	Unit	Test Standard
	Performance				
Length	15	15	16.5	m	EN 1848-2
Width	4	3.9	4.1	m	EN 1848-2
Mass per unit area (weight)	460	405	515	g/m²	EN 1849-2
Tensile MD	>128	-	-	N/50mm ⁻¹	EN 12311-2
Tensile CD	>117	-	-	N/50mm ⁻¹	EN 12311-2
Resistance to tearing MD	>263	-	-	N	EN 12310-1
Resistance to tearing CD	>311	-	-	N	EN 12310-1
Resistance to impact	>40	-	-	mm	EN 12691
Water tightness 2 kPa	Pass	-	-	Pass / Fail	EN 1928:2000

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance (DOP) is issued under the sole responsibility of the manufacturer identied above.

Authorised signatory

Company Stamp

TECHNICAL CIVILS

SOLUTIONS LTD

CO REG:- 6705826

REGISTERED OFFICE ADDRESS

Units 2 & 5 Tetbury Close Martland Industrial Park Wigan Greater Manchester WN5 0LA Adam Brooksbank (Product Manager)

noordank



Issue: 001

Wigan, 08/17





