



## Bonding and Priming Mortar

tuffbond Utility is a bonding and priming mortar used to enhance the adhesion bond between the paving units and bedding mortar and where present, between the bedding mortar and supporting concrete structure.

For ease of use tuffbond Utility has been packaged in pre-measured sachets contained in a reusable, recyclable tub. With individual sachets only the required amount of tuffbond Utility is used and wastage is minimised.

### Method

If tuffbond is being applied to the base ahead of the bedding mortar, make sure all loose debris is swept clear before the primer is mixed. The same applies to the pavers, which should be clean and individually wiped with a damp sponge to remove any dust or particles that could affect the adhesion performance.

To prepare tuffbond, add 1 litre of water into the tub, and empty 1 sachet of tuffbond into the tub. Using a cordless drill with a spiral mixing paddle or twin paddle mixer, mix thoroughly to form a thick, smooth paste.

With a working life of around 40 minutes at 20°C, the material may start to settle in the tub.

This can be avoided by stirring it once or twice after application to each paver, and if necessary, refreshed by adding an occasional splash of extra water. It is important that the primer is always in the form of a smooth paste before it is applied.

Apply a 1 -2 mm layer of primer to the concrete base using a stiff brush, and place the bedding at once, before the primer has had a chance to dry or skin.

### Technical Specs

Colour	Grey
Packaging	12 kg Tub (4x 3 kg Sachets)
Adhesion	~2 N/m <sup>2</sup>
Consumption	~1.5 kg/m <sup>2</sup> per layer ~8 m <sup>2</sup> per tub
Typical water used	1 litre per 3 kg sachet
Length of working time	40 min at 20 °C
Packages per pallet	36
Pallet quantity	460 kg
Shelf life	12 months from manufacture date
Compliance	BS 7533



Add 1 L of water, then 1 sachet and mix.



Clean area and underside of paving units



Brush apply tuffbond to the base\* and to the underside of the paving units

\* Where the base is in situ concrete or reinforced concrete.



**Steintec**<sup>®</sup>  
high performance paving mortars

1 Northwick Rd  
Canvey Island  
Essex  
SS8 0PU  
**+44 203 598 9800**  
www.steintec.co.uk