

COLSEAL



Colseal is a pre-mixed slurry seal for sealing utility reinstatement and patch repairs. It is also ideal for sealing pre-surface dressing patches. It can also be used for covering score marks and for the treatment of driveways and pathways.

Where to use?

- Carriageways
- Footways
- Driveways

Preparation

The surface should be clean, dry and free of any loose chippings/debris (the treatment and removal of any weeds and moss should be carried out prior to laying preparation). Use masking tape to protect any kerbs/ironwork, etc. from being covered (this is to be removed when the surface is completely dry, after the whole application is complete).

Application

Mix thoroughly before use with a drill paddle. Pour onto surface in manageable amounts and using a soft brush with handle or squeegee, spread evenly over the surface to the recommended thickness of approximately 1.5mm-2mm, promptly finishing this area in the same directional brush stroke.

If a thickness greater than 1.5mm-2mm is required we recommend an additional application but it must be ensured that the first application is set fully before reapplying.

The material should be applied on a dry day at temperatures of 10 °C and rising with no possibility of rainfall. Setting times vary with temperature. At the recommended thickness setting times will be, at 25°C approximately 1-3 hours and at 10°C 3-6 hours.

Coverage

1 x 25kg bag will cover approximately 10-14m² @ 1.5mm-2mm thickness, depending on surface texture.

Packaging

Colseal is supplied in 25kg buckets (36 x 25kg per pallet) or cardboard boxes containing 40 x 25kg bags.

Storage

Store in a cool, dry place, protect from frost.

Standards

Supplied in accordance to ISO9001.

Safety

For full safety information, please download the Colseal Safety Data Sheet 152 from our website www.colas.co.uk

OVERBANDING

Colstrips
Gripstrip
Jointrip OB

26
28
29

