

Description

rbs Greenpave Block Sealer SS is a clear, solvent free acrylic resin coating used to seal and protect concrete and block paving, it resists the effects of sunlight, water, oil, petrol and lichen growth.

Please note that this product is designed to stabilise the jointing sand. The resultant finish is a hard wearing water repellent film which has a low sheen and slip resistant finish.

Advantages

- Prevents the appearance of green mould.
- Prevents sand loss from joints and weed growth, lichen, moss & grass.
- Reduces penetration of oil, fuels & reduces staining.
- Hard wearing, durable and long lasting.
- One component system.
- Good UV resistance.

Directions For Use

- All surfaces must be free from grease, dust, loose material, lichen etc.
- The surface to be treated should be cleaned with a fungicidal wash, should there be heavy staining such as oil or grease this should be treated with a heavy duty degreasant.
- A nominal coverage rate of 4-5m²/litre per coat can be achieved.
- It must be stirred before use and may be applied to damp, but not wet, surfaces with a long pile roller or low pressure sprayer, ensuring an even, thorough coverage.
- Care should be taken to avoid ponding.
- Apply sealer to joints carefully to avoid removing sand.
- Drying time between coats is approximately 4 Hours at 20°C.
- Equipment should be cleaned with warm water immediately after use.

Limitations

- Do not apply below 5°C (air or surface temperature).
- rbs Greenpave Block Sealer SS should not be used on surfaces that have been previously treated with other waterproofing solutions such as Silicone or Stearate Based Treatments unless the surface has weathered to such an extent that no water

beading effects are observable.

- rbs Greenpave Block Sealer SS should not be used if rain is expected within 5 hours of application.
- Do not allow to enter watercourses.
- Areas treated with rbs Greenpave Block Sealer SS should be cleaned with warm water and detergent—Never use acid based cleaners or pressure washing systems.

Technical Data

Appearance	White emulsion
Flash Point (PMCC)	>100%
Freezing Point	-2°C
Coverage Rate	4-5m ² /litre per coat (approx)
Drying Time @ 20°C	4 hours at 20°C

Packaging

rbs Greenpave Block Sealer SS is available in 5 & 20 litre containers.

Storage

rbs Greenpave Block Sealer SS should be stored under dry, frost-free conditions away from direct sunlight, under such conditions the shelf life is at least twelve months.

Health & Safety

When working with rbs Greenpave Block Sealer SS suitable protective clothing, eye/face protection and gloves should be worn.

Areas where this product is being applied must be well ventilated. For further health and safety information, please refer to the relevant Safety Data Sheet.

Important Note

Whilst all reasonable care is taken in compiling technical data on the Company's products, all recommendations or suggestions regarding the use of such products are made without guarantee, since the conditions of use are beyond the control of the Company.

It is the responsibility of the customer to satisfy himself that each product is fit for the purpose for which he intends to use it, that the actual conditions of use are suitable, and that in the light of our continual research and development programme the information relating to each product has not been superseded

The information given on this sheet is, to the best of our knowledge, true and accurate. No guarantee of the results implied, or any loss or damage arising out of this material, however, are possible as the conditions of application are beyond our control. This is not withstanding any liability arising from the Consumer Protection Act 1987 and the Health & Safety at Work Act. Health and Safety data is available on this product and should be referred to prior to its use

Resapol Ltd

Unit D4, Moss Industrial Estate , Walter Leigh Way,
Leigh, Lancashire WN7 3PT
T 0800 083 1942 E sales@resapol.com
www.resapol.com

Resapol Foundation

Giving back *with every pack*

For more information on the Resapol Foundation, please visit our website at www.resapol.com.