

rbs Tanking Membrane GR SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier		
Trade name or designation of the mixture	rbs Tanking Membrane GR	
Registration number	-	
Synonyms	None.	
Issue date	09-February-2024	
Version number	01	
Revision date	-	
Supersedes date	-	
1.2. Relevant identified uses of t	he substance or mixture and us	ses advised against
Identified uses	Waterproofing Membrane	
Uses advised against	None known.	
1.3. Details of the supplier of the	e safety data sheet	
Supplier		
Company name	Resapol Ltd	
Address	Unit D4, Moss Industrial Estate	
	Walter Leigh Way,	
	Leigh, Lancashire, WN7 3PT	
Division	UK	
Telephone	General Assistance	+44 (0)1942 609 001
e-mail	sales@resapol.com	+++ (0)10+2 000 001
Contact person	Not available.	
1.4. Emergency telephone	Emergency Phone	+44 (0)1942 609 002
number		
	(Mon-Fri 8:00-5:00	
SECTION 2: Hazards ident	tification	
2.1. Classification of the substa	nce or mixture	

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended

This mixture does not meet the criteria for classification according to Regulation (EC) 1272/2008 as amended.

Hazard summary	Not classified for health hazards. However, occupational exposure to the mixture or substance(s) may cause adverse health effects.
2.2. Label elements	
Label according to Regulation (EC) No. 1272/2008 as amended
Hazard pictograms	None.
Signal word	None.
Hazard statements	The mixture does not meet the criteria for classification.
Precautionary statements	
Prevention	Observe good industrial hygiene practices.
Response	Wash hands after handling.
Storage	Store away from incompatible materials.

Disposal	Dispose of waste and residues in accordance with local authority requirements.
Supplemental label information	100 % of the mixture consists of component(s) of unknown acute oral toxicity. 100 % of the mixture consists of component(s) of unknown acute dermal toxicity. 100 % of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 100 % of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.
2.3. Other hazards	Not a PBT or vPvB substance or mixture.
SECTION 2. Composition/	information on ingradiante

SECTION 3: Composition/information on ingredients

3.2. Mixtures

The components are not hazardous or are below required disclosure limits.

List of abbreviations and symbols that may be used above

- #: This substance has been assigned Union workplace exposure limit(s).
- M: M-factor

PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

```
Composition comments
```

The full text for all H-statements is displayed in section 16.

SECTION 4: First aid measures

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

4.1. Description of first aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Wash off with soap and water. Get medical attention if irritation develops and persists.
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
4.2. Most important symptoms and effects, both acute and delayed	Exposure may cause temporary irritation, redness, or discomfort.
4.3. Indication of any immediate medical attention	Treat symptomatically.

and special treatment needed

SECTION 5: Firefighting measures

General fire hazards	No unusual fire or explosion hazards noted.
5.1. Extinguishing media	
Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
5.2. Special hazards arising from the substance or mixture	During fire, gases hazardous to health may be formed.
5.3. Advice for firefighters	
Special protective equipment for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Special fire fighting procedures	Use water spray to cool unopened containers.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	Keep unnecessary personnel away. For personal protection, see section 8 of the SDS.
For emergency responders	Keep unnecessary personnel away. Use personal protection recommended in Section 8 of the SDS.
6.2. Environmental precautions	Avoid discharge into drains, water courses or onto the ground.
6.3. Methods and material for containment and cleaning up	Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.
6.4. Reference to other sections	For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

SECTION 7: Handling and storage

7.1. Precautions for safe handling	Avoid prolonged exposure. Observe good industrial hygiene practices.
7.2. Conditions for safe storage, including any incompatibilities	Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).
7.3. Specific end use(s)	Not available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

Belgium. Exposure Limit Values.				
Components	Туре	Value	Form	
DISTILLATES (PETROLEUM) SOLVENT-DEWAXED HEAVY PARAFFINIC (CAS 64742-65-0)	STEL	10 mg/m3	Mist.	
	TWA	5 mg/m3	Mist.	
Polyethylene (CAS 9002-88-4)	TWA	3 mg/m3	Respirable fraction.	
		10 mg/m3	Inhalable fraction.	

Bulgaria. OELs. Regulation No 13 on protection of workers against risks of exposure to chemical agents at work

Components	Туре	Value	Form
DISTILLATES (PETROLEUM) SOLVENT-DEWAXED HEAVY PARAFFINIC (CAS 64742-65-0)	TWA	5 mg/m3	
Polyethylene (CAS 9002-88-4)	TWA	10 mg/m3	Dust.
Czech Republic. OELs. Governm	ent Decree 361		
Components	Туре	Value	Form
Polyethylene (CAS 9002-88-4)	TWA	5 mg/m3	Dust.
Denmark. Exposure Limit Values			
Components	Туре	Value	Form
DISTILLATES	TLV	1 mg/m3	
DISTILLATES (PETROLEUM) SOLVENT-DEWAXED HEAVY PARAFFINIC (CAS 64742-65-0) Estonia. OELs. Occupational Exp 2001)			on No. 293 of 18 September
(PETROLEUM) SOLVENT-DEWAXED HEAVY PARAFFINIC (CAS 64742-65-0) Estonia. OELs. Occupational Exp 2001)			ion No. 293 of 18 September Form
(PETROLEUM) SOLVENT-DEWAXED HEAVY PARAFFINIC (CAS 64742-65-0) Estonia. OELs. Occupational Exp 2001) Components Polyethylene (CAS	oosure Limits of Hazardous Su	bstances. (Annex of Regulati	-
(PETROLEUM) SOLVENT-DEWAXED HEAVY PARAFFINIC (CAS 64742-65-0) Estonia. OELs. Occupational Exp 2001) Components Polyethylene (CAS	oosure Limits of Hazardous Su Type	bstances. (Annex of Regulati Value	Form
(PETROLEUM) SOLVENT-DEWAXED HEAVY PARAFFINIC (CAS 64742-65-0) Estonia. OELs. Occupational Exp	oosure Limits of Hazardous Su Type	bstances. (Annex of Regulati Value 5 mg/m3	Form Respirable dust.
(PETROLEUM) SOLVENT-DEWAXED HEAVY PARAFFINIC (CAS 64742-65-0) Estonia. OELs. Occupational Exp 2001) Components Polyethylene (CAS 9002-88-4)	oosure Limits of Hazardous Su Type TWA	bstances. (Annex of Regulati Value 5 mg/m3 10 mg/m3 1 mg/m3	Form Respirable dust. Total dust. Dust.
(PETROLEUM) SOLVENT-DEWAXED HEAVY PARAFFINIC (CAS 64742-65-0) Estonia. OELs. Occupational Exp 2001) Components Polyethylene (CAS 9002-88-4) France. Threshold Limit Values (1	oosure Limits of Hazardous Su Type TWA	bstances. (Annex of Regulati Value 5 mg/m3 10 mg/m3 1 mg/m3	Form Respirable dust. Total dust. Dust.
(PETROLEUM) SOLVENT-DEWAXED HEAVY PARAFFINIC (CAS 64742-65-0) Estonia. OELs. Occupational Exp 2001) Components Polyethylene (CAS 9002-88-4) France. Threshold Limit Values (Components Polyethylene (CAS	oosure Limits of Hazardous Su Type TWA VLEP) for Occupational Expos	bstances. (Annex of Regulati Value 5 mg/m3 10 mg/m3 1 mg/m3 ure to Chemicals in France, I	Form Respirable dust. Total dust. Dust. NRS ED 984
(PETROLEUM) SOLVENT-DEWAXED HEAVY PARAFFINIC (CAS 64742-65-0) Estonia. OELs. Occupational Exp 2001) Components Polyethylene (CAS 9002-88-4) France. Threshold Limit Values (Components Polyethylene (CAS 9002-88-4)	oosure Limits of Hazardous Su Type TWA VLEP) for Occupational Expos Type	bstances. (Annex of Regulati Value 5 mg/m3 10 mg/m3 1 mg/m3 ure to Chemicals in France, I Value	Form Respirable dust. Total dust. Dust. NRS ED 984 Form
(PETROLEUM) SOLVENT-DEWAXED HEAVY PARAFFINIC (CAS 64742-65-0) Estonia. OELs. Occupational Exp 2001) Components Polyethylene (CAS 9002-88-4) France. Threshold Limit Values (Components Polyethylene (CAS 9002-88-4)	Dosure Limits of Hazardous Su Type TWA VLEP) for Occupational Expos Type VME	bstances. (Annex of Regulati Value 5 mg/m3 10 mg/m3 1 mg/m3 ure to Chemicals in France, I Value	Form Respirable dust. Total dust. Dust. NRS ED 984 Form

Components	Туре	Value	Form
ISTILLATES PETROLEUM) OLVENT-DEWAXED EAVY PARAFFINIC (CAS 4742-65-0)	TWA	5 mg/m3	Respirable fraction.
olyethylene (CAS 002-88-4)	TWA	4 mg/m3	Inhalable dust.
		0,3 mg/m3	Respirable dust.
ermany. TRGS 900, Limit Values i omponents	n the Ambient Air at the Workplac Type	ce Value	Form
olyethylene (CAS 002-88-4)	AGW	10 mg/m3	Inhalable fraction.
		1,25 mg/m3	Respirable fraction.
reece. OELs (Decree No. 90/1999,	-		_
components	Туре	Value	Form
VISTILLATES PETROLEUM) OLVENT-DEWAXED IEAVY PARAFFINIC (CAS 4742-65-0)	TWA	5 mg/m3	Mist.
lungary. OELs. Joint Decree on Ch components	emical Safety of Workplaces Type	Value	Form
DISTILLATES PETROLEUM) GOLVENT-DEWAXED IEAVY PARAFFINIC (CAS 4742-65-0)	Ceiling	5 mg/m3	Mist.
olyethylene (CAS 002-88-4)	TWA	6 mg/m3	Respirable dust.
		10 mg/m3	Total inhalable dust.
eland. OELs. Regulation 154/1999 omponents	on occupational exposure limits Type	Value	Form
DISTILLATES PETROLEUM) OLVENT-DEWAXED IEAVY PARAFFINIC (CAS 4742-65-0)	TWA	1 mg/m3	Mist.
olyethylene (CAS 002-88-4)	TWA	5 mg/m3	Respirable dust.
		10 mg/m3	Total dust.
eland. Occupational Exposure Lin omponents	iits Type	Value	Form
DISTILLATES PETROLEUM) OLVENT-DEWAXED IEAVY PARAFFINIC (CAS 4742-65-0)	TWA	5 mg/m3	Inhalable fraction.
olyethylene (CAS 002-88-4)	TWA	4 mg/m3	Respirable dust.
		10 mg/m3	Total inhalable dust.
aly. Occupational Exposure Limits omponents	Туре	Value	Form
ISTILLATES	TWA	5 mg/m3	Inhalable fraction.
PETROLEUM) SOLVENT-DEWAXED IEAVY PARAFFINIC (CAS 4742-65-0)		-	

Latvia. OELs. Occupational exposur Components	e limit values of chemical Type	substances in work environment Value	Form
Polyethylene (CAS 9002-88-4)	TWA	5 mg/m3	Dust.
ithuania. OELs. Limit Values for C C	hemical Substances, Gene Type	ral Requirements Value	Form
DISTILLATES PETROLEUM) SOLVENT-DEWAXED HEAVY PARAFFINIC (CAS 34742-65-0)	STEL	3 mg/m3	Fume and mist.
	TWA	1 mg/m3	Fume and mist.
Polyethylene (CAS 002-88-4)	TWA	10 mg/m3	
Netherlands. OELs (binding) Components	Туре	Value	Form
DISTILLATES PETROLEUM) SOLVENT-DEWAXED HEAVY PARAFFINIC (CAS 64742-65-0)	TWA	5 mg/m3	Mist.
lorway. Administrative Norms for C Components	ontaminants in the Workp Type	ace Value	Form
DISTILLATES PETROLEUM) SOLVENT-DEWAXED HEAVY PARAFFINIC (CAS 64742-65-0)	TLV	1 mg/m3	Mist.
Polyethylene (CAS 002-88-4)	TLV	5 mg/m3	Respirable dust.
		10 mg/m3	Total dust.
Ordinance of the Minister of Labour			sible concentrations and
ntensities of harmful health factors Components	in the work environment, . Type	Journal of Laws 2014, item 817 Value	Form
DISTILLATES PETROLEUM) SOLVENT-DEWAXED IEAVY PARAFFINIC (CAS 4742-65-0)	TWA	5 mg/m3	Inhalable fraction.
Portugal. VLEs. Norm on occupation Components	nal exposure to chemical a Type	gents (NP 1796) Value	Form
DISTILLATES PETROLEUM) SOLVENT-DEWAXED HEAVY PARAFFINIC (CAS 64742-65-0)	TWA	5 mg/m3	Inhalable fraction.
Romania. OELs. Protection of worke Components	ers from exposure to chem Type	ical agents at the workplace Value	
DISTILLATES PETROLEUM) SOLVENT-DEWAXED HEAVY PARAFFINIC (CAS S4742-65-0)	STEL	10 mg/m3	
/	TWA	5 mg/m3	
Slovakia. OELs. Regulation No. 300/ Components	2007 concerning protectio Type	n of health in work with chemica Value	l agents Form
DISTILLATES (PETROLEUM) SOLVENT-DEWAXED HEAVY PARAFFINIC (CAS 64742-65-0)	STEL	3 mg/m3	Fume and mist.

ado2-38.4) 2 mg/m3 Respirable acrosol fraction 2 mg/m3 Respirable acrosol fraction 10 mg/m3 Dust. 10 mg/m3 Dust. 10 mg/m3 Total Spain. Occupational Exposure Limits Components Type Value Form DISTILLATES STEL 10 mg/m3 Mist. SolVENT-DEWAXED HEAVY PARAFINIC (CAS S4742-65-0) TWA 5 mg/m3 Mist. Polyethylene (CAS TWA 3 mg/m3 Respirable fraction. SolVENT-DEWAXED DISTILLATES STEL 3 mg/m3 Mist. SolVENT-DEWAXED DISTILLATES Type Value Form DISTILLATES STEL 3 mg/m3 Mist. SolVENT-DEWAXED HEAVY PARAFINIC (CAS S4742-65-0) TWA 5 mg/m3 Mist. SolVENT-DEWAXED HEAVY PARAFINIC (CAS S4742-65-0) TWA 5 mg/m3 Mist. SolVENT-DEWAXED HEAVY PARAFINIC (CAS S4742-65-0) TWA 5 mg/m3 Mist. SolVENT-DEWAXED HEAVY PARAFINIC (CAS S4742-65-0) TWA 1 mg/m3 Mist. SolVENT-DEWAXED HEAVY PARAFINIC (CAS S4742-65-0) TWA 1 mg/m3 Mist. SolVENT-DEWAXED HEAVY PARAFINIC (CAS S4742-65-0) TWA 1 mg/m3 Mist. SolVENT-DEWAXED HEAVY PARAFINIC (CAS S4742-65-0) TWA 3 mg/m3 Inhalable dust. SolVENT-DEWAXED HEAVY PARAFINIC (CAS S4742-65-0) TWA 3 mg/m3 Inhalable dust. S4742-65-0) TWA 3 mg/m3 Inhalable dust. S4742-65-0) TWA 5 mg/m3 Inhalable dust. S4742-65-0) TWA 3 mg/m3 Inhalable dust. S4742-65-0) TWA 5 mg/m3 Inhalable dust. S4742-65-0) TWA 3 mg/m3 Inhalable dust. S4742-65-0) TWA 4 mg/m3 Respirable dust. S4742-65-01 10 mg/m3 Inhalable dust. S4742-65-01 10	Components	n No. 300/2007 concerning protectior Type	Value	Form
Polyethylene (CAS polyethylene			15 ppm	Fume and mist.
Polyethylene (CAS B002-88-4) Polyethylene (CAS Polyethylene (CAS Polyethylene (CAS Polyethylene (CAS Polyethylene (CAS Polyethylene (CAS Polyethylene (CAS SOLVENT-DEWAXED DISTLLATES POLYETHOL (CAS STEL POLYETHOL (CAS STEL POLY		TWA	1 mg/m3	Fume and mist.
2002-285.4) ************************************			5 ppm	Fume and mist.
2 mg/m3 Respirable aerosol fraction 2 mg/m3 Respirable aerosol fraction 10 mg/m3 Dust. 10 mg/m3 Aerosol 10 mg/m3 Aerosol 10 mg/m3 Total Spain. Occupational Exposure Limits Type Components Type DISTILLATES STEL DISTILLATES STEL Solv.ENT-DEWAXED TWA HAVY PARAFINIC (CAS SY472-26-01 TWA Sweden. OELs. Work Environment Authority (AV), Occupational Exposure Limit Yalues (AFS 2015: 7) Components Type Value Form DISTILLATES STEL Sweden. OELs. Work Environment Authority (AV), Occupational Exposure Limit Yalues (AFS 2015: 7) Components Type Value Form DISTILLATES STEL Sweden. OELs. Work Environment Authority (AV), Occupational Exposure Limit Yalues (AFS 2015: 7) Components Type Value Form DISTILLATES TWA Sweden. OELs. Work Environment Authority (AV), Occupational Exposure Limit Yalues (AFS 2015: 7) Components Type Value Form DISTILLATES TWA Sweden. OELs. Work Environment Authority (AV), Occupational Exp	Polyethylene (CAS 9002-88-4)	TWA	2 mg/m3	Respirable fraction.
2 mg/m3 Respirable aerosol fraction 10 mg/m3 Netrosol 10 mg/m3 Aerosol 10 mg/m3 Aerosol 10 mg/m3 Total Spain. Occupational Exposure Limits Type Components Type DisTLLATES STEL DisTLLATES STEL DisTLLATES STEL DistLATES TWA Solvent-DetwaxeD Hata HEAVY PARAFINIC (CAS Strike TWA 3 mg/m3 Respirable fraction. Strike TWA 3 mg/m3 Respirable fraction. Strike TWA 3 mg/m3 Inhalable fraction. Strike TWA 3 mg/m3 Inhalable fraction. Strike Type Value Form Distrike TwA Strike 3 mg/m3 Respirab			2 mg/m3	Respirable fraction.
Spain. Occupational Exposure Limits Components Type Value Form Spain. Occupational Exposure Limits Components Type Value Form DISTILLATES (PETROLEUM) SOLVENT-DEWAXED HEAVY PARAFINIC (CAS 34742-65-0) STEL 10 mg/m3 Mist. Polyethylene (CAS 002-86-4) TWA 5 mg/m3 Mist. Sweden. OELs. Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2015-7) Components Type Value Form DISTILLATES (PETROLEUM) SOLVENT-DEWAXED HEAVY PARAFINIC (CAS 3002-86-4) STEL 3 mg/m3 Mist. Polyethylene (CAS 3002-86-4) TWA 1 mg/m3 Mist. Sweden. OELs. Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2015-7) Form DISTILLATES Solveth-DEWAXED HEAVY PARAFINIC (CAS 34742-65-0) TWA 1 mg/m3 Mist. Polyethylene (CAS 3002-86-4) TWA 1 mg/m3 Mist. Switzerland. SUVA Grenzwerte am Arbeitsplatz Components TWA 1 mg/m3 Inhalable fraction. SUSTILLATES 3002-86-4) TWA 3 mg/m3 Respirable dust. Solveth-DEWAXED HEAVY PARAFINIC (CAS 34742-65-0) TWA 3 mg/m3 Respirable dust. DISTILLATES 3002-86-4) TWA 3 mg/m3 Inhalable fraction. Solveth-DEWAXED HEAVY PARAFINIC (CAS 34742-65-0) TWA 3 mg/m3			2 mg/m3	
10 mg/m3 Aerosol 10 mg/m3 Total Spain. Occupational Exposure Limits Type Value Form Components Type Value Form DISTILLATES STEL 10 mg/m3 Mist. Perrone Limits STEL 10 mg/m3 Mist. SOLVENT-DEWAXED TWA 5 mg/m3 Mist. Polyethylene (CAS TWA 3 mg/m3 Respirable fraction. 2002-88-4) 10 mg/m3 Inhalable fraction. 2002-88-4) 10 mg/m3 Mist. 201STILLATES STEL 3 mg/m3 Mist. Polyethylene (CAS STEL 3 mg/m3 Mist. 2002-88-4) Type Value Form 201STILLATES STEL 3 mg/m3 Mist. Polyethylene (CAS TWA 1 mg/m3 Mist. 2012-86-4) TWA 1 mg/m3 Inhalable dust. 202-86-4) Z.5 mg/m3 Inhalable dust. 202-86-4) TWA 1 mg/m3 Respirable dust. SWitzerland. SUVA Grenzwerte am Arbeittsplatz Yang Form Components Type Value Form DISTILLATES TWA 3 mg/m3 Inhalable dust.			2 mg/m3	
10 mg/m3 10 mg/m3 Total Spain. Occupational Exposure Limits Components Type Value Form DISTILLATES (PETROLEUM) SOLVENT-DEWAXED HEAVY PARAFFINIC (CAS 34742-85-0) STEL 10 mg/m3 Mist. Polyethylene (CAS 3002-88-4) TWA 5 mg/m3 Mist. Polyethylene (CAS 3002-88-4) TWA 5 mg/m3 Inhalable fraction. Structure of the exposure Limit Values (AFS 2015:7) Type Total Total Soutewin - Develoaction Type Value Form DISTILLATES (PETROLEUM) SOLVENT-DEVMAXED STEL 3 mg/m3 Mist. DISTILLATES (PETROLEUM) SOLVENT-DEVMAXED TWA 1 mg/m3 Mist. DISTILLATES (PETROLEUM) SOLVENT-DEVMAXED TWA 1 mg/m3 Mist. Polyethylene (CAS 3002-88-4) TWA 1 mg/m3 Mist. Soutewin - Devex TWA 5 mg/m3 Inhalable dust. Soutewin - Devex TWA 5 mg/m3 Inhalable dust. Soutewin - Devex TWA 3 mg/m3 Respirable dust. Soutewin - Devex Type Value Form DISTILLATES (PETROLEUM) TWA 3 mg/m3 Respirable dust. Soutewin - Devex Type Value Form DISTILLATES (PETROLEUM) TWA <			10 mg/m3	Dust.
Spain. Occupational Exposure Limits Components Type Value Form DISTILLATES (PETROLEUM) SOLVENT-DEVIAXED HEAVY PARAFFINIC (CAS 34742-65-0) STEL 10 mg/m3 Mist. Polyethylene (CAS 3002-86-4) TWA 5 mg/m3 Mist. Polyethylene (CAS 3002-86-4) TWA 5 mg/m3 Mist. Sweden. OELs. Work Environment Author/ty (AV), Occupational Exposure Limit Values (AFS 2015:7) Components TWA 3 mg/m3 DISTILLATES (PETROLEUM) SOLVENT-DEVIAXED HEAVY PARAFFINIC (CAS 34742-65-0) STEL 3 mg/m3 Mist. Polyethylene (CAS 3002-86-4) TWA 1 mg/m3 Mist. SOLVENT-DEVWAXED HEAVY PARAFFINIC (CAS 34742-65-0) TWA 5 mg/m3 Inhalable dust. Polyethylene (CAS 3002-86-4) TWA 5 mg/m3 Inhalable dust. SOLVENT-DEVWAXED HEAVY PARAFFINIC (CAS 34742-65-0) TWA 5 mg/m3 Inhalable fraction. SOLVENT-DEVWAXED HEAVY PARAFFINIC (CAS 34742-65-0) TWA 3 mg/m3 Respirable dust. SOLVENT-DEVWAXED HEAVY PARAFFINIC (CAS 34742-65-0) TWA 3 mg/m3 Respirable dust. DISTILLATES SOLVENT-DEVWAXED HEAVY PARAFFINIC (CAS 34742-65-0) TWA 3 mg/m3 Respirable dust. DISTILLATES SOLVENT-DEVWAXED HEAVY PARAFFINIC (CAS 34742-65-0) TWA 3 mg/m3 Respirable dust. DISTILLATES SOLVENT-DEVWAXED H			10 mg/m3	Aerosol
Spain. Occupational Exposure Limits Components Type Value Form DISTILLATES (PETROLEUM) SOLVENT-DEWAXED HEAVY PARAFFINIC (CAS 34742-65-0) STEL 10 mg/m3 Mist. Polyethylene (CAS 3002-88-4) TWA 5 mg/m3 Mist. Polyethylene (CAS 3002-88-4) TWA 3 mg/m3 Respirable fraction. Sweden. OELs. Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2015:7) Type Value Form DISTILLATES (PETROLEUM) STEL 3 mg/m3 Mist. Stell 3 mg/m3 Inhalable fraction. SolvENT-DEWAXED HEAVY PARAFFINIC (CAS 34742-65-0) TWA 1 mg/m3 Mist. Stell Stell <td></td> <td></td> <td>10 mg/m3</td> <td></td>			10 mg/m3	
Components Type Value Form DISTILLATES STEL 10 mg/m3 Mist. PETROLEUM) SOLVENT-DEWAXED HEAVY PARAFFINIC (CAS s4742-65-0) TWA 5 mg/m3 Mist. Polyethylene (CAS TWA 3 mg/m3 Respirable fraction. 2002-88-4) TWA 3 mg/m3 Respirable fraction. Sweden. OELs. Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2015:7) Components Type Value Form DISTILLATES (PETROLEUM) SOLVENT-DEWAXED HEAVY PARAFFINIC (CAS s4742-65-0) STEL 3 mg/m3 Mist. Polyethylene (CAS TWA 1 mg/m3 Mist. SOUVENT-DEWAXED HEAVY PARAFFINIC (CAS s4742-65-0) TWA 1 mg/m3 Mist. Polyethylene (CAS TWA 5 mg/m3 Inhalable dust. 2002-88-4) Z,5 mg/m3 Respirable dust. Switzerland. SUVA Grenzwerte am Arbeitsplatz Components Type Value Form DISTILLATES (PETROLEUM) SOLVENT-DEWAXED HEAVY PARAFFINIC (CAS s4742-65-0) TWA 3 mg/m3 Respirable dust. Solvertion -DeWAXED HEAVY PARAFFINIC (CAS s4742-65-0) TWA 3 mg/m			10 mg/m3	Total
DISTILLATES STEL 10 mg/m3 Mist. PETROLEUM) SOLVENT-DEWAXED HEAVY PARAFFINIC (CAS 54742-65-0) TWA 5 mg/m3 Respirable fraction. 5002-88-4) 10 mg/m3 Inhalable fraction. 5002-88-4) 10 mg/m3 Mist. 5002-88-4) DISTILLATES STEL 3 mg/m3 Mist. Form DISTILLATES STEL 3 mg/m3 Mist. Polyethylene (CAS 54742-65-0) TWA 1 mg/m3 Mist. Polyethylene (CAS 54742-65-0) TWA 5 mg/m3 Inhalable dust. 2,5 mg/m3 Respirable dust. 5002-88-4) DISTILLATES Type Value Form DISTILLATES STEL 3 mg/m3 Mist. Polyethylene (CAS 54742-65-0) TWA 1 mg/m3 Mist. Polyethylene (CAS 54742-65-0) TWA 5 mg/m3 Inhalable fraction. 5002-88-4) DISTILLATES Type Value Form DISTILLATES TWA 5 mg/m3 Inhalable fraction. SOLVENT-DEWAXED HEAVY PARAFFINIC (CAS 54742-65-0) Polyethylene (CAS TWA 3 mg/m3 Respirable dust. UK EH40 Workplace Exposure Limits (WELs) Components Type Value Form Polyethylene (CAS TWA 4 mg/m3 Respirable dust. UK EH40 Workplace Exposure Limits (WELs) Components Type Value Form Polyethylene (CAS TWA 4 mg/m3 Respirable dust. 2002-88-4) 10 mg/m3 Inhalable dust. 2002-88-4)				_
IPETROLEUMI SOLVENT-DEWAXED HEAVY PARAFFINIC (CAS 94742-65-0) TWA 5 mg/m3 Mist. Polyethylene (CAS 3002-88-4) TWA 3 mg/m3 Respirable fraction. 3002-88-4) 10 mg/m3 Inhalable fraction. Sweden. OELs. Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2015:7) Form Components Type Value Form DISTILLATES (PETROLEUM) SOLVENT-DEWAXED HEAVY PARAFFINIC (CAS 54742-65-0) STEL 3 mg/m3 Mist. Polyethylene (CAS 3002-88-4) TWA 1 mg/m3 Mist. Polyethylene (CAS 3002-88-4) TWA 5 mg/m3 Inhalable dust. Switzerland. SUVA Grenzwerte am Arbeitsplatz Components Type Value Form DISTILLATES SUTEL-TOEWAXED HEAVY PARAFFINIC (CAS 54742-65-0) TWA 5 mg/m3 Inhalable fraction. SWitzerland. SUVA Grenzwerte am Arbeitsplatz Components Type Value Form DISTILLATES SUZ-86-0) TWA 5 mg/m3 Inhalable dust. SOU-ENT-DEWAXED HEAVY PARAFFINIC (CAS 54742-65-0) TWA 5 mg/m3 Inhalable dust. SOU2-88-4) 10 mg/m3 Inhalable dust. 10 mg/m3 Inhalable dust. SOU2-88	-	Туре	Value	Form
Polyethylene (CAS 9002-88-4) TWA 3 mg/m3 Respirable fraction. Sweden. OELs. Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2015:7) Inhalable fraction. Sweden. OELs. Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2015:7) Polyethylenes (AFS 2015:7) DISTILLATES (PETROLEUM) SOUVENT-DEWAXED HEAVY PARAFFINIC (CAS 84742-65-0) STEL 3 mg/m3 Mist. Polyethylene (CAS 9002-88-4) TWA 1 mg/m3 Mist. Switzerland. SUVA Grenzwerte am Arbeitsplatz Components Type Value Form DISTILLATES 84742-65-0) TWA 5 mg/m3 Inhalable fraction. Switzerland. SUVA Grenzwerte am Arbeitsplatz Components Type Value Form DISTILLATES 8002-88-4) TWA 5 mg/m3 Inhalable fraction. SUVENT-DEWAXED HEAVY PARAFFINIC (CAS 84742-65-0) TWA 3 mg/m3 Respirable dust. DISTILLATES 8002-88-4) TWA 3 mg/m3 Inhalable fraction. UK. EH40 Workplace Exposure Limits (WELs) Components TWA 3 mg/m3 Respirable dust. 10 mg/m3 Inhalable dust. 10 mg/m3 Inhalable dust. 2002-88-4) TWA 4 mg/m3 Respirable dust. 2002-88-4) TWA 4 mg/m3 Inhalable dust. 2002-88-4) TWA <	(PETROLEUM) SOLVENT-DEWAXED		10 mg/m3	Mist.
3002-88-4) 10 mg/m3 Inhalable fraction. Sweden. OELs. Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2015:7) Form Components Type Value Form DISTILLATES STEL 3 mg/m3 Mist. PEROLEUM) SOLVENT-DEWAXED HEAVY PARAFFINIC (CAS 84742-65-0) TWA 1 mg/m3 Inhalable dust. 2002-88-4) TWA 5 mg/m3 Inhalable dust. 3002-88-4) 2,5 mg/m3 Respirable dust. Switzerland. SUVA Grenzwerte am Arbeitsplatz Components Type Value Form DISTILLATES TWA 5 mg/m3 Inhalable fraction. Sitzerland. SUVA Grenzwerte am Arbeitsplatz Form Components Type Value Form Inhalable fraction. DISTILLATES TWA 5 mg/m3 Inhalable fraction. Soluzentand. SUVA Grenzwerte am Arbeitsplatz Inhalable fraction. Stratescoluphical fraction. Soluzentand. TWA 5 mg/m3 Inhalable fraction. Soluzentand. TWA 3 mg/m3 Respirable dust. Soluzentand. TWA 3 mg/m3 Respirable dust.		TWA	5 mg/m3	Mist.
Sweden. OELs. Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2015:7) Value Form DISTILLATES (PETROLEUM) SOLVENT-DEWAXED HEAVY PARAFFINIC (CAS 34742-65-0) STEL 3 mg/m3 Mist. Polyethylene (CAS 3002-88-4) TWA 1 mg/m3 Mist. Polyethylene (CAS 3002-88-4) TWA 5 mg/m3 Inhalable dust. Switzerland. SUVA Grenzwerte am Arbeitsplatz Components Type Value Form DISTILLATES 34742-65-0) TWA 5 mg/m3 Inhalable dust. Switzerland. SUVA Grenzwerte am Arbeitsplatz Components Type Value Form DISTILLATES PETROLEUM) SOLVENT-DEWAXED HEAVY PARAFFINIC (CAS 34742-65-0) TWA 5 mg/m3 Inhalable fraction. POlyethylene (CAS 3002-88-4) TWA 3 mg/m3 Respirable dust. 3002-88-4) TWA 4 mg/m3 Inhalable dust. VL. EH40 Workplace Exposure Limits (WELS) Components TWA 4 mg/m3 Respirable dust. 2002-88-4) TWA 4 mg/m3 Respirable dust. 2002-88-4) TWA 4 mg/m3 Respirable dust. 2002-88-4) No biological exposure limits noted		TWA	3 mg/m3	Respirable fraction.
Components Type Value Form DISTILLATES (PETROLEUM) SOUVENT-DEWAXED HEAVY PARAFFINIC (CAS 34742-65-0) STEL 3 mg/m3 Mist. Polyethylene (CAS 3002-88-4) TWA 1 mg/m3 Mist. Polyethylene (CAS 3002-88-4) TWA 5 mg/m3 Inhalable dust. Switzerland. SUVA Grenzwerte am Arbeitsplatz Components Type Value Form DISTILLATES (PETROLEUM) SOUVENT-DEWAXED HEAVY PARAFFINIC (CAS 34742-65-0) TWA 5 mg/m3 Inhalable fraction. DISTILATES (PETROLEUM) SOUVENT-DEWAXED HEAVY PARAFFINIC (CAS 34742-65-0) TWA 3 mg/m3 Respirable dust. DISTILLATES (PETROLEUM) SOUVENT-DEWAXED HEAVY PARAFFINIC (CAS 34742-65-0) TWA 3 mg/m3 Respirable dust. Polyethylene (CAS 3002-88-4) TWA 3 mg/m3 Respirable dust. Q002-88-4) TWA 4 mg/m3 Respirable dust. Polyethylene (CAS 3002-88-4) TWA 4 mg/m3 Respirable dust. Polyethylene (CAS 3002-88-4) No biological exposure limits noted for the ingredient(s). Inhalable dust. Polyethylene (CAS 3002-88-4) No biological exposure limits noted for the ingredient(s). Inhalable dust. Polyethylene (CAS 3002-88-4) No			10 mg/m3	Inhalable fraction.
Initial and the second seco		• • • •		
(PETROLEUM) SOLVENT-DEWAXED HEAVY PARAFFINIC (CAS 84742-65-0) TWA 1 mg/m3 Mist. Polyethylene (CAS 9002-88-4) TWA 5 mg/m3 Inhalable dust. Switzerland. SUVA Grenzwerte am Arbeitsplatz Components Z,5 mg/m3 Respirable dust. Switzerland. SUVA Grenzwerte am Arbeitsplatz Components Type Value Form DISTILLATES (PETROLEUM) SOLVENT-DEWAXED HEAVY PARAFFINIC (CAS 84742-65-0) TWA 5 mg/m3 Inhalable fraction. Polyethylene (CAS 3002-88-4) TWA 3 mg/m3 Respirable dust. UK. EH40 Workplace Exposure Limits (WELs) Components Type Value Form Polyethylene (CAS 3002-88-4) TWA 4 mg/m3 Respirable dust. Polyethylene (CAS 3002-88-4) TWA 4 mg/m3 Inhalable dust. Polyethylene (CAS 3002-88-4) No biological exposure limits noted for the ingredient(s). Inhalable dust. Souce-88-4) No biological exposure limits noted for the ingredient(s). Form	Components	Туре	Value	Form
Polyethylene (CAS 2002-88-4) TWA 5 mg/m3 Inhalable dust. 2,5 mg/m3 Respirable dust. Switzerland. SUVA Grenzwerte am Arbeitsplatz Components Type Value Form DISTILLATES (PETROLEUM) SOLVENT-DEWAXED HEAVY PARAFFINIC (CAS 34742-65-0) TWA 5 mg/m3 Inhalable fraction. Polyethylene (CAS 3002-88-4) TWA 3 mg/m3 Respirable dust. Polyethylene (CAS 3002-88-4) TWA 3 mg/m3 Respirable dust. VUK. EH40 Workplace Exposure Limits (WELs) Components TWA 3 mg/m3 Respirable dust. Polyethylene (CAS 3002-88-4) TWA 4 mg/m3 Respirable dust. Polyethylene (CAS 3002-88-4) TWA 4 mg/m3 Inhalable dust. Polyethylene (CAS 3002-88-4) TWA 4 mg/m3 Inhalable dust. Polyethylene (CAS 3002-88-4) TWA 4 mg/m3 Inhalable dust. Polyethylene (CAS 3002-88-4) No biological exposure limits noted for the ingredient(s). Inhalable dust.	(PETROLEUM) SOLVENT-DEWAXED HEAVY PARAFFINIC (CAS		-	
2,5 mg/m3 Respirable dust. Switzerland. SUVA Grenzwerte am Arbeitsplatz Components Type Value Form DISTILLATES TWA 5 mg/m3 Inhalable fraction. PIETROLEUM) SOLVENT-DEWAXED HEAVY PARAFFINIC (CAS 34742-65-0) Polyethylene (CAS TWA 3 mg/m3 Respirable dust. 10 mg/m3 Inhalable dust. UK. EH40 Workplace Exposure Limits (WELs) Components Type Value Form Polyethylene (CAS TWA 4 mg/m3 Respirable dust. 2002-88-4) 10 mg/m3 Inhalable dust. UK. EH40 Workplace Exposure Limits (WELs) Components Type Value Form Polyethylene (CAS TWA 4 mg/m3 Respirable dust. 2002-88-4) No biological exposure limits noted for the ingredient(s). Follow standard monitoring procedures.		TWA	1 mg/m3	Mist.
Switzerland. SUVA Grenzwerte am Arbeitsplatz Components Type Value Form DISTILLATES (PETROLEUM) SOLVENT-DEWAXED HEAVY PARAFFINIC (CAS 34742-65-0) TWA 5 mg/m3 Inhalable fraction. Polyethylene (CAS 3002-88-4) TWA 3 mg/m3 Respirable dust. 0002-88-4) 10 mg/m3 Inhalable dust. VLK. EH40 Workplace Exposure Limits (WELs) Components Type Value Form Polyethylene (CAS 3002-88-4) TWA 4 mg/m3 Respirable dust. Polyethylene (CAS 3002-88-4) TWA 4 mg/m3 Inhalable dust. Polyethylene (CAS 3002-88-4) No biological exposure limits noted for the ingredient(s). 10 mg/m3 Inhalable dust.		TWA	·	
ComponentsTypeValueFormDISTILLATES (PETROLEUM) SOLVENT-DEWAXED HEAVY PARAFFINIC (CAS 64742-65-0)TWA5 mg/m3Inhalable fraction.Polyethylene (CAS 9002-88-4)TWA3 mg/m3Respirable dust.10 mg/m3Inhalable dust.UK. EH40 Workplace Exposure Limits (WELs) ComponentsTypeValueFormPolyethylene (CAS 9002-88-4)TWA4 mg/m3Respirable dust.UK. EH40 Workplace Exposure Limits (WELs) ComponentsTypeValueFormPolyethylene (CAS 9002-88-4)TWA4 mg/m3Respirable dust.Polyethylene (CAS 9002-88-4)TWA4 mg/m3Inhalable dust.Polyethylene (CAS 9002-88-4)TWA4 mg/m3Respirable dust.Polyethylene (CAS 9002-88-4)No biological exposure limits noted for the ingredient(s). Follow standard monitoring procedures.Inhalable dust.			2,5 mg/m3	Respirable dust.
DISTILATES TWA 5 mg/m3 Inhalable fraction. POISTILATES TWA 5 mg/m3 Inhalable fraction. SOLVENT-DEWAXED HEAVY PARAFFINIC (CAS 3 mg/m3 Respirable dust. POIsethylene (CAS TWA 3 mg/m3 Respirable dust. 9002-88-4) 10 mg/m3 Inhalable dust. UK. EH40 Workplace Exposure Limits (WELs) 10 mg/m3 Inhalable dust. Components Type Value Form Polyethylene (CAS TWA 4 mg/m3 Respirable dust. 9002-88-4) 10 mg/m3 Inhalable dust. 10 mg/m3 Polyethylene (CAS TWA 4 mg/m3 Respirable dust. 9002-88-4) No biological exposure limits noted for the ingredient(s). Foilow standard monitoring procedures.	Switzerland. SUVA Grenzy Components	•	Value	Form
(PETROLEUM) SOLVENT-DEWAXED HEAVY PARAFFINIC (CAS 54742-65-0) TWA 3 mg/m3 Respirable dust. Polyethylene (CAS 9002-88-4) TWA 3 mg/m3 Inhalable dust. UK. EH40 Workplace Exposure Limits (WELs) Components 10 mg/m3 Inhalable dust. Polyethylene (CAS 9002-88-4) TWA 4 mg/m3 Respirable dust. Polyethylene (CAS 9002-88-4) TWA 4 mg/m3 Respirable dust. Polyethylene (CAS 9002-88-4) TWA 4 mg/m3 Inhalable dust. Polyethylene (CAS 9002-88-4) TWA 4 mg/m3 Respirable dust. Polyethylene (CAS 9002-88-4) No biological exposure limits noted for the ingredient(s). Inhalable dust. Polyethylene (CAS 9002-88-4) No biological exposure limits noted for the ingredient(s). Follow standard monitoring procedures.	-	-	5 ma/m3	Inhalable fraction
Polyethylene (CAS TWA 3 mg/m3 Respirable dust. 9002-88-4) 10 mg/m3 Inhalable dust. UK. EH40 Workplace Exposure Limits (WELs) Value Form Components Type Value Form Polyethylene (CAS TWA 4 mg/m3 Respirable dust. 9002-88-4) TWA 4 mg/m3 Inhalable dust. Polyethylene (CAS TWA 10 mg/m3 Inhalable dust. Polyethylene (CAS TWA 5 mg/m3 Respirable dust. Polyethylene (CAS TWA 10 mg/m3 Inhalable dust. Polyethylene (CAS No biological exposure limits noted for the ingredient(s). Follow standard monitoring procedures. Follow standard monitoring procedures. Follow standard monitoring procedures. Follow standard monitoring procedures.	(PETROLEUM) SOLVENT-DEWAXED HEAVY PARAFFINIC (CAS			
UK. EH40 Workplace Exposure Limits (WELs) Yalue Form Components Type Value Form Polyethylene (CAS TWA 4 mg/m3 Respirable dust. 9002-88-4) 10 mg/m3 Inhalable dust. ogical limit values No biological exposure limits noted for the ingredient(s). Follow standard monitoring procedures.	Polyethylene (CAS 9002-88-4)	TWA	3 mg/m3	Respirable dust.
ComponentsTypeValueFormPolyethylene (CAS 9002-88-4)TWA4 mg/m3Respirable dust.10 mg/m3Inhalable dust.to mg/m3Inhalable dust.to mg/m3Follow standard monitoring procedures.			10 mg/m3	Inhalable dust.
Polyethylene (CAS TWA 4 mg/m3 Respirable dust. 9002-88-4) 10 mg/m3 Inhalable dust. pogical limit values No biological exposure limits noted for the ingredient(s). Follow standard monitoring procedures.	UK. EH40 Workplace Expo Components		Value	Form
9002-88-4) 10 mg/m3 Inhalable dust. ogical limit values No biological exposure limits noted for the ingredient(s). Follow standard monitoring procedures. Follow standard monitoring procedures. Follow standard monitoring procedures. Follow standard monitoring procedures.	-	-		Respirable dust.
ogical limit valuesNo biological exposure limits noted for the ingredient(s).ommended monitoring eduresFollow standard monitoring procedures.	9002-88-4)		-	
edures Follow standard monitoring procedures.	ogical limit values	No biological exposure limits poted f	-	initialable dust.
	ommended monitoring			
		Not available		

Predicted no effect concentrations (PNECs)	Not available.
8.2. Exposure controls	
Appropriate engineering controls	Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.
Individual protection measures, such as personal protective equipment	
General information	Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.
Eye/face protection	Wear safety glasses with side shields (or goggles).
Skin protection	
- Hand protection	Wear appropriate chemical resistant gloves.
- Other	Wear suitable protective clothing.
Respiratory protection	In case of insufficient ventilation, wear suitable respiratory equipment.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
Hygiene measures	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.
Environmental exposure controls	Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state	Solid.
Form	Solid. Roll.
Colour	Dark grey
Odour	Bitumen Characteristic.
Odour threshold	Not available.
рН	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.
Flash point	Not available.
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or expl	osive limits
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Vapour pressure	Not available.
Vapour density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Explosive properties	Not explosive.
Oxidising properties	Not oxidising.

9.2. Other information	
Density	0,87 g/cm3 estimated
Specific gravity	0,87 estimated

SECTION 10: Stability and reactivity

10.1. Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
10.2. Chemical stability	Material is stable under normal conditions.
10.3. Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
10.4. Conditions to avoid	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Contact with incompatible materials.
10.5. Incompatible materials	Strong oxidising agents.
10.6. Hazardous decomposition products	Carbon monoxide. Irritating and/or toxic fumes and gases may be emitted upon the product's decomposition.

SECTION 11: Toxicological information

General information Occupational exposure to the substance or mixture may cause adverse effects.

General information	occupational exposure to the substance of mixture may cause adverse enects.
Information on likely routes of ex	xposure
Inhalation	Prolonged inhalation may be harmful.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of occupational exposure.
Symptoms	Exposure may cause temporary irritation, redness, or discomfort.
11.1. Information on toxicological effects	
Acute toxicity	Not known.
Skin corrosion/irritation	Due to partial or complete lack of data the classification is not possible.
Serious eye damage/eye irritation	Due to partial or complete lack of data the classification is not possible.
Respiratory sensitisation	Due to partial or complete lack of data the classification is not possible.
Skin sensitisation	Due to partial or complete lack of data the classification is not possible.
Germ cell mutagenicity	Due to partial or complete lack of data the classification is not possible.
Carcinogenicity	Due to partial or complete lack of data the classification is not possible.
(as amended)	nance on protection against and preventing risk relating to exposure to carcinogens at work
Not listed.	
Reproductive toxicity	Due to partial or complete lack of data the classification is not possible.
Specific target organ toxicity - single exposure	Due to partial or complete lack of data the classification is not possible.
Specific target organ toxicity - repeated exposure	Due to partial or complete lack of data the classification is not possible.
Aspiration hazard	Due to partial or complete lack of data the classification is not possible.
Mixture versus substance information	No information available.
Other information	This product has no known adverse effect on human health.
SECTION 12: Ecological information	
12.1. Toxicity	Based on available data, the classification criteria are not met for hazardous to the aquatic environment.
12.2. Persistence and degradability	No data is available on the degradability of any ingredients in the mixture.
12.3. Bioaccumulative potential	No data available.
Partition coefficient n-octanol/water (log Kow)	Not available.


SECTION 13: Disposal considerations

13.1. Waste treatment methods	
Residual waste	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.
EU waste code	The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Disposal methods/information	Collect and reclaim or dispose in sealed containers at licensed waste disposal site.
Special precautions	Dispose in accordance with all applicable regulations.

SECTION 14: Transport information

ADI	2	
	14.1. UN number	UN3082
	14.2. UN proper shipping	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (DISTILLATES
	name	(PETROLEUM) SOLVENT-DEWAXED HEAVY PARAFFINIC)
	14.3. Transport hazard class	les)
	Class	9
	Subsidiary risk	-
	Label(s)	9
	Hazard No. (ADR)	90
	Tunnel restriction code	E
	14.4. Packing group	III
	14.5. Environmental hazards	
	14.6. Special precautions	Read safety instructions, SDS and emergency procedures before handling.
RID	for user	
RID		UN3077
	14.1. UN number 14.2. UN proper shipping	Environmentally hazardous substance, solid, n.o.s. (DISTILLATES (PETROLEUM)
	name	SOLVENT-DEWAXED HEAVY PARAFFINIC)
	14.3. Transport hazard class(,
	Class	9
	Subsidiary risk	-
	Label(s)	9
	14.4. Packing group	III
	14.5. Environmental hazards	Yes
	14.6. Special precautions	Read safety instructions, SDS and emergency procedures before handling.
	for user	
ADI	-	100000
	14.1. UN number	UN3082
	14.2. UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (DISTILLATES (PETROLEUM) SOLVENT-DEWAXED HEAVY PARAFFINIC)
	14.3. Transport hazard class(
	Class	9
	Subsidiary risk	-
	Label(s)	9
	14.4. Packing group	III
	14.5. Environmental hazards	Yes
	14.6. Special precautions	Read safety instructions, SDS and emergency procedures before handling.
	for user	
IAT		100000
	14.1. UN number	UN3082
	14.2. UN proper shipping name	Environmentally hazardous substance, liquid, n.o.s. (DISTILLATES (PETROLEUM) SOLVENT-DEWAXED HEAVY PARAFFINIC)
	14.3. Transport hazard class	les)
	Class	9
	Subsidiary risk	-
	14.4. Packing group	III
	14.5. Environmental hazards	Yes
	ERG Code	9L

14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only	Allowed with restrictions.
IMDG	
14.1. UN number	UN3082
14.2. UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (DISTILLATES (PETROLEUM) SOLVENT-DEWAXED HEAVY PARAFFINIC), MARINE POLLUTANT
14.3. Transport hazard class	s(es)
Class	9
Subsidiary risk	-
14.4. Packing group	III
14.5. Environmental hazards	3
Marine pollutant	Yes
EmS	F-A, S-F
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.
ADN; ADR; IATA; IMDG; RID	



Marine pollutant



General information

IMDG Regulated Marine Pollutant.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

- Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended Not listed.
- Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended Not listed.
- Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended Not listed.
- Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended Not listed.
- Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended Not listed.
- Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended

Not listed.

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA Not listed.

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended Not listed.

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.

Not listed.

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended	
Not listed.	
Other regulations	The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006, as amended.
National regulations	Follow national regulation for work with chemical agents in accordance with Directive 98/24/EC, as amended.
15.2. Chemical safety	No Chemical Safety Assessment has been carried out.

assessment

SECTION 16: Other information

List of abbreviations	Not available.
References	Not available.
Information on evaluation method leading to the classification of mixture	The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.
Full text of any H-statements not written out in full under Sections 2 to 15	None.
Revision information	None.
Training information	Follow training instructions when handling this material.
Issued by	Dan Libby
Disclaimer	The information offered in this data sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication, however, no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process. This material is intended for industrial use only. No warranty, expressed or implied is made.