



TECSOLV EB

Product Codes

Packaging listed overleaf.

Description

Tecsolv EB is a synergistic blend of aliphatic and aromatic compounds designed to solvent polyurethane and epoxy based products. Tecsolv EB may be used as a lubricating trowelling aid to achieve a smooth finish to applied resin based mortars and screeds. Mixing equipment and application tools should always be cleaned with Tecsolv EB before setting and hardening has occurred.

Uses include: Obtaining a smooth finish to applied resin based mortars and screeds.

Cleaning spillages and snots before hardening has taken place.

Cleaning of mixing and application tools. Cleaning and keying elastic bearings.

Typical Properties of Tecsolv EB

The chemical blend acts synergistically to solvent the main classes of resins used in construction Polyurethane and Epoxy.

Tecsolv EB is a clear liquid with an aromatic odour. The use of any solvent should always be carried out in a well ventilated area.

Tecsolv EB is flammable and no smoking should be allowed in the work area.

Specification Outline

Finishing and cleaning operations should be carried out using Tecsolv EB as manufactured by Parex Ltd The product must be stored and used in accordance with the manufacturer's instructions.

Quality Assurance

Parex Ltd is a firm of Assessed Capability. The Company's quality and environmental management systems conform to ISO 9001:2008 and ISO14001:2004 respectively as assessed by UK CARES LTD.

Instructions For Use

When using Tecsolv EB always wear suitable gloves and work in accordance with the health and safety advice given below and in the Safety Data Sheet.

For use as a finishing medium apply a thin coating to application tools such as trowels by means of a dampened cloth. Repeat the coating regularly as the work progresses.

For use as a cleaning up medium apply a more liberal coating to the particular areas involved and work with a cloth to remove the spills.

After use place used cloths into a sealed container for disposal.

Details are given in the Safety Data Sheet.

Storage And Shelf Life

Tecsolv EB will have a shelf life of 12 months when kept in moderate ambient conditions. Tins should be tightly closed when not in use. Storage should be in accordance with the Highly Flammable Liquids and Petroleum Gases Regulations 1972.

Packaging And Ordering

Tecsolv EB supplied in screw-cap tins: 1 litre tin Product Code TM60

For further information and sales please contact your local Parex Ltd office as listed below.

Fire

Tecsolv EB is flammable. Should fire occur extinguish with CO_2 or foam.







TECSOLV EB

Precautions Health and Safety

Tecsolv EB is classified under the health and safety legislation CHIP Regulations as "harmful". When used with care, as described in the Safety Data Sheet, Solvent is eminently suitable for site use.

Resin based products and solvents may cause allergic reactions in some people. When using Solvent with resins/hardeners wear gloves, use barrier cream on unprotected skin areas and wear eye protection when mixing, using and cleaning. Ensure adequate ventilation to prevent inhalation of vapours. If skin contact occurs remove resin/hardener immediately with cleansing cream and wash with soap and water.

Should eye contact occur rinse immediately with plenty of clean water and seek medical advice. If, with resin based products, resin/hardener or Solvent is swallowed do not induce vomiting. Seek medical advice immediately.

Keep out of water courses and avoid release to the environment.

Full health and safety data are given in Product Safety Data Sheet.

Parex Ltd products are guaranteed against defective materials and manufacture. Products are sold subject to the Parex Ltd Terms and Conditions of Sale, copies of which are forwarded on invoice and are available on request. Parex Ltd endeavours to ensure that the above data and any further advice is correct, however, it cannot accept any direct or indirect liability for the use of its products as such usage is beyond its control.

Parex Ltd, Holly Lane Industrial Estate, Atherstone, Warwickshire, CV9 2QZ Tel: 01827 711755, Fax: 01827 711330, E-mail: enquiries@parex.co.uk **www.parex.co.uk**

