

July 2018

A universal solvent-based cleaner for removing uncured epoxy and polyester resins

webertec solvent



About this product

A solvent used for cleaning tools and equipment used with resin-based products.

Technical data

webertec solvent Contains benzyl alcohol and Alcohols C9-11, ethoxylated.

Uses

- Suitable for removing uncured epoxy resins
- A general-purpose cleaning solvent for epoxy and polyester resins

Constraints:

Must not be used as a diluent for reducing the viscosity of epoxy resins.

Features and benefits

- Fast and efficient cleaning of uncured resins from tools and equipment.
- Supplied in UN-approved containers.

webertec solvent

Cleaning

All equipment should be cleaned, preferably by soaking overnight followed by wiping thoroughly with a clean cloth or brush.

Packaging

webertec solvent is supplied in 5 litre metal containers.

Storage and shelf life

Store in well ventilated conditions away from sunlight or sources of ignition in conditions between 5 and 40°C.

Ensure the container is kept well sealed.

Shelf life of unopened container in correct storage conditions is up to 12 months.

Health and safety

For further details on safe handling, please refer to the relevant Safety Data Sheet for the product.

Technical services

Weber's Customer Services Department has a team of experienced advisors available to provide on-site advice both at the specification stage and during application. Detailed specifications can be provided for specific projects or more general works. Site visits and on-site demonstrations can be arranged on request.

Technical helpline Tel: 08703 330 070 e-mail technical@netweber.co.uk

Saint-Gobain Weber

Dickens House, Enterprise Way, Maulden Road, Flitwick, Bedford MK45 5BY, UK Tel: 08703 330 070 Fax: 0800 014 2995 e-mail: mail@netweber.co.uk www.netweber.co.uk



Sales enquiries

UK and Ireland

Tel:

Fax:

e-mail

08703 330 070

0800 014 2995

sales@netweber.co.uk

Weber products are distributed throughout the

UK through selected stockists and distributors.

Please contact the relevant Customer Services

Team below for all product orders and enquiries.

To the best of our knowledge and belief this information is true and accurate, but as conditions of use and any labour involved are beyond our control, the end user must satisfy himself by prior testing that the product is suitable for his specific application, and no responsibility can be accepted, or any warranty given by our Representatives. Agents or Distributors. Products are sold subject to our Standard Conditions of Sale and the end user should ensure that he has consulted our latest literature.