



Technical Datasheet

Arbo Bond Breaker Tape

Arbo Bond Breaker Tape is a laminated polyethylene cloth tape combined with a pressure sensitive adhesive backing. The laminated polyethylene prevents sealant adhesion to ensure that the sealant does not form a three sided adhesive bond. High bond strength of the pressure sensitive adhesive ensures good adhesion to a variety of common construction substrates. Bond Breaker Tape has good conformability ensuring good adhesion to both regular and irregular surfaces.

Main Applications

Recommended for sealant joints to ensure that the sealant adheres to the two principle surfaces of the joint only. Bond breaker tape prevents adhesion to the back of the joint. Three sided adhesion can lead to sealant splitting, cracking and early joint failure.

Packaging

50m x 4.5mm 50m
x 20mm
50m x 6mm
50m x 10mm
50m x 12mm

Colours

Black

Application

All surfaces to be bonded must be clean and dry.

Shelf Life

Not applicable if product is stored in a cool, dry place out of direct sunlight.

Health and Safety.

No hazards associated with the product.

Technical Data

Thickness: 0.2 mm

Application Temperature: + 5° C to + 40° C



Page 1 of 2

First Issue: 27.08.08

Service Temperature: - 50° C to + 150° C

Tensile Strength: 110 – 115 N/25mm

Important: The information in this leaflet is given in good faith and based on results gained from experience and tests. However, all recommendations or suggestions are made without guarantee since the conditions of use are beyond our control. Goods are supplied subject to the Company's terms and conditions of sales, a copy of which is available on request.

Adshead Ratcliffe, Derby Road, Belper, Derbyshire DE56 1WJ, England.

Telephone: 01773 826661 Fax:

01773 821215

Internet: www.arbo.co.uk

