



RS Bitukold Spray is a rapid setting, cold applied bitumen emulsion designed for sealing vertical joints. The cationic formulation of **RS Bitukold Spray** ensures a rapid set even in cold, damp conditions, with an initial cure taking place within 15 minutes.

Where to use?

- Transverse and longitudinal vertical joints
- Trench reinstatements
- Patch repairs
- Drain or manhole frames
- Kerb channels

Preparation

Ensure that the surface is clean and free from loose materials, oil, grease, standing water and weeds.

Application

Shake can well and invert. Apply **RS Bitukold Spray** in even strokes with nozzle 200-300mm away from the surface to be treated. Ensure complete coverage. After use, spray briefly, with can in upright position to clear nozzle.

Coverage

The coverage rate for **RS Bitukold Spray** should be 0.7 – 1.5 kg/m², depending on the texture and porosity of the surface.

Packaging

RS Bitukold Spray is supplied in 600ml aerosol cans (12 per box).

Storage

- Caution: pressurised container, protect from sunlight
- Do not pierce or burn even after use
- Do not expose to temperatures exceeding 50°C
- Do not spray on a naked flame or any incandescent material
- Keep out of reach of children

Standards

RS Bitukold Spray complies with BS 594987 clause 6.8 Joints, vertical face coating.

Safety

For full safety information, please download the **RS Bitukold Spray Safety Data Sheet 54** from our website www.colas.co.uk



Colspray is a rapid setting, cold applied bitumen spray designed for sealing vertical joints. **Colspray** can also be used as a tack coat helping to prevent the ingress of water.

Where to use?

- Transverse or longitudinal vertical joints
- Trench reinstatements
- Patch repairs
- Drain or manhole frames
- Kerb channels

Preparation

Ensure that the surface is clean and free from loose materials, oil, grease, standing water and weeds.

Application

Shake can vigorously before use. Turn can upside down and apply **Colspray** in even strokes with nozzle 200-300mm away from the surface to be treated. Ensure complete coverage. After use spray briefly with can in upright position to clear nozzle.

Coverage

The coverage rate for **Colspray** should be 0.7 to 1.5m², depending on the texture and porosity of the surface.

Packaging

Colspray is supplied in 750ml aerosol cans (12 per pack).

Storage

- Caution: pressurised container, protect from sunlight
- Do not pierce or burn even after use
- Do not expose to temperatures exceeding 50°C
- Do not spray on a naked flame or any incandescent material
- Keep out of reach of children

Standards

Colspray complies with BS 594987 clause 6.8 joints, vertical face coating.

Safety

For full safety information, please download the **Colspray Safety Data Sheet 148** from our website www.colas.co.uk