

SAFETY DATA SHEET

according to Regulation (EU) 2015/830

Page 1/5

Larprime EU Pt A

Revision Revision date 2019-12-13

| SECTION 1: Identification of the substance/mixture and | of the company/undertaking |
|--|----------------------------|
|--|----------------------------|

1.1. Product identifier

1.2. Relevant identified uses of the substance or mixture and uses advised against

| 1.2. Projectalit Idonation decoration of this additional definition and accordance against | | | | | |
|--|---|--|--|--|--|
| Product Use | [SU22] Professional uses: Public domain (administration, education, entertainment, services, | | | | |
| | craftsmen); [SU19] Building and construction work; [PC0] Other; [PROC5] Mixing or blending in | | | | |
| | hatch processes for formulation of preparations and articles (multistage and/or significant contact | | | | |

1.3. Details of the supplier of the safety data sheet

| Company | Larsen Building Products Ltd |
|---------|------------------------------|
|---------|------------------------------|

Address 4 West Bank Road

Belfast Harbour Industrial Estate

[ERC3] Formulation in materials;

Belfast BT3 9JL United Kingdom

www.larsenbuildingproducts.com

+44 (0)28 9077 4000 **Telephone** +44 (0)28 9077 6945 Fax

Email t.moore@larsenbuildingproducts.com

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

| 2. | 1.2. | Clas | ssitic | catio | n - | E | J |
|----|------|------|--------|-------|-----|---|---|
| 12 | 72/ | 2008 | 3 | | | | |

Skin Irrit. 2: H315; Skin Sens. 1: H317; Eye Irrit. 2: H319; Aquatic Chronic 2: H411;

2.2. Label elements

Web

Hazard pictograms





Signal Word

Warning **Hazard Statement** Skin Irrit. 2: H315 - Causes skin irritation.

Skin Sens. 1: H317 - May cause an allergic skin reaction.

Eye Irrit. 2: H319 - Causes serious eye irritation.

Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.

Precautionary Statement:

P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.

Prevention

P264 - Wash thoroughly after handling.

P272 - Contaminated work clothing should not be allowed out of the workplace.

P273 - Avoid release to the environment.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary Statement:

P302+P352 - IF ON SKIN: Wash with plenty of water/ .

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact Response

Revision Revision date 2019-12-13

2.2. Label elements

lenses, if present and easy to do. Continue rinsing. P321 - Specific treatment (see on this label). P332+P313 - If skin irritation occurs: Get medical advice/attention. P333+P313 - If skin irritation or rash occurs: Get medical advice/attention. P337+P313 - If eye irritation persists: Get medical advice/attention. P391 - Collect spillage.

Precautionary Statement:

P501 - Dispose of contents/container to

Disposal

SECTION 3: Composition/information on ingredients

3.2. Mixtures

EC 1272/2008

| Chemical Name | Index No. | CAS No. | EC No. | REACH Registration Number | Conc. (%w/w) | Classification |
|-----------------------------------|--------------|------------|-----------|------------------------------|-----------------|------------------------------------|
| Bisphenol A-(epichlorhydrin) | 603-074-00-8 | 25068-38-6 | 500-033-5 | | | Eye Irrit. 2: H319; Skin Irrit. 2: |
| (reaction product) | | | | | | H315; Skin Sens. 1: H317; |
| | | | | | | Aquatic Chronic 2: H411; |
| Bisphenol F Type Epoxy Resin | | 28064-14-4 | | | | Skin Irrit. 2: H315; Skin Sens. |
| | | | | | | 1: H317; Eye Irrit. 2: H319; |
| | | | | | | Aquatic Chronic 2: H411; |
| Glycidylether of C12-C14 alcohols | | 68809-97-2 | 271-846-8 | | | Skin Irrit. 2: H315; Skin Sens. |
| | | | | | | 1: H317; Eye Irrit. 2: H319; |
| Air Release Additve | | | | | | Flam. Liq. 3: H226; Asp. Tox. |
| | | | | | | 1: H304; STOT SE 3: H335; |
| | | | | | | STOT SE 3: H336; Aquatic |
| | | | | | | Chronic 2: H411; |

SECTION 4: First aid measures

4.1. Description of first aid measures

| Inhalation | Irritating to respiratory system. Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system. Move the exposed person to fresh air. Seek medical attention. |
|--------------|---|
| Eye contact | Irritating to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist. |
| Skin contact | Irritating to skin. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist. |
| Ingestion | Ingestion may cause nausea and vomiting. Seek medical attention if irritation or symptoms persist. DO NOT INDUCE VOMITING. |

SECTION 5: Firefighting measures

5.1. Extinguishing media

Carbon oxides.

5.2. Special hazards arising from the substance or mixture

Burning produces irritating, toxic and obnoxious fumes.

5.3. Advice for firefighters

Wear suitable respiratory equipment when necessary.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation of the working area. Wear suitable protective equipment.

6.2. Environmental precautions

Do not allow product to enter drains. Prevent further spillage if safe.

6.3. Methods and material for containment and cleaning up

Revision 4
Revision date 2019-12-13

6.3. Methods and material for containment and cleaning up

Absorb with inert, absorbent material. Sweep up. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Adopt best Manual Handling considerations when handling, carrying and dispensing.

7.2. Conditions for safe storage, including any incompatibilities

Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers.

SECTION 8: Exposure controls/personal protection

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Ensure adequate ventilation of the working area.

8.2.2. Individual protection measures

Wear chemical protective clothing.

Eye / face protection

Respiratory protection

Approved safety goggles.

Skin protection - Handprotection

Chemical resistant gloves (PVC).

Wear:. Suitable respiratory equipment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Odour

Appearance Colour

Liquid Colourless

Characteristic

SECTION 10: Stability and reactivity

10.2. Chemical stability

Stable under normal conditions.

SECTION 11: Toxicological information

11.1.4. Toxicological Information

No data available

SECTION 12: Ecological information

12.1. Toxicity

No data available

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

SECTION 13: Disposal considerations

General information

Dispose of in compliance with all local and national regulations.

SECTION 14: Transport information

Hazard pictograms



Revision 4
Revision date 2019-12-13

Hazard pictograms



| -4 | 14 4 | | ш | NI. | _ | | h~" |
|----|------|-----|---|-----|-----|------|-----|
| | 4.1 | . ' | u | INI | ΙIL | 1111 | ber |

UN3082

14.2. UN proper shipping name

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

14.3. Transport hazard class(es)

| ADR/RID | 9 |
|-----------------|---|
| Subsidiary risk | - |
| IMDG | 9 |
| Subsidiary risk | - |
| IATA | 9 |
| Subsidiary risk | - |

14.4. Packing group

| Packing | aroup | Ш |
|----------------|-------|---|
| | | |

14.5. Environmental hazards

| Environmental hazards | Yes |
|-----------------------|-----|
| Marine pollutant | Yes |

ADR/RID

| Hazard ID | 90 |
|-----------------|-----|
| Tunnel Category | (E) |

IMDG

| EmS Code | F-A S-F |
|----------|---------|
|----------|---------|

IATA

| Packing Instruction (Cargo) | 964 |
|-----------------------------|-------|
| Maximum quantity | 450 L |
| Packing Instruction | 964 |
| (Passenger) | |
| Maximum quantity | 450 L |

Further information

The product is not classified as dangerous for carriage.

Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.

SECTION 15: Regulatory information

SECTION 16: Other information

Other information

| Text of Hazard Statements in | Skin Irrit. 2: H315 - Causes skin irritation. | |
|------------------------------|--|--|
| Section 3 | Skin Sens. 1: H317 - May cause an allergic skin reaction. | |
| | Eye Irrit. 2: H319 - Causes serious eye irritation. | |
| | Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects. | |
| | Flam. Liq. 3: H226 - Flammable liquid and vapour. | |

Revision 4
Revision date 2019-12-13

| Other information | | |
|---------------------|--|--|
| | STOT SE 3: H335 - May cause respiratory irritation. STOT SE 3: H336 - May cause drowsiness or dizziness. | |
| Further information | | |
| | The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process. | |

