10

Safety Data Sheet

according to Regulation (EC) No 1907/2006

	KÖSTER FS Primer 20	A	
Revision date: 20.03.2018	Product code: J139a		Page 1 of 1
SECTION 1: Identification of the	ne substance/mixture and of the compa	any/undertaking	
1.1. Product identifier			
KÖSTER FS Primer 2C A			
1.2. Relevant identified uses of th	ne substance or mixture and uses advised a	against	
Use of the substance/mixture			
The product is intended for	professional use.		
Uses advised against			
No identified use(s).			
1.3. Details of the supplier of the	<u>safety data sheet</u>		
Company name:	KOESTER BAUCHEMIE AG		
Street:	Dieselstrasse 1 - 10		
Place:	D-26607 Aurich		
Telephone:	+49-4941-9709-0	Telefax:+49-4941-9709-40	
e-mail (Contact person): Internet:	produktsicherheit@koester.eu www.koester.eu		
Responsible Department:	Forschung & Entwicklung		
1.4. Emergency telephone	+49-551-19240 (24 h, Giftinformations:	zentrum Nord)	
number:	· +		
SECTION 2: Hazards identifica	ation		

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories: Skin corrosion/irritation: Skin Irrit. 2 Serious eye damage/eye irritation: Eye Irrit. 2 Respiratory or skin sensitisation: Skin Sens. 1 Hazardous to the aquatic environment: Aquatic Chronic 2 Hazard Statements: Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction. Toxic to aquatic life with long lasting effects.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

epoxy resin (number average molecular weight <= 700), reaction product: bisphenol-A-(epichlorhydrin) Bisphenol-F-Epoxidharz (MW < 700) 1,6-Hexanediol diglycidyl ether

Signal word: Pictograms: Warning



Hazard statements

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.

according to Regulation (EC) No 1907/2006

KÖSTER FS Primer 2C A

Revision date: 20.03.2018

Product code: J139a

Page 2 of 10

Precautionary statements

	• • • • • • • • • • • • • • • • • • •
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352	IF ON SKIN: Wash with plenty of water.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P501	Dispose of contents/container to according to local regulations.

Special labelling of certain mixtures

EUH205 Contains epoxy constituents. May produce an allergic reaction.

Additional advice on labelling

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Contains epoxy constituents with an average molecular weight of 700.

Hazardous components

CAS No	Chemical name			Quantity
	EC No	REACH No		
	Classification according to Regulati	on (EC) No. 1272/2008 [CLP]		
25068-38-6	epoxy resin (number average mole (epichlorhydrin)	ct: bisphenol-A-	< 90 %	
	500-033-5	603-074-00-8		
	Eye Irrit. 2, Skin Irrit. 2, Skin Sens.	1, Aquatic Chronic 2; H319 H315 H3	17 H411	
9003-36-5	Bisphenol-F-Epoxidharz (MW < 700)			< 15 %
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens.	1, Aquatic Chronic 2; H315 H319 H3	17 H411	
16096-31-4	1,6-Hexanediol diglycidyl ether			< 15 %
	240-260-4		01-2119463471-41	
	Skin Irrit. 2, Eye Irrit. 2A, Skin Sens	. 1, Aquatic Chronic 3; H315 H319 H	317 H412	

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection! Move victim out of danger zone. In all cases of doubt, or when symptoms persist, seek medical advice.

After inhalation

Provide fresh air. Move victim to fresh air. Put victim at rest and keep warm. In case of irregular breathing or respiratory arrest provide artificial respiration. No mouth-to-mouth or mouth-to-nose resuscitation. Use Ambu bag or ventilator. If unconscious place in recovery position and seek medical advice.

After contact with skin

After contact with skin, wash immediately with polyethylene glycol, followed by plenty of water. Take off immediately all contaminated clothing and wash it before reuse. Call a doctor if you feel unwell.

according to Regulation (EC) No 1907/2006

KÖSTER FS Primer 2C A

Revision date: 20.03.2018

Product code: J139a

Page 3 of 10

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician in any case!

After ingestion

Rinse mouth immediately and drink plenty of water. Remove casualty to fresh air and keep warm and at rest. Rinse mouth thoroughly with water. Let water be drunken in little sips (dilution effect). Caution if victim vomits: Risk of aspiration! If unconscious place in recovery position and seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

Allergic reactions.

Causes tears.

Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation).

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings. Suitable extinguishing media: Water spray jet, Foam, Carbon dioxide (CO2), Dry extinguishing powder.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated:

Carbon dioxide. Carbon monoxide Gases/vapours, harmful. In case of fire and/or explosion do not breathe fumes.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment. Wear personal protection equipment. Provide adequate ventilation. Avoid contact with skin, eyes and clothes.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Avoid release to the environment. Refer to special instructions/Safety data sheets. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Disposal: see section 13.

6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

according to Regulation (EC) No 1907/2006

KÖSTER FS Primer 2C A

Revision date: 20.03.2018

Product code: J139a

Page 4 of 10

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

When using do not eat, drink, smoke, sniff. Avoid release to the environment. Keep only in the original container in a cool, well-ventilated place. Do not breathe gas/fumes/vapour/spray. People who suffer from skin sensitazion problems, asthma, allergies, chronic or recurring respiratory illnesses should not be deployed in any process using this preparation. Avoid release to the environment.

Advice on protection against fire and explosion

Usual measures for fire prevention. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Further information on handling

When using do not eat, drink, smoke, sniff. Avoid release to the environment. Keep only in the original container in a cool, well-ventilated place. Do not breathe gas/fumes/vapour/spray. Avoid release to the environment. Keep container tightly closed.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Store in a place accessible by authorized persons only. Keep container tightly closed. Keep only in the original container in a cool, well-ventilated place. Protect from sunlight.

Advice on storage compatibility

Keep away from food, drink and animal feedingstuffs.

Further information on storage conditions

Protect against: Frost.

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Additional advice on limit values

To date, no national critical limit values exist.

8.2. Exposure controls

Appropriate engineering controls

If local exhaust ventilation is not possible or not sufficient, the entire working area must be ventilated by technical means. If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Protect skin by using skin protective cream. After work, wash hands and face. When using do not eat or drink.

Eye/face protection

Suitable eye protection: goggles. Tightly sealed safety glasses.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. Suitable material: NBR (Nitrile rubber). PVC (Polyvinyl chloride). Butyl rubber. Breakthrough times and swelling properties of the material must be taken into consideration.

Skin protection

When handling with chemical substances, protective clothing with CE-labels including the four control digits must be worn. Only wear fitting, comfortable and clean protective clothing.

according to Regulation (EC) No 1907/2006

	according to Regulation (EC) No 1907/2006	
	KÖSTER FS Primer 2C A	
Revision date: 20.03.2018	Product code: J139a	Page 5 of 10
	asures are not possible or insufficient , respiratory protection must be equipment with CE-symbol including four digit test number.	
SECTION 9: Physical and chemical pro		
9.1. Information on basic physical and che Physical state: Colour:	emical properties liquid transparent	
Odour:	characteristic	
Changes in the physical state Melting point: Initial boiling point and boiling range:	not determined > 200 °C	
Flash point:	> 160 °C	
Flammability Solid: Gas: Explosive properties	not applicable not applicable	
not explosive.		
Lower explosion limits:	not determined	
Upper explosion limits:	not determined	
Auto-ignition temperature Solid: Gas: Decomposition temperature:	not applicable not applicable not determined	
Oxidizing properties	not determined	
Vapour pressure: (at 23 °C)	0,0001 hPa	
Density:	1,1 g/cm³	
Partition coefficient:	not determined	
Viscosity / dynamic: (at 23 °C)	< 1000 mPa·s	
Vapour density:	not determined	
Evaporation rate:	not determined	
9.2. Other information		

No information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

Danger of polymerisation. The product is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

according to Regulation (EC) No 1907/2006

KÖSTER FS Primer 2C A

Revision date: 20.03.2018

Product code: J139a

Page 6 of 10

No hazardous reaction when handled and stored according to provisions. Reacts with : Alkalis (alkalis). Alcohols.

10.4. Conditions to avoid

Keep away from heat. Protect against direct sunlight.

10.5. Incompatible materials

Oxidizing agents.

10.6. Hazardous decomposition products

The product is stable under storage at normal ambient temperatures. No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicocinetics, metabolism and distribution

No information available.

Acute toxicity

Based on available data, the classification criteria are not met.

No information available.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
9003-36-5	Bisphenol-F-Epoxidharz (MW < 700)				
	oral	LD50 > 23800 mg/kg	Rat		
	dermal	LD50 > 2000 mg/kg	Rabbit		

Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

Irritating to eyes. After skin contact: irritant.

Sensitising effects

May cause an allergic skin reaction. (epoxy resin (number average molecular weight <= 700), reaction product: bisphenol-A-(epichlorhydrin); Bisphenol-F-Epoxidharz (MW < 700); 1,6-Hexanediol diglycidyl ether)

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

No information available.

Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP]. Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

SECTION 12: Ecological information

12.1. Toxicity

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

according to Regulation (EC) No 1907/2006

KÖSTER FS Primer 2C A

Revision date: 20.03.2018

Product code: J139a

Page 7 of 10

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method
9003-36-5	Bisphenol-F-Epoxidharz (MW < 700)						
	Acute fish toxicity	LC50 mg/l	1,5 - 7,7		Oncorhynchus mykiss (Rainbow trout)		
	Acute algae toxicity	ErC50	220 mg/l	96 h			
	Acute crustacea toxicity	EC50 mg/l	1,1 - 3,6	48 h	Daphnia magna		

12.2. Persistence and degradability

Product is not easily biodegradable.

12.3. Bioaccumulative potential

On the basis of existing data about the elimination/degradation and bioaccumulation potential longer term damage to the environment cannot be ruled out.

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

12.6. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Classification according to Regulation (EC) No 1272/2008 [CLP]

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

Waste disposal number of waste from residues/unused products

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

· · · /	
<u>14.1. UN number:</u>	UN3082
14.2. UN proper shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxidharz MW < 700)
14.3. Transport hazard class(es):	9
14.4. Packing group:	III
Hazard label:	9

according to Regulation (EC) No 1907/2006

	KÖSTER FS Primer 2C A	
Revision date: 20.03.2018	Product code: J139a	Page 8 of 10
		Fage 8 01 10
Classification code:	M6	
Special Provisions:	274 335 601 5 L	
Limited quantity: Excepted quantity:	5L E1	
Transport category:	3	
Hazard No:	90	
Tunnel restriction code:	E	
Other applicable information (land tran E1	sport)	
Inland waterways transport (ADN)		
<u>14.1. UN number:</u>	UN3082	
14.2. UN proper shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxidharz MW < 700)	
<u>14.3. Transport hazard class(es):</u>	9	
14.4. Packing group:	III	
Hazard label:	9	
Classification code:	M6	
Special Provisions:	274 335 601	
Limited quantity:	5 L	
Excepted quantity:	E1	
Other applicable information (inland wa E1 Marine transport (IMDG)	aterways transport)	
<u>14.1. UN number:</u>	UN3082	
14.2. UN proper shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy resin MW < 700)	
<u>14.3. Transport hazard class(es):</u>	9	
14.4. Packing group:	III	
Hazard label:	9	
Marine pollutant:	1	
Special Provisions:	274, 335	
Limited quantity:	5 L	
Excepted quantity:	E1	
EmS:	F-A, S-F	
Other applicable information (marine tr E1	ransport)	
Air transport (ICAO-TI/IATA-DGR)		
<u>14.1. UN number:</u>	UN3082	
14.2. UN proper shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy resin MW < 700)	
14.3. Transport hazard class(es):	9	
14.4. Packing group:	III	
Hazard label:	9	

according to Regulation (EC) No 1907/2006

	according to Regulation (EC) No 1907/2006	
	KÖSTER FS Primer 2C A	
Revision date: 20.03.2018	Product code: J139a	Page 9 of 10
Special Provisions:	A97 A158	
Limited quantity Passenger: Passenger LQ:	30 kg G Y964	
IATA-packing instructions - Passenger: IATA-max. quantity - Passenger: IATA-packing instructions - Cargo: IATA-max. quantity - Cargo:	964 450 L 964 450 L	
Other applicable information (air trans E1 Passenger-LQ: Y964	port)	
•		
14.5. Environmental hazards		\wedge
ENVIRONMENTALLY HAZARDOUS:	yes	¥
Danger releasing substance:	SECTION 12: Ecological information	~
SECTION 7: Handling and storage SECTION 8: Exposure controls/pers 14.7. Transport in bulk according to Anne- not applicable	-	
SECTION 15: Regulatory information		
	ulations/legislation specific for the substance or mixture	<u>}</u>
EU regulatory information		
2004/42/EC (VOC):	1 % (1 g/l)	
National regulatory information		
Water contaminating class (D):	3 - highly water contaminating	
<u>15.2. Chemical safety assessment</u> Chemical safety assessments for sul	ostances in this mixture were not carried out.	
SECTION 16: Other information		
(European Agreement concerning the IMDG: International Maritime Code for IATA: International Air Transport Asso GHS: Globally Harmonized System of	ociation of Classification and Labelling of Chemicals ting Commercial Chemical Substances	

LD50: Lethal dose, 50%

Relevant H and EUH statements (number and full text)

H315 Causes skin irritation.

according to Regulation (EC) No 1907/2006

cause an allergic skin reaction.	
ses serious eye irritation.	
to aquatic life with long lasting effects.	
nful to aquatic life with long lasting effects.	
ains epoxy constituents. May produce an allergic reaction.	
	to aquatic life with long lasting effects. Inful to aquatic life with long lasting effects.

properties and establishes no contract legal rights. The receiver of our product is singulary responsible for adhering to existing laws and regulations. The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)