according to Regulation (EC) No. 1907/2006

# SikaScreed®-20 EBB Part A



Revision Date 23.07.2014

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : SikaScreed®-20 EBB Part A

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

At present there is no complete information available on identified uses. When the data becomes available, it will be integrated into the safety data sheet.

Product use : Special system.

#### 1.3 Details of the supplier of the safety data sheet

Company : Sika Österreich GmbH

Bingser Dorfstraße 23

6700 Bludenz

Telephone : +4350610

E-mail address : EHS@at.sika.com

#### 1.4 Emergency telephone number

Emergency telephone num: 0043 1 4064343 (Giftinformationszentrale Wien)

ber EHS@at.sika.com

## **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

Type of product : Mixture

## Classification (REGULATION (EC) No 1272/2008)

Skin irritation, Category 2 H315: Causes skin irritation.

Eye irritation, Category 2 H319: Causes serious eye irritation.
Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

Chronic aquatic toxicity, Category 2 H411: Toxic to aquatic life with long lasting effects.

Classification (67/548/EEC, 1999/45/EC)

Sensitising R43: May cause sensitisation by skin contact.

Irritant R36/38: Irritating to eyes and skin.

Dangerous for the environment R51/53: Toxic to aquatic organisms, may cause

long-term adverse effects in the aquatic environ-

ment.

#### 2.2 Label elements

### Labelling (REGULATION (EC) No 1272/2008)

according to Regulation (EC) No. 1907/2006

## SikaScreed®-20 EBB Part A



Revision Date 23.07.2014

Print Date 12.05.2017

Hazard pictograms :





Signal word : Warning

Hazard statements : H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : **Prevention:** 

P261 Avoid breathing dust/ fume/ gas/ mist/ va-

pours/ spray.

P273 Avoid release to the environment.

P280 Wear protective gloves/ eye protection/ face

protection.

Response:

P333 + P313 If skin irritation or rash occurs: Get medical

advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/

attention.

P391 Collect spillage.

Hazardous components which must be listed on the label:

500-033-5 reaction product: bisphenol-A-(epichlorhydrin) and epoxy resin (number)

average molecular weight <= 700)

• 271-846-8 oxirane, mono[(C12-14-alkyloxy)methyl]derivs

#### **Additional Labelling:**

Contains epoxy constituents. May produce an allergic reaction.

## 2.3 Other hazards

This mixture contains no substance considered to be persistent, bioaccumulating nor toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

### **SECTION 3: Composition/information on ingredients**

## 3.2 Mixtures

## **Hazardous components**

Chemical Name	Classification	Classification	Concentration
CAS-No.	(67/548/EEC)	(REGULATION	[%]
EC-No.		(EC) No	
Registration number		1272/2008)	
reaction product: bisphenol-A-	Xi; R36/38	Eye Irrit.2; H319	>= 25 - < 50
(epichlorhydrin) and epoxy resin (num-	R43	Skin Irrit.2; H315	
ber average molecular weight <= 700)	N; R51/53	Skin Sens.1; H317	
25068-38-6		Aquatic Chronic2;	
500-033-5		H411	

according to Regulation (EC) No. 1907/2006

# SikaScreed®-20 EBB Part A



Revision Date 23.07.2014

Print Date 12.05.2017

01-2119456619-26-XXXX			
oxirane, mono[(C12-14- alkyloxy)methyl]derivs 68609-97-2 271-846-8 01-2119485289-22-XXXX	Xi; R38 R43	Skin Irrit.2; H315 Skin Sens.1; H317	>= 2,5 - < 5
(1-methylethyl)-1,1'-biphenyl 25640-78-2 247-156-8 01-2119982993-17-XXXX Contains: diisopropyl-1,1'-biphenyl	Xn; R65 N; R50/53 Xi; R36	Eye Irrit.2; H319 Asp. Tox.1; H304 Aquatic Acute1; H400 Aquatic Chronic1; H410	>= 3 - < 5

For the full text of the R-phrases mentioned in this Section, see Section 16. For the full text of the H-Statements mentioned in this Section, see Section 16.

#### **SECTION 4: First aid measures**

### 4.1 Description of first aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Induce vomiting immediately and call a physician.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

#### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Allergic reactions

**Excessive lachrymation** 

Erythema Dermatitis

See Section 11 for more detailed information on health effects

and symptoms.

Risks : irritant effects

sensitising effects

according to Regulation (EC) No. 1907/2006

# SikaScreed®-20 EBB Part A

Print Date 12.05.2017

Revision Date 23.07.2014

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

## **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion prod- : No hazardous combustion products are known

5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Further information : Collect contaminated fire extinguishing water separately. This

> must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accord-

ance with local regulations.

#### **SECTION 6: Accidental release measures**

## 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Deny access to unprotected persons.

6.2 Environmental precautions

**Environmental precautions** : Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

### 6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

#### 6.4 Reference to other sections

according to Regulation (EC) No. 1907/2006

# SikaScreed®-20 EBB Part A

Revision Date 23.07.2014 Print Date 12.05.2017

For personal protection see section 8.

## **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

Advice on safe handling : Do not breathe vapours or spray mist. Avoid exceeding of the

given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Follow standard hygiene

measures when handling chemical products

Advice on protection against

fire and explosion

: Normal measures for preventive fire protection.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

> practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage

areas and containers

: Keep container tightly closed in a dry and well-ventilated

place. Store in accordance with local regulations.

Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

: No data available Specific use(s)

## **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

#### Components with workplace control parameters

Contains no substances with occupational exposure limit values.

## 8.2 Exposure controls

#### Personal protective equipment

Eye protection : Safety glasses with side-shields

Eye wash bottle with pure water

Hand protection : Chemical-resistant, impervious gloves complying with an ap-

according to Regulation (EC) No. 1907/2006

# SikaScreed®-20 EBB Part A



Revision Date 23.07.2014

Print Date 12.05.2017

proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufactures appailing times

facturer specifications.

Suitable for short time use or protection against splashes:

Butyl rubber/nitrile rubber gloves (0,4 mm), Contaminated gloves should be removed.

Suitable for permanent exposure:

Viton gloves (0.4 mm), breakthrough time >30 min.

Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345,

long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing

and stirring work.

Respiratory protection : No special measures required.

### **Environmental exposure controls**

General advice : Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

### **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

Appearance : paste

Colour : grey

Odour : No data available

Odour Threshold : No data available

Flash point : > 101 °C

Ignition temperature : not applicable

Lower explosion limit (Vol%) : No data available

Upper explosion limit (Vol%) : No data available

Flammability (solid, gas) : No data available

Oxidizing properties : No data available

Auto-ignition temperature : No data available

pH : Note: not applicable

according to Regulation (EC) No. 1907/2006

# SikaScreed®-20 EBB Part A

Revision Date 23.07.2014 Print Date 12.05.2017

Melting point/range / Freez-

ing point

: No data available

Boiling point/boiling range : No data available

Vapour pressure : ca.0,2 hPa

Density : ca.1,4 g/cm3

at 20 °C

Water solubility : Note: insoluble

Partition coefficient: n-

octanol/water

: No data available

Viscosity, dynamic : No data available

Viscosity, kinematic : > 20,5 mm2/s

at 40 °C

Relative vapour density : No data available

Evaporation rate : No data available

#### 9.2 Other information

No data available

### **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

#### 10.2 Chemical stability

The product is chemically stable.

## 10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

## 10.6 Hazardous decomposition products

## **SECTION 11: Toxicological information**

## 11.1 Information on toxicological effects

#### **Acute toxicity**

according to Regulation (EC) No. 1907/2006

# SikaScreed®-20 EBB Part A

Revision Date 23.07.2014



## **Components:**

reaction product: bisphenol-A-(epichlorhydrin) and epoxy resin (number average molecular

weight <= 700) :

Acute oral toxicity : LD50 Oral rat: > 5.000 mg/kg

Acute dermal toxicity : LD50 Dermal rabbit: > 20.000 mg/kg

#### Skin corrosion/irritation

#### **Product**

Causes skin irritation.

## Serious eye damage/eye irritation

#### **Product**

Causes serious eye irritation.

## Respiratory or skin sensitisation

#### **Product**

May cause an allergic skin reaction.

## Germ cell mutagenicity

### **Product**

Mutagenicity : No data available

## Carcinogenicity

## **Product**

Carcinogenicity : No data available

### Reproductive Toxicity/Fertility

Reproductive toxicity : No data available

No data available

## Reproductive Toxicity/Development/Teratogenicity

Teratogenicity : No data available

No data available

## STOT - single exposure

No data available

## STOT - repeated exposure

No data available

according to Regulation (EC) No. 1907/2006

# SikaScreed®-20 EBB Part A

Print Date 12.05.2017

Revision Date 23.07.2014

#### **Aspiration toxicity**

No data available

#### **SECTION 12: Ecological information**

#### 12.1 Toxicity

## **Components:**

(1-methylethyl)-1,1'-biphenyl:

Toxicity to daphnia and other : LC50: 0,167 mg/l, 48 h, Daphnia magna (Water flea)

aquatic invertebrates

## 12.2 Persistence and degradability

No data available

## 12.3 Bioaccumulative potential

No data available

## 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

#### **Product:**

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

#### 12.6 Other adverse effects

No data available

### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized

wherever possible.

Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe

way.

Dispose of surplus and non-recyclable products via a licensed

waste disposal contractor.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Avoid dispersal of spilled material and runoff and contact with

according to Regulation (EC) No. 1907/2006

# SikaScreed®-20 EBB Part A



Revision Date 23.07.2014

soil, waterways, drains and sewers.

: 55510 Austria - Waste catalogue

European Waste Catalogue : 08 04 09\* waste adhesives and sealants containing organic

solvents or other dangerous substances

Contaminated packaging : Completely emptied packagings can be given for recycling.

Packaging containing remains of dangerous substances, as well as packagings disposed of remains can be unharmed

eliminated in accordance with the regulations.

15 01 10\* packaging containing residues of or contaminated

by dangerous substances

## **SECTION 14: Transport information**

**ADR** 

14.1 UN number : 3082

14.2 Description of the goods ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID.

N.O.S.

(epoxy resin)

**14.3 Class** 9 14.4 Packing group Ш Classification Code M6 Labels 9 Tunnel restriction code : (E) 14.5 Environmentally hazard-: yes

IATA

14.1 UN number 3082

14.2 Description of the goods Environmentally hazardous substance, liquid, n.o.s.

(epoxy resin)

**14.3 Class** 9 14.4 Packing group Ш 9 Labels 14.5 Environmentally hazard-: yes

ous

**IMDG** 

14.1 UN number : 3082

14.2 Description of the goods ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

> N.O.S. (epoxy resin)

**14.3 Class** 9 14.4 Packing group Ш Labels 9 **EmS Number 1** F-A EmS Number 2 S-F 14.5 Marine pollutant : yes

# SikaScreed®-20 EBB Part A



Revision Date 23.07.2014

Print Date 12.05.2017

## 14.6 Special precautions for user

No data available

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code not applicable

### **SECTION 15: Regulatory information**

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Labelling according to EC Directives (1999/45/EC)

Hazard pictograms





Irritant

Dangerous for the environment

R-phrase(s) : R36/38 Irritating to eyes and skin.

R43 May cause sensitisation by skin contact.
R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

S-phrase(s) : S24 Avoid contact with skin.

S37 Wear suitable gloves.

Hazardous components which must be listed on the label:

500-033-5 reaction product: bisphenol-A-(epichlorhydrin) and epoxy resin (number

average molecular weight <= 700)

• 271-846-8 oxirane, mono[(C12-14-alkyloxy)methyl]derivs

Special labelling of certain

mixtures

: Contains epoxy constituents. See information supplied by the

manufacturer.

**Prohibition/Restriction** 

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

preparations and articles (Annex XVII)

: not applicable

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

: None of the components are listed

(=> 0.1 %).

REACH - List of substances subject to authorisation

(Annex XIV)

: not applicable

REACH Information: All substances contained in our Products are

according to Regulation (EC) No. 1907/2006

# SikaScreed®-20 EBB Part A



Revision Date 23.07.2014

- preregistered or registered by our upstream suppliers, and/or

preregistered or registered by us, and/or
excluded from the regulation, and/or
exempted from the registration.

Risk classification according

to VbF

: Exempt

Water contaminating class

(Germany)

: WGK 2 water endangering

Gemäß VwVws vom 30.Juli 2005

VOC-CH (VOCV) : 0,03 %

no VOC duties

VOC-EU (solvent) : 0,03 %

#### 15.2 Chemical Safety Assessment

This product contains substances for which Chemical Safety Assessments are still required.

#### **SECTION 16: Other information**

#### **Full text of R-Phrases**

R36 Irritating to eyes.

R36/38 Irritating to eyes and skin.

R38 Irritating to skin.

R43 May cause sensitisation by skin contact.

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in

the aquatic environment.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

R65 Harmful: may cause lung damage if swallowed.

#### **Full text of H-Statements**

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.H411 Toxic to aquatic life with long lasting effects.

#### Full text of other abbreviations

Aquatic Acute
Aquatic Chronic
Asp. Tox.
Aspiration hazard
Eye Irrit.
Skin Irrit.
Skin Sens.
Scute aquatic toxicity
Chronic aquatic toxicity
Aspiration hazard
Eye irritation
Skin irritation
Skin sensitisation

# SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

# SikaScreed®-20 EBB Part A



Revision Date 23.07.2014

Print Date 12.05.2017

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any any use and processing.

Changes as compared to previous version!