

DESCRIPTION

rbs Epoxy Primer is a two pack epoxy primer and bonding agent for concrete and masonry structures. It exhibits outstanding ease of application and provides excellent bond to both damp and dry substrates.

USES

- Primer for rbs Epoxy Lightweight Mortar.
- Adhesive to bond freshly mixed cementitious mortars on vertical, horizontal surfaces and soffits.
- Adhesive to bond cut / mitred bricks and neoprene bearing pads to concrete.
- Protective coating to exposed steel in marine environments from excessive chloride attack.
- Adhesive to pavement repair concretes in areas of high traffic loadings or exceptional circumstances.

DIRECTIONS FOR USE

Substrate Preparation:

- All substrates must be structurally sound, free from contaminants such as oil, grease and traces of other coatings, and should be free from standing water.
- Concrete should be free from laitance and lightly textured to provide mechanical key.
- For preparation of other substrates such as mild steel, galvanized steel, aluminium or timber, contact our technical department.

Mixing:

- rbs Epoxy Primer should be mixed using a slow speed drill fitted with an EPI MR2 mixer paddle, thoroughly blending the resin and hardener components until uniform.

Application:

- Application may be by tar brush or roller, brushing being essential for a damp surface when the primer must be sheared into the substrate to displace any moisture (there must be no free standing water).
- Coverage will depend on the porosity and texture of the substrate and the nature of the material to be subsequently applied.

Cleaning:

- All tools should be cleaned using a proprietary solvent-based cleaner before the material hardens.

- If the resin is allowed to set it can only be removed by mechanical means.

TECHNICAL DATA

Colour	Amber Liquid
Flash Point	>100°C
Usable life (depending on temp.)	20 minutes
Cure Time	Remains tacky for 90 mins
Tests carried out @ 20°C	
Bond to Concrete	> 3.8 N/mm ²
Pot Life	20 minutes
Temperature limitations	rbs Epoxy Primer should not be applied at temperatures below 5°C

PACKAGING

rbs Epoxy Primer is a two component material.

Pack yields	3 kg (2.75 litres)
Coverage Rate	3-5m ² /ltr as a primer for screed 5-8m ² /ltr as a primer for coating

Actual coverage rate is dependant upon surface profile, operating conditions and techniques.

STORAGE

Store in dry, cool, frost-free conditions. Under such conditions the shelf life will be at least 12 months.

HEALTH & SAFETY

When working with rbs Epoxy Primer suitable protective clothing, eye/face protection and gloves should be worn. Areas where this product is being applied must be well ventilated.

For further health and safety information, please refer to the relevant Safety Data Sheet.



building solutions

rbs Epoxy Primer

Two Pack Epoxy Primer and Bonding Agent

IMPORTANT NOTE

Whilst all reasonable care is taken in compiling technical data on the Company's products, all recommendations or suggestions regarding the use of such products are made without guarantee, since the conditions of use are beyond the control of the Company.

It is the responsibility of the customer to satisfy himself that each product is fit for the purpose for which he intends to use it, that the actual conditions of use are suitable, and that in the light of our continual research and development programme the information relating to each product has not been superseded.



Resapol 
Foundation

Every bag counts!
For more information on the Foundation,
please visit our website.
www.resapol.com