

## TECHNICAL DATA SHEET – HPC 08 NU-GUARD® AG COLOUR

### THE ONE COAT WATER WASHABLE ANTI GRAFFITI COATING

**DESCRIPTION:**

Nu-Guard AG Colour Coating is a specially formulated single pack external coating designed to give effective protection against both fly-posting and graffiti.

**ADVANTAGES:**

A one coat application where graffiti will not adhere to the surface, once dry, graffiti can be removed quick and easy by using warm soapy water.

**USES:**

Most surfaces can be protected with just one coat of Nu-Guard AG Colour, giving quick application and protection from Graffiti and fly posting.

**COLOUR RANGE:**

Any RAL Colour.

**PACK SIZE:**

Single component product, supplied in 5 litre cans.

**VOLUME SOLIDS:**

70%

**COVERAGE RATE:**

One coat @ 8-10 m<sup>2</sup> / Litre  
WFT – 125 microns  
DFT – 90 microns

**DRYING TIME:**

Touch Dry :.....1-2 Hours.  
Full Cure :.....6 Hours

**PREPARATION:**

Ensure surfaces to be treated are clean, free from contamination and dry. Application to very porous surfaces, it is advisable to apply one coat of Nu-Guard WB Concrete Sealer.

**APPLICATION:**

By brush/roller or spray.  
Apply in one heavy coat.  
Do not apply too thin.  
Should not be applied at temperatures below 5°C or when the relative humidity exceeds 85%.

**GRAFFITI REMOVAL:**

Graffiti should be removed using warm soapy water. If using a pressure washer, no more than 70bar should be used.

**EQUIPMENT CARE:**

All equipment should be cleaned with white spirit.

**STORAGE:**

Store away from direct sunlight and sources of heat. Protect from frost. Do not allow moisture into the tin.

**SHELF LIFE:**

12 months (in original sealed container).

**HEALTH & SAFETY:**

Refer to MSDS