



UNDERWATER GROUTS AND MORTARS

Rapid Set & Strength Gain
Waterproof & Set Underwater
Potable Water Approved (DWI reg.31)
Environmentally Friendly



UNDERWATER GROUTS & MORTARS

Natural Cement manufacture a range of Environmentally Friendly Mortars and Grouts suitable for a range of underwater applications.

The products are chemically resistant, waterproof and have proven to be great time savers due to their rapid strength gain and short curing times. A number of products are also DWI Reg.31 approved for potable water applications.



BENEFITS

Natural Cement products are based on a unique Natural Cement binder that has been in use for over 200 years. The products contain no chemical additives and have many benefits over alternatives including:

- Fast Setting
- Rapid Strength Gain
- Anti-Washout
- Sets Underwater
- High Chemical Resistance
- Potable Water Approved
- No Curing Period
- PH Neutral - No affect on Water
- No Free Lime
- Excellent Adhesion



APPLICATIONS

Natural Cement manufacture products suitable for a broad range of underwater applications and uses including:

- Underwater Repairs
- Concrete Repairs
- Underwater Pointing
- General work in and around Watercourses
- Leak Sealing
- Reservoirs and Water Tanks
- Environmentally Sensitive Areas
- Scour Protection
- Coastal Environments
- Underwater Grouting
- Rivers & Canals



THE RANGE

There are a broad range of Grouts and Mortars available from Natural Cement which are all based on the same unique Natural Cement binder and carry the same benefits.

Products are designed for different applications with various set times, aggregate sizes and flowable / non flowable options available.

Options are shown on the Product Selection Table on the next page.



PRODUCT SELECTION

	Set Time (Mins)	Min Depth	Max Depth	Max Aggregate	Flowable	Reg.31 Approved	Under Water
NATCEM 35	35-40	10mm	N/A	2mm	N	Y	Y
NATCEM AC	35-40	3mm	N/A	250 Micron	N	Y	Y
NATCEM D	35-45	0mm	N/A	96 Micron	Y	Y	Y
NATCEM DW	40-50	10mm	N/A	2mm	N	Y	Y
TRACKCRETE	30-35	35mm	N/A	8mm	N	N	Y
LUL RAPIDSET	08-10	2mm	N/A	250 Micron	N	N	Y
CWG Grout	35-45	10mm	N/A	2mm	Y	N	Y

Please contact our technical department on **01226 381133** or email enquiries@naturalcement.co.uk for further advice and guidance on the best solution for your project.