

rbs Injection Resin LV Kit - CrackSeal Part B

Date of compilation: 15/01/2026

Version: 2

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier: rbs Injection Resin LV Kit - CrackSeal Part B

Other means of identification: Not relevant

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses (Professional users): Adhesive for construction

Relevant uses (Industrial user): Adhesive for construction

For Professional users/Industrial user only.

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Details of the supplier of the safety data sheet:

Resapol Ltd
Unit D4, Moss Industrial Estate
Leigh, WN7 3PT, United Kingdom
Phone: +44 1942 609 001
sales@resapol.com
www.resapol.com

1.4 Emergency telephone number: +44 (0)1942 609 001 (Mon - Fri 08:00 - 17:00)

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture:

GB CLP Regulation (UK S.I. 2019/720 and UK S.I. 2020/1567):

Classification of this product has been carried out in accordance with GB CLP Regulation (UK S.I. 2019/720 and UK S.I. 2020/1567).

Aquatic Acute 1: Hazardous to the aquatic environment, acute hazard, Category 1, H400

Aquatic Chronic 1: Hazardous to the aquatic environment, long-term hazard, Category 1, H410

Eye Irrit. 2: Eye irritation, Category 2, H319

Skin Sens. 1: Sensitisation, skin, Category 1, H317

2.2 Label elements:

GB CLP Regulation (UK S.I. 2019/720 and UK S.I. 2020/1567):

Warning



Hazard statements:

Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects.

Eye Irrit. 2: H319 - Causes serious eye irritation.

Skin Sens. 1: H317 - May cause an allergic skin reaction.

Precautionary statements:

P273: Avoid release to the environment.

P280: Wear protective gloves/protective clothing/eye protection.

P302+P352: IF ON SKIN: Wash with plenty of soap and water.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333+P313: If skin irritation or rash occurs: Get medical advice/attention.

P501: Dispose of contents/ container in accordance with local/regional/national/international regulation.

Substances that contribute to the classification

Dibenzoyl peroxide

2.3 Other hazards:

Product does not meet PBT/vPvB criteria

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Not relevant

rbs Injection Resin LV Kit
- CrackSeal Part B

Date of compilation: 15/01/2026 Version: 2

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)

3.2 Mixture:

Chemical description: Mixture composed of additives, pigments and resins

Components:

In accordance with Annex II of The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020, the product contains:

Identification	Chemical name/Classification	Concentration
CAS: 94-36-0 EC: 202-327-6 REACH: 01-2119511472-50-XXXX	Dibenzoyl peroxide Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Eye Irrit. 2: H319; Org. Perox. B: H241; Skin Sens. 1: H317 - Danger	 10 - <25 %
CAS: 1333-86-4 EC: 215-609-9 REACH: 01-2119384822-32-XXXX	Carbon black Carc. 2: H351 - Warning	 0.1 - <0.5 %

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

Other information:

Identification	M-factor	
Dibenzoyl peroxide CAS: 94-36-0	Acute	10
	Chronic	10
Identification	Specific concentration limit	
Dibenzoyl peroxide CAS: 94-36-0	% (w/w) >=52: Org. Perox. B - H241 35<= % (w/w) <52: Org. Perox. D - H242	

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

This product does not contain substances classified as hazardous for inhalation, however, in case of symptoms of intoxication remove the person affected from the exposure area and provide with fresh air. Seek medical attention if the symptoms get worse or persist.

By skin contact:

May cause an allergic skin reaction. In case of contact it is recommended to clean the affected area thoroughly with water and neutral soap. In case of changes on the skin (stinging, redness, rashes, blisters), seek medical advice with this Safety Data Sheet

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

In case of consumption, seek immediate medical assistance showing the SDS for the product.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Not relevant

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

Product is non-flammable under normal conditions of storage, handling and use. In the case of combustion as a result of improper handling, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems.

Unsuitable extinguishing media:

rbs Injection Resin LV Kit
- CrackSeal Part B

Date of compilation: 15/01/2026 Version: 2

SECTION 5: FIREFIGHTING MEASURES (continued)

Non-applicable

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and Self Contained Breathing Apparatus. Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...)

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Sweep up and shovel product or collect by other means and place in container for reuse (preferred) or disposal

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Sweep up and shovel product or collect by other means and place in container for reuse (preferred) or disposal

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks with regards manually handling weights. Maintain order, cleanliness and dispose of using safe methods (section 6).

B.- Technical recommendations for the prevention of fires and explosions

Due to its non-inflammable nature, the product does not present a fire risk under normal conditions of storage, handling and use.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Preferably use aspiration for cleaning. Given the danger of the product by inhalation, any cleaning method that involves exposure to the product in this way (sweeping, etc.) is not recommended

7.2 Conditions for safe storage, including any incompatibilities:

A.- Specific storage requirements

Minimum Temp.: 5 °C

Maximum Temp.: 25 °C

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

rbs Injection Resin LV Kit
- CrackSeal Part B

Date of compilation: 15/01/2026

Version: 2

SECTION 7: HANDLING AND STORAGE (continued)

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be assessed in the workplace:

EH40/2005 Workplace exposure limits, fourth edition, published 2020:

Identification	Occupational exposure limits	
	WEL (8h)	10 mg/m ³
Glycerol CAS: 56-81-5	WEL (15 min)	
Carbon black CAS: 1333-86-4	WEL (8h)	3.5 mg/m ³
Zinc distearate CAS: 557-05-1	WEL (15 min)	7 mg/m ³
Dibenzoyl peroxide CAS: 94-36-0	WEL (8h)	4 mg/m ³
	WEL (15 min)	20 mg/m ³
	WEL (8h)	5 mg/m ³
	WEL (15 min)	

Nuisance dust: Inhalable dust 10 mg/m³ // Respirable dust 4 mg/m³

DNEL (Workers):

Identification	Short exposure		Long exposure	
	Systemic	Local	Systemic	Local
Dibenzoyl peroxide CAS: 94-36-0 EC: 202-327-6	Oral	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	13.3 mg/kg
	Inhalation	Not relevant	Not relevant	39 mg/m ³

DNEL (General population):

Identification	Short exposure		Long exposure	
	Systemic	Local	Systemic	Local
Dibenzoyl peroxide CAS: 94-36-0 EC: 202-327-6	Oral	Not relevant	Not relevant	2 mg/kg
	Dermal	Not relevant	Not relevant	Not relevant
	Inhalation	Not relevant	Not relevant	Not relevant

PNEC:

Identification				
	STP	0.35 mg/L	Fresh water	0.00002 mg/L
Dibenzoyl peroxide CAS: 94-36-0 EC: 202-327-6	Soil	0.003 mg/kg	Marine water	0.000002 mg/L
	Intermittent	0.000602 mg/L	Sediment (Fresh water)	0.013 mg/kg
	Oral	Not relevant	Sediment (Marine water)	0.001 mg/kg

8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<UKCA marking>> or <<CE marking>>. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

Pictogram	PPE	Remarks
 Mandatory respiratory tract protection	Filter mask for gases and vapours (Filter type: P2/FFP2)	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

C.- Specific protection for the hands

rbs Injection Resin LV Kit
- CrackSeal Part B

Date of compilation: 15/01/2026

Version: 2

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Pictogram	PPE	Remarks
	Protective gloves against minor risks	Replace gloves in case of any sign of damage. For prolonged periods of exposure to the product for professional users/industrials, we recommend using CE III gloves in line with standards EN ISO 21420:2020 and EN ISO 374-1:2016+A1:2018

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection

Pictogram	PPE	Remarks
	Panoramic glasses against splash/projections.	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection

Pictogram	PPE	Remarks
	Work clothing	Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 6529:2013, EN ISO 6530:2005, EN ISO 13688:2013, EN 464:1994.
	Anti-slip work shoes	Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 20345:2022 y EN 13832-1:2019

F.- Additional emergency measures

It is advised to implement additional emergency equipments in workplaces that are particularly exposed to the product or in situations where risk assessments highlight the necessity of such equipments.

Emergency measure	Standards	Emergency measure	Standards
	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011		DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

Environmental exposure controls:

To comply with environmental protection regulations, it is recommended to prevent any spillage of the product and its container. For more detailed information, please refer to subsection 7.1.D.

The Volatile Organic Compounds in Paints, Varnishes and Vehicle Refinishing Products Regulations 2012:

V.O.C. (Supply): 0 % weight

V.O.C. density at 21 °C: 0 kg/m³ (0 g/L)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C: Solid

Appearance: Paste

Colour: Black

Odour: Characteristic

Odour threshold: Not relevant *

Volatility:

*Not relevant due to the nature of the product, not providing information property of its hazards.

rbs Injection Resin LV Kit
- CrackSeal Part B

Date of compilation: 15/01/2026 Version: 2

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Boiling point at atmospheric pressure: Not relevant *

Vapour pressure at 21 °C: Not relevant *

Vapour pressure at 50 °C: Not relevant *

Evaporation rate at 21 °C: Not relevant *

Product description:

Density at 21 °C: Not relevant *

Relative density at 21 °C: 1.55

Dynamic viscosity at 21 °C: Not relevant *

Kinematic viscosity at 21 °C: Not relevant *

Kinematic viscosity at 40 °C: >20.5 mm²/s

Concentration: Not relevant *

pH: 6 (at 10 %)

Vapour density at 21 °C: Not relevant *

Partition coefficient n-octanol/water 21 °C: Not relevant *

Solubility in water at 21 °C: Not relevant *

Solubility properties: Miscible

Decomposition temperature: Not relevant *

Melting point/freezing point: Not relevant *

Flammability:

Flash Point: Not relevant *

Flammability (solid, gas): Not relevant *

Autoignition temperature: >435 °C

Lower flammability limit: Not relevant *

Upper flammability limit: Not relevant *

Explosive (Solid):

Lower explosive limit: Not relevant *

Upper explosive limit: Not relevant *

Particle characteristics:

Median equivalent diameter: Not relevant *

9.2 Other information:

Information with regard to physical hazard classes:

Explosive properties: Not relevant *

Oxidising properties: Not relevant *

Corrosive to metals: Not relevant *

Heat of combustion: Not relevant *

Aerosols-total percentage (by mass) of flammable components: Not relevant *

Other safety characteristics:

Surface tension at 21 °C: Not relevant *

Refraction index: Not relevant *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

rbs Injection Resin LV Kit
- CrackSeal Part B

Date of compilation: 15/01/2026 Version: 2

SECTION 10: STABILITY AND REACTIVITY (continued)

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Heating may cause a fire or explosion	Avoid direct impact	Not applicable

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Precaution	Avoid alkalines, heavy metals, reducing agents, peroxide accelerating agents

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for consumption. For more information see section 3
- Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for skin contact. For more information see section 3.
- Contact with the eyes: Produces eye damage after contact.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with carcinogenic effects. For more information see section 3.
IARC: Glass, oxide, chemicals (1); Carbon black (2B); Dibenzoyl peroxide (3)
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
- Skin: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.

rbs Injection Resin LV Kit
- CrackSeal Part B

Date of compilation: 15/01/2026

Version: 2

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

F- Specific target organ toxicity (STOT) - single exposure:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

Not relevant

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
Dibenzoyl peroxide CAS: 94-36-0 EC: 202-327-6	LD50 oral	7710 mg/kg	Rat
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation dust	>5 mg/L	
Carbon black CAS: 1333-86-4 EC: 215-609-9	LD50 oral	>2000 mg/kg	
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation dust	>5 mg/L	

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

Very toxic to aquatic life with long lasting effects.

12.1 Toxicity:

Acute toxicity:

Identification	Concentration		Species	Genus
Dibenzoyl peroxide CAS: 94-36-0 EC: 202-327-6	LC50	0.0602 mg/L (96 h)	Oncorhynchus mykiss	Fish
	EC50	0.11 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	0.071 mg/L (72 h)	Pseudokirchneriella subcapitata	Algae
Carbon black CAS: 1333-86-4	LC50	1000 mg/L (96 h)	Brachydanio rerio	Fish
	EC50	5600 mg/L (24 h)	Daphnia magna	Crustacean
	EC50	Not relevant		

Chronic toxicity:

Identification	Concentration		Species	Genus
Dibenzoyl peroxide CAS: 94-36-0	NOEC	>0.01 - 0.1 mg/L		Fish
	NOEC	>0.01 - 0.1 mg/L		Crustacean

12.2 Persistence and degradability:

Substance-specific information:

Identification	Degradability		Biodegradability	
Dibenzoyl peroxide CAS: 94-36-0 EC: 202-327-6	BOD5	Not relevant	Concentration	Not relevant
	COD	Not relevant	Period	10 days
	BOD5/COD	Not relevant	% Biodegradable	68 %

12.3 Bioaccumulative potential:

Not relevant

12.4 Mobility in soil:

**rbs Injection Resin LV Kit
- CrackSeal Part B**

Date of compilation: 15/01/2026 Version: 2

SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Absorption/desorption		Volatility	
Dibenzoyl peroxide CAS: 94-36-0	Koc	6309.57	Henry	Not relevant
	Conclusion	Immobile	Dry soil	Not relevant
	Surface tension	Not relevant	Moist soil	Not relevant

12.5 Results of PBT and vPvB assessment:

Product does not meet PBT/vPvB criteria

12.6 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class
08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances	Hazardous

Type of waste:

HP14 Ecotoxic, HP13 Sensitising

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance The Waste (England & Wales) Regulations 2011, 2011 No. 988. As under 15 01 of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-hazardous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:


In accordance with Annex II of UK REACH the provisions related to waste management are stated:

UK legislation: The Waste (England & Wales) Regulations 2011.

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2023 and RID 2023:



14.1 UN number:	UN3077
14.2 UN proper shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Dibenzoyl peroxide)
14.3 Transport hazard class(es):	9
Labels:	9
14.4 Packing group:	III
14.5 Environmental hazards:	Yes
14.6 Special precautions for user	
Tunnel restriction code:	-
Physico-Chemical properties:	see section 9
Limited quantities:	5 kg
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:	Not relevant

Transport of dangerous goods by sea:

With regard to IMDG 41-22:

**rbs Injection Resin LV Kit
- CrackSeal Part B**

Date of compilation: 15/01/2026

Version: 2

SECTION 14: TRANSPORT INFORMATION (continued)



14.1 UN number:	UN3077
14.2 UN proper shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Dibenzoyl peroxide)
14.3 Transport hazard class(es):	9
Labels:	9
14.4 Packing group:	III
14.5 Marine pollutant:	Yes
14.6 Special precautions for user	
Special regulations:	335, 966, 274, 967, 969
EmS Codes:	F-A, S-F
Physico-Chemical properties:	see section 9
Limited quantities:	5 kg
Segregation group:	Not relevant
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:	Not relevant

Transport of dangerous goods by air:

With regard to IATA/ICAO 2025:



14.1 UN number:	UN3077
14.2 UN proper shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Dibenzoyl peroxide)
14.3 Transport hazard class(es):	9
Labels:	9
14.4 Packing group:	III
14.5 Environmental hazards:	Yes
14.6 Special precautions for user	
Physico-Chemical properties:	see section 9
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:	Not relevant

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

- Substances listed in UK candidate list of substances of very high concern (SVHCs): Not relevant
- Substances listed in UK REACH Authorisation List (Annex 14): Not relevant

The Control of Major Accident Hazards Regulations 2015:

Section	Description	Lower-tier requirements	Upper-tier requirements
E1	ENVIRONMENTAL HAZARDS	100	200

Restrictions to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII UK REACH, etc):

Not relevant

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020.

The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations 2020.

Control of Substances Hazardous to Health Regulations 2002 (as amended)

EH40/2005 Workplace exposure limits.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

- CONTINUED ON NEXT PAGE -

rbs Injection Resin LV Kit
- CrackSeal Part B

Date of compilation: Version: 2

SECTION 16: OTHER INFORMATION (continued)

This safety data sheet has been designed in accordance with ANNEX II-The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020.

Texts of the legislative phrases mentioned in section 2:

H319: Causes serious eye irritation.

H317: May cause an allergic skin reaction.

H400: Very toxic to aquatic life.

H410: Very toxic to aquatic life with long lasting effects.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

GB CLP Regulation (UK S.I. 2019/720 and UK S.I. 2020/1567):

Aquatic Acute 1: H400 - Very toxic to aquatic life.

Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects.

Carc. 2: H351 - Suspected of causing cancer.

Eye Irrit. 2: H319 - Causes serious eye irritation.

Org. Perox. B: H241 - Heating may cause a fire or explosion.

Skin Sens. 1: H317 - May cause an allergic skin reaction.

Classification procedure:

Eye Irrit. 2: Calculation method

Skin Sens. 1: Calculation method

Aquatic Acute 1: Calculation method

Aquatic Chronic 1: Calculation method

Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

<http://echa.europa.eu>

<http://eur-lex.europa.eu>

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5day biochemical oxygen demand

BCF: Bioconcentration factor

LD50: Lethal Dose 50

LC50: Lethal Concentration 50

EC50: Effective concentration 50

LogPOW: Octanol/water partition coefficient

Koc: Partition coefficient of organic carbon

UFI: unique formula identifier

IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at UK, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.